



Electrolux
PROFESSIONAL

Genuine Replacement Parts Catalogue 2022

www.electroluxprofessional.com

INDEX

Genuine Replacement Parts Catalogue

Cooking

Piezo electric igniters and wires	1
Pilot burners 100 series	2
Pilot burners 140 series	3
Pilot burners 160 series	4
Pilot burners 190 series	5
Pilot burners	6
Accessories for pilot burners 160 series	8
Accessories for pilot burners 140 series	9
Accessories for pilot burners 100-190 series	11
Spark plugs	14
Static oven door hinges	16
Water column	17
2 positions	19
3 positions	20
4 positions	21
5 positions	23
6 positions	23
7 positions	24
Miscellaneous switches	25
Lighting	27
Terminal block electrical connections	29
Screw electrical connections	31
Heating elements	33
Feet	35
Castors	37
Accessories for castors/wheels	41
Water drain and inlet taps	42
Safety and thermostatic	46
Gas tap accessories	48
M8x1 series	52
M9x1 series	52
Threaded series	53
M8x1 Quick series	53
M9x1 Quick series	53
"Quick" series M10x1	54
"Interrupted thermocouples" series	54
"Generic" series	55
Thermocouple accessories	56
Single-phase	57
Three-phase	60
Single-phase	62
Three-phase	65
Flexible gas pipes - UNI-EN14800 compliant	69
Flexible-extensible gas pipes - UNI-11353 compliant	70
MINISIT series	71
EUROSIT series	72
MINISIT, EUROSIT accessories	73

ELETTROSIT series	75
NOVA series	75
TANDEM-SIGMA series	76
ELETTROSIT, NOVA, TANDEM, SIGMA accessories	77
MERTIK series	79
MERTIK accessories	80
Valves for water, gas and steam	84
Extractor fans, regulators and filters	86

Refrigeration

Hermetic condensing units	90
Hermetic compressors	94
Digital temperature controllers	105
Temperature controller accessories	108
Anti-acid filter driers	111
Thermostatic valves and orifices	113
Fans and timers	116
Cold room accessories	117

Dishwashing

Contactors	118
Internal dispensers for dishwashers	124
Accessories for internal dispensers	125
External dispensers for dishwashers	126
Accessories for external dispensers	128
Faston connection	130
P5 connection	131
Brass solenoid valves - 2-way	133
Coils for solenoid valves	136
Spare parts - taps and valves	137
Traps - drains - overflows	138
Water inlet and drain hoses	140
Pressure switch - 1 level	144
Pressure switch - 2 levels	146

Water treatment

Automatic water softeners	147
Manual water softeners	151
Water softeners consumables	152
Purity C Quell ST	154
Purity C Quell ST System accessories and replacement cartridges	155
Purity STEAM for OVENS	157
Purity STEAM System accessories and replacement cartridges	157
Purity C STEAM for ovens	158
Accessories Purity C STEAM for ovens and replacement cartridges	158
Purity Clean and Clean Extra	159
Purity CLEAN and CLEAN EXTRA System accessories and replacement cartridges	160
Purity AquaQuell System accessories and replacement cartridges	160
Reverse osmosis filtration system with atmospheric boiler	161
Spare parts for reverse osmosis filter RO600C	162

Work tools and chemical products






Work tools	164
Maintenance stickers	165
Gas measuring instruments	165
Pocket Testo series	167
Refrigeration measuring instruments	167
Electricity measuring instruments-miscell	169
Water analysis	172
Electrolux Professional SkyLine ovens chemicals	174
Electrolux Professional chemicals for professional ovens	175
Electrolux Professional chemicals	175
Detergents and Rinse Aids	177
Degreasing and descaling products	178
Greases	179
Sealants and insulators	181
Oil for vacuum packaging machines	183

Piezo electric igniters and wires



Code	Spare Part Description	Picture
0C9240	Piezoelectric igniter complete with rubber cap male faston Ø 2.4 mm for Ø 18 mm hole	
0C9409	Rubber cap for piezo complete with washer	
0C8410	Piezo igniter Model MINISIT with cover Faston for ignition 6.35x0.8 mm	
0H6070	Piezo igniter VERNITRON Male faston Ø 2.4 mm For Ø 22 mm hole	
0C7190	Ignition cable for Mertik valves L=1550 mm faston for ignition Ø 2.4 mm faston for spark plug Ø 4 mm	
005559	Ignition cable; L=1000 mm faston for ignition Ø 2.4 mm faston for spark plug Ø 2.4 mm	
0C9198	Ignition cable L=710 mm faston for ignition Ø 2.4 mm faston for spark plug Ø 4 mm silicone rubber tube	
058225	Piezo electric igniter "Junkers"	
0C8450	Piezo igniter Model MINISIT Male faston Ø 2.4 mm For Ø 22 mm hole	



Piezo electric igniters and wires





Code	Spare Part Description	Picture
059578	Ignition cable L= 500 mm faston for ignition Ø 2.4 mm faston for spark plug Ø 4 mm	
004943	Ignition cable L= 600 mm faston for ignition Ø 2.4 mm faston for spark plug Ø 4 mm	
054273	Ignition cable; L=1000 mm faston 6.35x0.8 mm for ignition faston Ø 4 mm for spark plug	
0C0298	Ignition cable L= 500 mm faston 2 mm	
002544	Ignition cable L= 1000 mm; faston for ignition Ø 2.4 mm faston for spark plug Ø 4 mm; permanent temperature 200 °C	

Pilot burners 100 series



Code	Spare Part Description	Picture
027073	1-flame pilot burner, nozzle Ø 0.20 mm 100 series	
004946	2-flame pilot burner multigas with nozzle Ø 0.20 mm complete with bracket, 3 positions	



Pilot burners 100 series


Code	Spare Part Description	Picture
004216	3-flame pilot burner, nozzle Ø 0.20 mm 100 series	
029776	2-flame pilot burner, nozzle Ø 0.20 mm 100 series	
054335	3-flame pilot burner complete with bracket, 3 positions nozzle Ø 0.20 mm 100 series	
0H6338	Pilot burner supplied with head and gasket	

Pilot burners 140 series






Code	Spare Part Description	Picture
059379	Pilot burner "Target" 140 series	
0C7102	Pilot burner 140 series Supplied without spark plug, nozzle and gasket	



Pilot burners 140 series




Code	Spare Part Description	Picture
059214	Pilot burner 140 series For cooking HD 900 Supplied without nozzle	

Pilot burners 160 series





Code	Spare Part Description	Picture
0A2472	1-flame pilot burner 160 series Supplied without spark plug, nozzle and gasket	
003204	2-flame pilot burner, pressed LH Supplied without spark plug, nozzle and gasket	
0H6336	3-flame pilot burner, pressed supplied without spark plug, nozzle and gasket	
058383	2-flame pilot burner, pressed RH 160 series	
057411	3-flame pilot burner 160 series	



Pilot burners 160 series




Code	Spare Part Description	Picture
0C0744	3-flame pilot burner 160 series Supplied without nozzle	
058146	3-flame pilot burner 160 series	
0C3770	Gasket for pilot (pack of 5 pcs)	

Pilot burners 190 series




Code	Spare Part Description	Picture
020152	3-flame pilot burner, nozzle Ø 0.20 mm 190 series	
058329	3-flame pilot burner, nozzle Ø 0.35 mm. 190 series	
052246	Bracket 2 positions 052246 + 052256 to be ordered together	
052256	Bracket 2 positions 052246 + 052256 to be ordered together	



Pilot burners 190 series

Code	Spare Part Description	Picture
002783	3-flame pilot burner Supplied without spark plug and nozzle	
051624	3-flame pilot burner, nozzle Ø 0.25 mm. 190 series	
056751	3-flame pilot burner, nozzle Ø 0.35 mm. 190 series	

Pilot burners

Code	Spare Part Description	Picture
0C3644	Pilot burner For N700 and N900 Supplied without nozzle	
0C5534	M4x10 s/steel screws for modular cooking pilot fastening N900 Pack 30pcs	
0H6342	Upper pilot burner	






Pilot burners




Code	Spare Part Description	Picture
0G2024	Pilot burner body lower part	
0H6343	Pilot burner mount	
052280	Pilot blowpipe dim. mm 49x35h	
054032	3-flame pilot burner	
0H6316	Pilot burner body lower LPG	
0H6645	Gasket	
059301	Pilot blowpipe dim. mm 40x40h	



Pilot burners

Code	Spare Part Description	Picture
0A5441	Pilot blowpipe dim. mm 64x40h	
003328	Pilot blowpipe dim. mm 65x39.5h	
006128	Pilot blowpipe dim. mm 88x41h	

Accessories for pilot burners 160 series


Code	Spare Part Description	Picture
054593	Pilot nozzle Ø 0.25 LPG	
053667	Pilot nozzle Ø 0.30 LPG	
053670	Pilot nozzle Ø 0.41 GN	



Accessories for pilot burners 160 series

Code	Spare Part Description	Picture
053668	Pilot nozzle Ø 0.51 GN	
052125	Union screw for the connection of pipe Ø 4mm; thread M10x1	
0C0121	Connector for thermocouple M10x1 Ø 6,5 mm	
053665	Pilot double cone for pipe Ø 4mm	
057960	Connector for fixing spark plug	

Accessories for pilot burners 140 series

Code	Spare Part Description	Picture
059216	Pilot nozzle Ø 0.14 LPG	
0S2469	Pilot nozzle Ø 0.19 GPL	



Accessories for pilot burners 140 series

Code	Spare Part Description	Picture
059215	Pilot nozzle Ø 0.27 GN	
057960	Connector for fixing spark plug	
052125	Union screw for the connection of pipe Ø 4mm; thread M10x1	
0C0121	Connector for thermocouple M10x1 Ø 6,5 mm	
059161	Pilot double cone TARGET Ø 4mm	
003863	Pilot double cone TARGET Ø 6mm	
003859	NUT; SET 10PCS	

Accessories for pilot burners 100-190 series

Code	Spare Part Description	Picture
052281	Pilot body with nozzle Ø 0.25 mm	
052686	Pilot body with nozzle Ø 0.35 mm	
006725	Pilot body with nozzle Ø 0.40 mm	
056799	Pilot nozzle Ø 0.20 LPG	
058330	Pilot nozzle Ø 0.25 LPG	
058525	Pilot nozzle Ø 0.30 GN	
056656	Pilot nozzle Ø 0.35 GN	



Accessories for pilot burners 100-190 series

Code	Spare Part Description	Picture
056578	Pilot nozzle Ø 0.30 GN	
056750	Pilot nozzle Ø 0.20 LPG	
0H6050	Pilot head	
052833	Connector and double cone Ø 4 mm	
052834	Connector and double cone Ø 6 mm	
052125	Union screw for the connection of pipe Ø 4mm; thread M10x1	
0G2223	Connection for pipe Ø 12 mm	






Accessories for pilot burners 100-190 series




Code	Spare Part Description	Picture
050682	Double cone for pipe Ø 12 mm	
0C6621	Pilot nozzle Ø 0.21 LPG	
054286	Pilot nozzle Ø 0.25 LPG	
054037	Pilot nozzle Ø 0.25 GN	
054038	Pilot nozzle Ø 0.45 GN	
053667	Pilot nozzle Ø 0.30 LPG	



Accessories for pilot burners 100-190 series










Code	Spare Part Description	Picture
053670	Pilot nozzle Ø 0.41 GN	
053668	Pilot nozzle Ø 0.51 GN	
053665	Pilot double cone for pipe Ø 4mm	

Spark plugs

Code	Spare Part Description	Picture
052610	Spark plug; Ø 6mm L=44mm, H=35 mm, connection M4x1mm	
059380	Spark plug; Ø 6mm L=44mm, H=26.4 mm connection M4x1mm	
054336	Spark plug; Ø 6mm L=44mm, connection Ø 2.4mm	






Spark plugs





Code	Spare Part Description	Picture
0A2164	Spark plug; Ø7/10mm L=52 mm	
002637	Spark plug Ø 9 x 60 mm connection Ø 6 mm	
004970	Spark plug Ø 6 x 32 mm cable with sheath L=750 mm connection Ø 2.5 mm	
056754	Spark plug; Ø 6mm L=44mm, connection M4x1 mm	
054099	Spark plug; Ø 5+8mm L=52mm, connection faston 2.8x0.8mm	
002344	Spark plug Ø 9 x 60mm connection Ø 6 mm	
0H6803	Spark plug; Ø 9mm L=60 mm, connection Ø 6mm	
003556	Spark plug; Ø 9mm L=60 mm, connection faston Ø 6mm	
0A5169	Flame detection plug Ø 9x 62 mm with cable 900 mm	



Spark plugs


Code	Spare Part Description	Picture
006023	Wires for plugs ovens FCV/G 10 1/1	
006024	Wires for plugs ovens FCV/G 10 2/1	
002638	Flame detection plug; Ø 9mm L=60 mm, connection faston Ø 4mm	

Static oven door hinges






Code	Spare Part Description	Picture
059227	Oven hinge complete with roller holder base for HD900	
0A2005	Oven door RH hinge with roller holder for model ECO 70, ECO 90	
0C0203	Oven hinge complete with roller holder base for N700 and N900	
050766	Oven hinge complete with roller holder base for R700, MD700, PR700, H900	



Static oven door hinges

Code	Spare Part Description	Picture
0A2004	Oven door LH hinge with roller holder for model ECO 70, ECO 90	

Water column

Code	Spare Part Description	Picture
OC9108	Adjustable water column for cooker 700-900 series complete with fixing plate (extension pipes not included) H=700	
OS0350	Adjustable water column with horizontal tap swivel spout 250 mm Complete with: gaskets, washer and locknuts H= 550 mm	
OS0134	Tap valve 1/2" for single/double hole group and water column code OS0350 broach connection 8x20	
OS0977	Knob broach connection 8x20	
OC5240	Extension for water column 900 series dim. Ø 1/2" G x 244 mm dim. Ø 1/2" G x 394 mm	



Water column







Code	Spare Part Description	Picture
0C5241	Extension for water column 700 series dim. Ø 1/2" G x 173 mm dim. Ø 1/2" G x 698 mm	
025260	Knob square connection 7x7 mm thread 1/2"	
0C6826	External mount for water column 700-900 series dim. 44x55x266 h mm	
0C3108	Water column tap kit with 200 mm complete with valve square connection 7x7 thread 1/2" spout tap	
058967	Spout Ø 18x200 mm	
0S0719	Spout Ø 18x300 mm	
0C2963	Tap valve square connection 7x7 thread 1/2" for HD900 (2005)	
0S0948	French O-Ring R12 (lot 50pcs)	

2 positions


Code	Spare Part Description	Picture
003142	Cam switch 0-1 pos 2 control positions - 2 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23mm faston connectors 6.3x0.8mm	
OK8420	Cam switch 0-1 pos 2 control positions - 2 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23mm screw connections	
0A2036	Cam switch 0-1 pos 2 control positions - 2 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23mm faston connectors 6.3x0.8mm rear hole for thermostat	
0H6688	Cam switch 0-1 pos 2 control positions - 2 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23mm faston connectors 6.3x0.8mm	
028390	Cam switch 0-1 pos 2 control positions - 2 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23mm screw connections	
032677	Cam switch 0-1 pos 2 control positions - 4 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23mm faston connectors 6.3x0.8mm	
026945	Cam switch 0-1 pos 2 control positions - 4 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23mm screw connections rear hole for thermostat	
0A2134	Cam switch 0-1 pos auxiliary 2 control positions - 4 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23mm faston connectors 6.3x0.8mm	



2 positions



Code	Spare Part Description	Picture
058125	Cam switch 0-1 pos auxiliary 2 control positions - 2 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23mm faston connectors 6.3x0.8mm	
048271	Cam switch 0-1-2 pos 3 control positions - 3 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 26mm faston connectors 6.3x0.8mm	
054375	Cam switch 0-1 pos auxiliary 2 control positions - 2 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23mm faston connectors 6.3x0.8mm	
006649	Cam switch 0-1 pos 2 control positions - 4 poles contacts with rating 32A-250V D shaft Ø 6x4.6 mm spindle length 23mm screw connections	
0H6284	Cam switch 0-1-2 pos 3 control positions - 5 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23mm faston connectors 6.3x0.8mm	
OK1004	SWITCH	

3 positions

Code	Spare Part Description	Picture
OL3145	Cam switch 0-1-2 pos 3 control positions - 3 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23mm faston connectors 6.3x0.8mm	



3 positions









Code	Spare Part Description	Picture
OKV045	Cam switch 0-1-2 pos 3 control positions - 8 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23mm faston connectors 6.3x0.8mm	
OH9806	Cam switch 0-1-2 pos 3 control positions - 4 poles contacts with rating 32A-250V D shaft Ø 6x4.6 mm spindle length 23mm screw connections	

4 positions

Code	Spare Part Description	Picture
032857	Cam switch 0-3 pos 4 control positions - 2 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 17 mm screw connections	
0G7663	Cam switch 0-3 pos 4 control positions - 3 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	
OK6631	Cam switch 0-3 pos 4 control positions - 3 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	
0A2241	Cam switch 0-1 0-1 pos 4 control positions - 4 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23mm faston connectors 6.3x0.8mm	
003761	Cam switch 0-3 pos 4 control positions - 5 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	





4 positions




Code	Spare Part Description	Picture
OK4921	Cam switch 0-3 pos 4 control positions - 4 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm screw connections	
059544	Cam switch 0-3 pos 4 control positions - 5 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	
OC7965	Cam switch 0-3 pos 4 control positions - 8 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 17 mm faston connectors 6.3x0.8mm	
OH6682	Cam switch 0-1 0-1 pos 4 control positions - 4 poles contacts with rating 32A-250V D shaft Ø 6x4.6 mm spindle length 23 mm screw connections	
OH6683	Cam switch 0-3 pos 4 control positions - 4 poles contacts with rating 32A-250V D shaft Ø 6x4.6 mm spindle length 23 mm screw connections	
OC9725	Cam switch 0-3 pos 4 control positions - 11 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	
OK1383	Cam switch 0-3 pos 4 control positions - 3 poles contacts with rating 32A-250V D shaft Ø 6x4.6 mm spindle length 23 mm screw connections	
OKV044	Cam switch 0-3 pos 4 control positions - 4 poles contacts with rating 32A-250V D shaft Ø 6x4.6 mm spindle length 23 mm screw connections	



4 positions

Code	Spare Part Description	Picture
0H6598	COMMUTATOR; 4 POS	
0A2162	DOUBLE-POLE SWITCH; 16A 250V	

5 positions



Code	Spare Part Description	Picture
052749	Cam switch 0-4 pos 5 control positions - 3 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm screw connections	
0C9080	Cam switch 0-4 pos 5 control positions - 7 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 24 mm faston connectors 6.3x0.8mm	
0C7353	Cam switch 0-4 pos 5 control positions - 11 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	
0S2624	COMMUTATOR	

6 positions






Code	Spare Part Description	Picture
0S2273	Cam switch 0-5 pos 6 control positions - 1 pole contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	



6 positions




Code	Spare Part Description	Picture
OK5159	Cam switch 0-5 pos 6 control positions - 6 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	
048286	Cam switch 6 control positions - 1 pole contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	

7 positions




Code	Spare Part Description	Picture
0H6685	Cam switch 0-6 pos 7 control positions - 3 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	
053408	Cam switch 0-6 pos 7 control positions - 6 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	
OK4914	Cam switch 0-6 pos 7 control positions - 5 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	
OC3936	Cam switch 0-6 pos 7 control positions - 7 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm screw connections	
0A2021 710A2021	Cam switch 0-6 pos 7 control positions - 3 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm screw connections	



7 positions







Code	Spare Part Description	Picture
002661	Cam switch 0-6 pos 7 control positions - 5 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	
004741	Cam switch 0-6 pos 7 control positions - 7 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	
0A2022	Cam switch 0-6 pos 7 control positions - 3 poles contacts with rating 32A-250V D shaft Ø 6x4.6 mm spindle length 23 mm screw connections	

Miscellaneous switches

Code	Spare Part Description	Picture
OE5132	Switch 0-1 pos and push button 3 control positions - 3 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	
OC6245	Switch 0-7 pos 8 control positions - 5 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	
OC0084	Switch with card and LED lights 0-9 pos 10 control positions -1 pole contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm Cable length 500mm connections with plug connector	



Miscellaneous switches

Code	Spare Part Description	Picture
OK5063	Switch with connector 0-1 pos 2 control positions -4 poles contacts with rating 32A-250V D shaft Ø 6x4.6 mm spindle length 23 mm Cable length 2400mm screw connections version with potentiometer	
OE5131	Switch 0-1 pos 2 control positions - 4 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	
OK8614	Switch 0-2 pos 3 control positions - 5 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	
OE5222	Switch 0-1 pos 2 control positions - 6 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm faston connectors 6.3x0.8mm	
OG3298	Switch with connector 0-1 pos 2 control positions -2 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 23 mm Cable length 2400mm connections with plug connector version with potentiometer	
048829	Wash cycle switch 0-7 pos 8 control positions - 5 poles contacts with rating 16A-250V D shaft Ø 6x4.6 mm spindle length 24 mm faston connectors 6.3x0.8mm	

Lighting

Code	Spare Part Description	Picture
054840	Clear tubular lamp 25 W small connection E14 230 V	
006645	Halogen lamp 40 W; small connection E14; 230V; for temperatures even above 300°C	
0S2260	Halogen lamp 40 W connection G9 230 V	
0S2518	Halogen lamp 4 W connection G9 3000 °K 230V	
0S2385	Infrared halogen lamp 200W connection R7S 235 V dim. L 185,7mm Ø 7 mm	
0S2587	Infrared halogen lamp 350W connection R7S 235 V dim. L 185,7mm Ø 9,6 mm	
0PR505	Infrared halogen lamp 500W connection R7S 235 V dim. L 220.6mm Ø 11 mm	
0S0596	Lamp, olive 40 W small connection E14 230 V for temperatures up to max 300°C	





Cooking

Lighting



Code	Spare Part Description	Picture
OCB661	HALOGEN LAMP	
OS1983	Halogen lamp 20W connection G4 12V for temperatures up to 300°C	
093041	Halogen lamp 160 W connection R7S 230 V dim. L 118 mm	
OS1957	LED lamp 10W connection R7S lumens 1200 light 2700K 230V 50/60Hz dim. Ø22x118mm	
OS1918	Infrared halogen lamp 250 W connection E27 230 V light colour	
093515	Fluorescent tubular lamp 36 W T8 class II Power supply 230V(I) 50/60Hz Length 970mm	
OS2519	Ciling lamp 1x36W dim. 1293x190x92 mm	
OPE645	Overhead lamp for extractor hoods with connection (halogen) complete with halogen lamp 40 W connection G9 230V	
OPE842	Fluorescent tubular lamp 18 W T8 class II Power supply 230V(I) 50/60Hz Length 590mm	



Lighting

Code	Spare Part Description	Picture
032276	Ceiling lamp 1x36W with protection no. 1 lamp 36 W dim. 1257x65x124 mm	
033804	Overhead lamp for extractor hoods with 40 W lamp and glass globe lamp connection E14 max temperature 300°C	
004160	Lamp holder for lamps with screw connection E14	
004163	Glass globe	
0S2588	Lamp holder complete Lamp 25W 230V Connection E14	
0S2501	LIGHTING FIXTURE	

Terminal block electrical connections

Code	Spare Part Description	Picture
053406	Electric hot plate 1500W 230V dim. Ø 145 mm	
003930	Electric hot plate 1500W 400V dim. Ø 145 mm	





Terminal block electrical connections







Code	Spare Part Description	Picture
OK0356	Electric hot plate 2000W 400V dim. Ø 220 mm	
OH6080	Electric hot plate 2500W 400V dim. Ø 310 mm	
OG6313	Electric hot plate 1500W 230V dim. Ø 180 mm	
OKJ793	Electric hot plate 1500W 400V dim. Ø 180 mm	
004914	Electric hot plate 2000W 230V dim. Ø 180 mm	
053407	Electric hot plate 2600W 230V dim. Ø 220 mm	
053606	Electric hot plate 2600W 240V dim. Ø 220 mm	



Terminal block electrical connections

Code	Spare Part Description	Picture
003931	Electric hot plate 2600W 400V dim. Ø 220 mm	
003929	Electric hot plate 2600W 440V dim. Ø 220 mm	
0S2625	EL. HOT PLATE	

Screw electrical connections

Code	Spare Part Description	Picture
006220	Electric hot plate 2600W 230V dim. 220x220 mm	 
0C6243	Electric hot plate 2600W 400V dim. 220x220 mm	 
0C6244	Electric hot plate 2600W 440V dim. 220x220 mm	 
0H6079	Electric hot plate 2500W 400 V flip-up hot plate dim. 300x300 mm	






Screw electrical connections


Code	Spare Part Description	Picture
0H6082	Electric hot plate 4000W 400 V flip plate dim. 300x300 mm	
052196	Electric hot plate 3000W 230V dim. 300x300 mm	
052198	Electric hot plate 3000W 240V dim. 300x300 mm	
OK4756	Electric hot plate 3000W 400V dim. 300x300 mm	
052199	Electric hot plate 4000W 230V dim. 300x300 mm	
052200	Electric hot plate 4000W 400V dim. 300x300 mm	



Screw electrical connections





Code	Spare Part Description	Picture
0C2524	Electric hot plate 4000W 440V dim. 300x300 mm	
0C4077	Radiant heating element 3400W 230 V for glass ceramic dim. Ø 320 mm	
OK0589	Radiant heating element 4000W 400 V for glass ceramic hob without pot sensor dim. 300x300 mm	
OKD885	Radiant heating element 4000W 400 V for glass ceramic hob with pot sensor dim. 300x300 mm	
OKI634	Radiant heating element 1800W 230 V for glass ceramic dim. Ø 180 mm	
OS1438	Radiant heating element 1200W 230 V for glass ceramic dim. Ø 165 mm	

Heating elements

Code	Spare Part Description	Picture
032086	Adhesive heating element Etch Foil 500/595W 220/240V Complete with thermostat (150 ° C), with automatic reset. Dim: 290x175 mmm	



Heating elements

Code	Spare Part Description	Picture
088274	Adhesive heating element Etch Foil 1000W 220V Complete with thermostat (200 °C), with automatic reset. Dim: 400x290 mm	
032666	Adhesive heating element Etch Foil 1000/1190W 220/240V Complete with cables Dim: 470x275 mm	
032094	Adhesive heating element Etch Foil 1000W 230V Complete with thermostat (150 ° C), with automatic reset. Dim : 400x290 mm	
ORT229	Adhesive heating element Etch Foil 390W 240V Complete with cables Dim: 370x95mm	
088319	Adhesive heating element Etch Foil 286W 230V Complete with cables and thermostat (150 ° C), with automatic reset. Dim: 470x290 mm	
058144	Ceramic heating element 400W 230V Complete with cables Dim: 245x60 mm	
0S2564	Ceramic heating element 1000W 230V complete with cables Dim: 245x60 mm	
0S2291	Ceramic heating element 500W 230V Complete with cables Dim: 245x60 mm	

Feet

Code	Spare Part Description	Picture
053792	Adjustable foot in s/steel connection Ø 2" H 125 mm	
059218	Adjustable foot in AISI 304 connection Ø 2" sleeve and flange H 150÷220 mm	
032550	Adjustable foot in AISI 304 connection Ø 1" black plastic threaded 40x40 mm base ESA H 115÷175 mm	
004249	Adjustable foot in AISI 304 Ø 1" ¾ round base connection Ø 50mm sleeve and flange 80x80 mm H 145÷250 mm	
0C4823	Adjustable foot in AISI 304 connection Ø2" sleeve and flange 74x74 mm H 130÷210 mm	
054418	Adjustable foot in s/steel connection Ø 1"1/2 H 125 mm	







Cooking

Feet



Code	Spare Part Description	Picture
048579	Adjustable foot in AISI 304 connection Ø 2" round base sleeve and flange 74x74 mm H 135÷235 mm	
OPE204	Adjustable foot in AISI 304 connection Ø 1" white plastic threaded 40x40 mm base ESA H 115÷175 mm	
089140	Adjustable foot in AISI 304 connection Ø 1" ¾ round base connection Ø 60mm sleeve and plastic coated flange 100x110 mm H 130÷190 mm	
0C4824	Adjustable foot in AISI 304 connection Ø2" sleeve and flange 74x74 mm H 190÷270 mm	
0C0204	Adjustable foot in AISI 304 connection 1" ¾ round base Ø 50 mm sleeve and screw M10x15 H 150÷200 mm	
0C4664	Adjustable foot in AISI 304 round base Ø 2" sleeve and flange 74x74 mm H 135÷210 mm	



Feet








Code	Spare Part Description	Picture
049393	Rubber foot Ø 30 mm M8x1 H 30 mm	
0C9565	Flange foot for floor fixing SET 2PCS in AISI 304 base 80x80 mm centre distance 60x60 mm threaded connection 1" 3/4 Ø 50.5 mm height 140mm - utile 100mm Compatible with 0C0204	
026806	Rubber foot Ø 17 mm with screw M6 H 37 mm	
085942	Rubber foot Ø 40 mm with screw M10x0.5 H 52 mm	

Castors

Code	Spare Part Description	Picture
0S0124	Castor with brake, round expansion Ø 21.5 H 68 mm dim. Ø 125x30 mm	
0S0125	Castor with brake, square expansion 20.5x20.5 H 68 mm dim. Ø 125x30 mm	










Castors

Code	Spare Part Description	Picture
0S0126	Castor with brake, square expansion 37.5x37.5 H 68 mm dim. Ø 125x30 mm	
0S1428	Castor with brake dim. Ø 125x30 mm	
003342	Castor with brake with pin Ø 19 mm H 45 mm dim. Ø 125x30 mm	
033656	Castor with brake with screw M10x1.5 dim. Ø 100x30 mm	
0S1070	Kit of 4 castors (two with brake) square expansion consisting of: n.2 033656 castor with brake n.2 033657 castor without brake n.4 033655 square expansion for kit PNC 855030	
0S0127	Castor without brake, round expansion Ø 21.5 H 68 mm dim. Ø 125x30 mm	
0S0128	Castor without brake, square expansion 20.5x20.5 H 68 mm dim. Ø 125x30 mm	









Castors

Code	Spare Part Description	Picture
0S0129	Castor without brake, square expansion 37.5x37.5 H 68 mm dim. Ø 125x30 mm	
0S1427	Castor without brake dim. Ø 125x30 mm	
003341	Castor without brake with pin Ø 19 mm H 45 mm dim. Ø 125x30 mm	
033657	Castor without brake dim. Ø 100x30 mm	
0S0122	Castor with plate without brake fixing plate 90x70 mm centre distance 70x50 mm dim. Ø 125x30 mm	
031561	Swivel plate castor with brake fixing plate dim. 105x85 mm hole centre distance 80/77 x 60 mm dim. Ø 125x32 mm	
0S1434	Fixed plate castor without brake fixing plate 105x85 mm hole centre distance 80/77 x 60 mm dim. Ø 125x32 mm	





Cooking

Castors




Code	Spare Part Description	Picture
032146	Swivel plate castor with brake fixing plate 136x105 mm centre distance 105x80 mm dim. Ø 160x40 mm	
OCA963	Fixed plate castor without brake fixing plate dim. 105x85 mm hole centre distance 80/77 x 60 mm dim. Ø 125x40 mm	
OS0123	Castor with plate with brake fixing plate 90x70 mm centre distance 70x50 mm dim. Ø 125x30 mm	
087111	Swivel plate castor without brake; fixing plate dim. 105x85 mm; hole centre distance 80/77 x 60 mm dim. Ø 125x32 mm	
032148	Fixed plate castor without brake centre distance 105x80 mm dim. Ø 160x40 mm	
093280	Swivel plate castor with brake fixing plate dim. 105x85 mm hole centre distance 80/77 x 60 mm dim. Ø 125x40 mm	
OC1631	Castor with brake Diameter 100 mm	



Castors

Code	Spare Part Description	Picture
OC1632	Castor without brake Diameter 125 mm	
OS2626	CASTOR WITH BRAKE	
OS2627	CASTOR WITHOUT BRAKE	

Accessories for castors/wheels



Code	Spare Part Description	Picture
OS0882	Square expansion galv. nut M10 E14 20.5x20.5mm H 68 mm for OS0125	
033655	Square expansion galv. nut M10 E14 36x36mm H 42 mm for square leg tables	
OS1209	Round expansion Ø 21.5 H 68 mm for OS0127	



Accessories for castors/wheels

Code	Spare Part Description	Picture
OPE119	Round expansion galv. nut M10 E14 Ø 50mm H 42 mm for round leg tables	
OS1068	Bumper with round hole Ø 25 mm	
033717	Bumper for trolley side 90 mm	
OS1069	Kit of 4 bumpers with square hole 25x25 mm	
OL2658	Set of 4 pcs/small wheels for dishwasher dim 80x62.6 mm H 20 mm	

Water drain and inlet taps

Code	Spare Part Description	Picture
OS1037	Drain tap with conical seal and safety swivel connection Ø 1"½ F	
OH6421	Drain tap with conical seal and safety swivel connection Ø 1"½ F	



Water drain and inlet taps

Code	Spare Part Description	Picture
0CA949	Drain tap GBM with O Ring swivel connection Ø 2" F	
0S0287	Heatproof handle for drain taps 2"	
017215	Drain tap with nut connection M60x2	
0S1034	Drain ta with conical seal and safety fixed connection Ø 1"¼ F	
0S0568	Heatproof handle for drain taps 1"¼ , 1"½	
0C3142	O-ring Pack of 3 pcs for drain taps 1"¼, 1"½	
0S2227	Drain tap GBM with conical seal swivel connection Ø 2" F	



Water drain and inlet taps

Code	Spare Part Description	Picture
0HB198	O-ring for drain tap Ø 2"F for TECNO and GBM type	
052907	Drain tap with nut connection M68x3 int. hole Ø 50 mm	
053159	Drain tap conical seal with nut connection: M78x3 mm	
0S2118	Grease for taps with O-ring g 100 certification NSFH1	
0S1145	Food-grade grease for taps with conical seal 2 tubes g 45	
0C7121	Single hole inlet tap with swivel spout ½"F and 3/8"M complete with 2 hoses	
0S0724	Hose 3/8"M 1/2"F Ø12x850 mm	




Water drain and inlet taps




Code	Spare Part Description	Picture
008000	Single hole tap with swivel spout for filling pots Ø ½" F	
0S1336	Tap valve ¾" for single hole tap connection 7x7 mm	
0S1067	Heatproof handle for drain tap M78x3	
0S2277	Food-grade grease for taps with conical seal kg 1	
OC9506	Lubricating grease Anti-slip Aluminum One 500 g pack	
OC4530	Flange dim. 90x70 mm	
OC4531	Connection Ø45 mm for hoses 3/8"	
0S0247	Knob with blue insert connection 7x7 mm	
0S0246	Knob with red insert connection 7x7 mm	



Water drain and inlet taps









Code	Spare Part Description	Picture
0S1035	DRAIN TAP; 1"1/2; FIXED ATTACK	

Safety and thermostatic

Code	Spare Part Description	Picture
054109	Gas tap PEL 20 S without pilot flame connections ØM16x1.5 mm thermocouple connection M8x1, D shaft Ø 8x6.5 mm	
059460	Gas tap PEL 21 S connections ØM16x1.5 mm thermocouple connection M8x1, D shaft Ø 8x6.5 mm	
0C0205	Gas tap PEL 21 S with special bridle inlet connection Ø 9mm outlet connection ØM16x1.5 mm thermocouple connection M8x1 D shaft Ø 8x6.5 mm	
052146	Gas tap PEL 22 V with vertical flange connections ØM20x1.5 mm, thermocouple connection M9x1, D shaft L=26.5 mm Ø 10x8 mm	
052432	Gas tap PEL 22 V with vertical flange connections ØM20x1.5 mm thermocouple connection M9x1, minimum adj. screw Ø 0.30 mm, D shaft Ø 10x8 mm	
004237	Gas tap PEL 20 S without pilot flame connections ØM16x1.5 mm thermocouple connection M9x1, D shaft Ø 8x6.5 mm	









Safety and thermostatic


Code	Spare Part Description	Picture
004282	Gas tap PEL 21S with pilot flame connections ØM16x1.5 mm thermocouple connection M8x1 D shaft Ø 8x6.5 mm shaft length 39 mm	
052145	Gas tap PEL 22 V with vertical flange connections ØM20x1.5 mm D shaft Ø 10x8 mm	
0C0489	Gas tap PEL 22 V with vertical flange, connections ØM20x1.5 mm, thermocouple connection M9x1 D shaft Ø 10x8 mm L=33.5 mm Ø 10x8 mm	
0A2001	Gas tap PEL 22 O with horizontal flange, with flow regulator, connections ØM20x1.5 mm thermocouple connection M8x1, D shaft Ø 10x8 mm	
0S0595	Gas tap PEL 22 O with pilot flame and horizontal flange with flow regulator connections ØM20x1.5 mm thermocouple connection M9x1 D shaft Ø 10x8 mm	
0C8647	Gas tap PEL 22S/V with fine adjustment, pilot flame and vertical flange connections ØM20x1.5 mm thermocouple connection M9x1 D shaft Ø 10x8 mm shaft length 33 mm / 26 mm	
005466	Gas tap PEL 23O with pilot flame and horizontal flange inlet connection ØM28x1.5 mm outlet connection ØM24x1.5 mm thermocouple connection M9x1 D shaft Ø 10x8 mm shaft length 25 mm	
058369	Thermostatic gas tap PEL 24 ST fixed connections ØM20x1.5 mm adjustment range: 120°-320°C thermocouple connection M9x1 bulb Ø 6x100 mm D shaft Ø 10x8 mm	



Safety and thermostatic

Code	Spare Part Description	Picture
0C0060	Thermostatic gas tap PEL 25ST inlet outlet connections ØM16x1.5 mm adjustment range: 140°-300°C thermocouple connection: M8x1 bulb Ø 6x86 mm capillary length 1000mm D shaft Ø 8x6.5 mm	
004956	Gas tap SABAF gas inlet flange pipe Ø 16mm gas outlet 1/4" Ø 8mm thermocouple connection M8x1 D shaft Ø 8x6.5 mm complete with bracket and various screws	
0S2375	Gas tap SABAF without bracket and various screws	
0C6758	Gas tap PEL 22 S with pilot flame and vertical flange connections ØM20x1.5 mm thermocouple connection M9x1 D shaft Ø 10x8 mm shaft length 24,5 mm	
054811	Gas tap PEL 23 O with horizontal flange inlet connections ØM28x1.5 mm outlet connection ØM24x1.5 mm thermocouple connection M9x1 D shaft L=34 mm, Ø 10x8 mm	
006597	Thermostatic gas tap PEL 25 ST connections ØM16x1.5 mm adjustment range: 140°-300°C, thermocouple connection: M8x1, bulb Ø 6x120 mm, D shaft Ø 8x6.5 mm	

Gas tap accessories

Code	Spare Part Description	Picture
059854	Cap with pin PEL 20 for taps code 054109 - 054628 - 054629 - 054166 A=Ø 8x6,5 B=22 mm C=21 mm	



Gas tap accessories

Code	Spare Part Description	Picture
0S1934	Cap with pin PEL 20 for tap code 004237 A=Ø 8x6,5 B=39.5 mm C=21 mm	
002185	Cap with pin PEL 21 for tap code 059460 A=Ø 8x6,5 B=22 mm C=21 mm	
0S0661	Cap with pin PEL 21 for tap code 0C0205 A=Ø 8x6,5 B=32 mm C=21 mm	
056597	Cap with pin PEL 22 for taps 052146 - 052145 - 0S0595 - 0A2001 - 0C6758 A=Ø 10x8 B=27 mm C=25 mm	
059853	Cap with pin PEL 23 for taps code 054811 - 005466 A=Ø 10x8 B=35 mm C=30 mm	
0S0053	Horizontal flange with pressure point for PEL 22	
056594	Magnetic group for tap PEL 22 with large head	
056595	Magnetic group for tap PEL 20-21 with small head	
056596	Magnetic group for tap PEL 23 thermocouple connection M9x1	



Gas tap accessories




Code	Spare Part Description	Picture
0C1521	Magnetic group for tap PEL 23 thermocouple connection M10x1	
0A2125	Connection for pipe Ø10mm for PEL 20-21	
052124	Connection for pipe Ø10mm for PEL 22	
054816	Connection for pipe Ø16mm for PEL 23	
060325	Olive for pipe (double cone) ØE=12MM; ØI=10 MM; L=7,5MM	
052127	Olive for pipe (double cone) ø 4mm	
020992	Pilot double cone for pipe Ø6mm for PEL 21-22	
0K0059	Copper pipe for pilot burner Ø4mm	









Gas tap accessories

Code	Spare Part Description	Picture
052125	Union screw for the connection of pipe Ø 4mm; thread M10x1	
052128	Double cone for pipe Ø10mm for PEL 22	
050682	Double cone for pipe Ø 12 mm	
052671	Double cone for pipe Ø16mm for MINISIT and PEL 23 (h 9mm)	
054817	Double cone for pipe Ø16mm for PEL 23 (h 11mm)	
054815	Double cone for pipe Ø20mm for PEL 23	
0S2733	CAP COVER	




M8x1 series

Code	Spare Part Description	Picture
0G1120	Thermocouple M8x1, L=450 mm	
0G2906	Thermocouple M8x1, L=550 mm	
0K5730	M8x1 series Thermocouple M8x1, L=1200 mm	



M9x1 series

Code	Spare Part Description	Picture
027317	M8x1 series Thermocouple M9x1, L=500 mm	
025031	M8x1 series Thermocouple M9x1 aluminised tip, L=600 mm	
027350	M8x1 series Thermocouple M9x1, L=1000 mm	
020094	M8x1 series Thermocouple M9x1 aluminised tip, L=1200 mm	
059064	M8x1 series Thermocouple M9x1, L=1500 mm	
0C1634	Thermocouple M9x1, L=1900 mm M8x1 series	





Threaded series

Code	Spare Part Description	Picture
0K5688	"Threaded" series Thermocouple M8x1 joint M8x1, L=600 mm	
0U2960	"Threaded" series Thermocouple M8x1 joint M8x1, L=1000 mm	
025677	"Threaded" series Thermocouple M9x1 joint M8x1, L=600 mm	



M8x1 Quick series

Code	Spare Part Description	Picture
0C0202	"Quick" series M8x1 Thermocouple M8x1 aluminised tip, L=750 mm	
051119	"Quick" series M8x1 Thermocouple M8x1 aluminised tip, L=1500 mm	





M9x1 Quick series

Code	Spare Part Description	Picture
004942	"Quick" series M9x1 Thermocouple M9x1 L=500 mm	
057781	"Quick" series M9x1 Thermocouple M9x1, L=600 mm	
003281	"Quick" series M9x1 Thermocouple M9x1, L=1200 mm	
0M0893	"Quick" series M9x1 Thermocouple M9x1, L=1500 mm	

"Quick" series M10x1


Code	Spare Part Description	Picture
0H6253	Thermocouple M10x1 L=850 mm	
0H6252	Thermocouple M10x1 L=1500 mm	

"Interrupted thermocouples" series

Code	Spare Part Description	Picture
058503	"Interrupted thermocouple" series Interrupted thermocouple M9x1 L=600 mm	
051635	"Interrupted thermocouple" series Interrupted thermocouple M9x1 L=1000 mm, wire length 1000 mm	
0C3162	"Interrupted thermocouple" series Interrupted thermocouple ORKLY M9x1 L=1000 mm, wire length 1000 mm	
0CA280	Interrupted thermocouple M9x1 QUICK OFF L=730 mm Wire length 500 mm	



“Interrupted thermocouples” series






Code	Spare Part Description	Picture
0C9165	Interrupted thermocouple M8x1 NORMAL L=750 mm Wire length 100 mm	
0C3197	Interrupted thermocouple M9x1 L=1000 mm Wire length 850 mm	
002784	“Interrupted thermocouple” series Interrupted thermocouple M9x1 L=1000 mm, wire length 600 mm	
0C7716	Interrupted thermocouple M9x1 NORMAL L=1450 mm Wire length 700 mm	
0CA188	Interrupted thermocouple M9x1 NORMAL L=1700 mm Wire length 200 mm	

“Generic” series



Code	Spare Part Description	Picture
004955	Thermocouple M8x1 L=600 mm Joint M6x1	



"Generic" series

Code	Spare Part Description	Picture
0U2961	Thermocouple ASA L=1000 mm	
0S0055	Thermocouple L=900 mm Joint for threaded pilot M6x0.75 (A513) Complete with adapters (6 pcs)	
0S0056	Thermocouple L=1200 mm Joint for threaded pilot M6x0.75 (A513) Complete with adapters (6 pcs)	
052163	Thermocouple M9x1 L=1000 mm Joint M8x1	
0U1115	Thermocouple L=900 mm Complete with 4 connections (M10x1; 11/32" - M10x1 milled; M8x1 - M9x1 milled; 7/16"), bushings, adapters and spacers	

Thermocouple accessories


Code	Spare Part Description	Picture
055032	Thermocouple extension M9x1 L=600 mm Female nut M9x1	
OK3024	Interrupted connection ASA M 11/32	



Thermocouple accessories

Code	Spare Part Description	Picture
005687	Interrupted connection M9x1	
0C0121	Connector for thermocouple M10x1 Ø 6,5 mm	
055033	NUT; M8X1	
OK3025	Milled double connection M10x1 - 11/32 ASA	
OCB504	Thermocouple fitting ASA 11/32	

Single-phase

Code	Spare Part Description	Picture
054323	Single-phase thermostat 0-300°C Bulb Ø3.5x190 mm Capillary 1500 mm 15A 230V Knob pin Ø6x4.6 mm	









Single-phase

Code	Spare Part Description	Picture
051142	Single-phase thermostat 30-90°C Bulb Ø6x174 mm Capillary 980 mm 16A 380V Knob pin Ø6x4.6 mm	
033716	Single-phase thermostat 30-90°C Bulb Ø6x100 mm Capillary 960 mm 16A 230V Knob pin Ø6x4.6 mm	
002109	Single-phase thermostat 50-260°C with auxiliary switch Bulb Ø4x115 mm capillary 1300 mm 10A 400V Knob pin Ø6x4.6 mm	
0H6439	Single-phase thermostat 50-250°C Bulb Ø3x160 mm Coated capillary 1430 mm 16A 230V Knob pin Ø6x4.6 mm Packing gland M9x1	
003262	Single-phase thermostat 30-90°C Bulb Ø6x130 mm Capillary 1500 mm 16A 380V Knob pin Ø6x4.6 mm	
0E5032	Single-phase thermostat 30-110°C Bulb Ø3x197 mm Capillary 3000 mm 16A 230V Knob pin Ø6x4.6 mm	
031480	Single-phase thermostat 60-175°C Bulb Ø3x226 mm Capillary 870 mm Knob pin Ø6x4.6 mm	
056384	Single-phase thermostat 50-296°C Capillary 1000 mm Bulb Ø3x219 mm 16A 380V Knob pin Ø6x4.6 mm	




Single-phase






Code	Spare Part Description	Picture
057937	Single-phase thermostat 50-260°C Capillary 900 mm Bulb Ø3x219 mm 16A 380V Knob pin Ø6x4.6 mm	
051360	Single-phase thermostat 50-260°C Bulb Ø4x115 mm Capillary 1200 mm 16A 250V Knob pin Ø6x4.6 mm	
002602	Single-phase thermostat 90-185°C 0.5A 12V Bulb Ø4x230 mm Capillary 1300 mm Knob pin Ø6x4.6 mm	
052330	Single-phase thermostat 90-185°C with auxiliary switch Bulb Ø4x229 mm Capillary 2350 mm 16A 380V Knob pin Ø6x4.6 mm	
058163	Single-phase thermostat 95-190°C Bulb Ø6x135 mm Coated capillary 900 mm 16A, 250V Knob pin Ø6x4.6 mm Packing gland M10x1	
050412	Single-phase thermostat 90-185°C 16A 250V Bulb Ø4x230 mm Capillary 1300 mm Knob pin Ø6x4.6 mm	



Single-phase








Code	Spare Part Description	Picture
003049	Single-phase thermostat 90-185°C with auxiliary switch Bulb Ø4x229 mm Capillary 2350 mm 16A 380V Knob pin Ø6x4.6 mm	

Three-phase

Code	Spare Part Description	Picture
004911	Three-phase thermostat 30-110°C Bulb Ø6x130 mm capillary 900 mm 10A 400V Knob pin Ø6x4.6 mm Packing gland M9x1	
032858	Three-phase thermostat 30-110°C Bulb Ø6x130 mm Capillary 1200 mm, 10A 400V Knob pin Ø6x4.6 mm	
0A2206	Three-phase thermostat 50-320°C Bulb Ø3x219 mm Capillary 900 mm 16A, 380V Knob pin Ø6x4.6 mm	
055996	Three-phase thermostat 50-300°C Bulb Ø2.5x330 mm Capillary 1150 mm 16A 380V Knob pin Ø6x4.6 mm	
052099	Three-phase thermostat 60-320°C Bulb Ø4x130 mm Capillary 1300 mm 16A 380V Knob pin Ø6x4.6 mm	





Three-phase





Code	Spare Part Description	Picture
0H6233	Three-phase thermostat 95-180°C Bulb Ø6X133 mm Capillary 1800 mm 16A 230V Knob pin Ø6X4.6 mm, packing gland M9x1	
052000	Three-phase thermostat 30-90°C Bulb Ø6x175 mm Capillary 870 mm 16A 380V Knob pin Ø6x4.6 mm	
0H6217	Three-phase thermostat 50-300°C Bulb Ø6x80 mm Capillary 1740 mm 16A, 230V Knob pin Ø6x4.6 mm	
005940	Three-phase thermostat 60 - 185°C Bulb Ø4X231 mm Capillary 1200 mm 10A 400V Knob pin Ø6X4.6 mm	
0C7528	Three-phase thermostat 90 - 230°C Bulb Ø4X131 mm Capillary 1250 mm 10A 400V Knob pin Ø6X4.6 mm	
059235	Three-phase thermostat 100 - 285°C Bulb Ø3X225 mm Capillary 1150 mm 10A 400V Knob pin Ø6X4.6 mm	
052916	Three-phase thermostat 100-300°C Bulb Ø6X80 mm Capillary 1150 mm 10A 400V Knob pin Ø6X4.6 mm	



Three-phase

Code	Spare Part Description	Picture
051361	Three-phase thermostat 60-185°C Bulb Ø4X231 mm Capillary 2600 mm 16A 380V Knob pin Ø6X4.6 mm	
004363	Three-phase thermostat 115 - 300°C Bulb Ø3X144 mm Capillary 1150 mm 10A 400V Knob pin Ø6X4.6 mm	

Single-phase

Code	Spare Part Description	Picture
0C1147	Single-phase thermostat 150°C Bulb Ø6X74 mm Capillary 1700 mm 0.5A 12V	
004912	Single-phase thermostat 130°C Bulb Ø6X130 mm Capillary 870 mm 16A 250V	
031482	Single-phase thermostat 177°C Bulb Ø3X160 mm Capillary 560 mm 16A 250V	
0C1000	Single-phase thermostat 210°C Bulb Ø6X75 mm Capillary 1250 mm 0.5A 12V	









Single-phase

Code	Spare Part Description	Picture
0C4279	Single-phase thermostat 230°C Bulb Ø6X87 mm Capillary 900 mm 0.5A 12V	
005680	Single-phase thermostat 338°C Bulb Ø11X6 mm Capillary 900 mm 20A 400V	
002711	Single-phase thermostat 150°C Bulb Ø6X74 mm Capillary 1700 mm 20A 400V	
0H6142	Single-phase thermostat 190°C Bulb Ø3X178 mm Capillary 350 mm 16A 250V	
0S1933	Single-phase thermostat 220°C Bulb Ø6X133 mm Capillary 2020 mm 16A 250V	
058164	Single-phase thermostat 230°C Bulb Ø6X130 mm Coated capillary 1000 mm 16A, 250V With thermocouple wiring	
053012	Single-phase thermostat 235°C Bulb Ø5X100 mm Capillary 1000 mm 15A 250V	
003121	Single-phase thermostat 240°C Bulb Ø6X80 mm Coated capillary 1300 mm 16A 250V Packing gland M10x1	






Single-phase




Code	Spare Part Description	Picture
005931	Single-phase thermostat 250°C Capillary 900 mm Bulb Ø6X87 mm 0.5A, 12V	
0A5435	Single-phase thermostat 245°C Capillary 1100 mm Bulb Ø6X87 mm 0.5A, 12V	
002730	Single-phase thermostat 338°C Bulb Ø11X6 mm Capillary 900 mm 20A 400V	
003594	Single-phase thermostat 360°C Bulb Ø6X79 mm Capillary 1500 mm 0.5A 12V	
004354	Single-phase thermostat 240°C Bulb Ø6X79 mm Capillary 2000 mm 0.5A 12V	
004951	Single-phase thermostat 239°C Bulb Ø6X80 mm Capillary 900 mm 10A, 400V	



Single-phase







Code	Spare Part Description	Picture
0C0999	Single-phase thermostat 260°C Bulb Ø6X75 mm Capillary 1250 mm 0.5A 12V	
007042	Single-phase thermostat 338°C Bulb Ø6X39 mm Capillary 900 mm 20A 400V	
004269	Single-phase thermostat 360°C Bulb Ø4X120 mm Capillary 900 mm 0.5A, 12V	

Three-phase

Code	Spare Part Description	Picture
004862	Three-phase thermostat 140°C Bulb Ø6X87 mm Capillary 900 mm 20A 400V	
006433	Three-phase thermostat 150°C Bulb Ø6X73 mm Capillary 1730 mm 0.5A 12V	
005295	Three-phase thermostat 170°C Bulb Ø6X87 mm Capillary 900 mm 0.5A 12V	









Three-phase

Code	Spare Part Description	Picture
0C4463	Three-phase thermostat 230°C Bulb Ø6X87 mm Capillary 900 mm 20A 400V	
0C2983	Three-phase thermostat 140°C Bulb Ø6X87 mm Capillary 900 mm 20A 400V	
004742	Three-phase thermostat 170°C Bulb Ø6X87 mm Capillary 900 mm 20A 400V	
059552	Three-phase thermostat 225°C Bulb Ø6X159 mm Capillary 940 mm 20A 380V	
003120	Three-phase thermostat 240°C Bulb Ø6X100 mm Coated capillary 900 mm 10A 400V Packing gland M10x1	
004472	Three-phase thermostat 245°C Bulb Ø6X87 mm Capillary 2700 mm 20A 400V	










Three-phase

Code	Spare Part Description	Picture
005941	Three-phase thermostat 250°C Bulb Ø6X87 mm Capillary 900 mm 20A 400V	
052331	Three-phase thermostat 250°C Bulb Ø6X159 mm Capillary 1230 mm 1A 380V	
006307	Three-phase thermostat 270°C Bulb Ø6X87 mm Capillary 900 mm 20A 400V	
004921	Three-phase thermostat 293°C Bulb Ø4X120 mm Capillary 900 mm 10A 400V	
006282	Three-phase thermostat 245°C Bulb Ø6X87 mm Capillary 900 mm 0.5A 12V	
054932	Three-phase thermostat 250°C Bulb Ø6X239 mm Capillary 2530 mm 20A 380V	





Three-phase





Code	Spare Part Description	Picture
051369	Three-phase thermostat 250°C Bulb Ø6X239 mm Capillary 2530 mm 10A 400V	
053183	Three-phase thermostat 285°C Bulb Ø6X157 mm Capillary 940 mm 0.5A 12V	
0H6215	Three-phase thermostat 315°C Bulb Ø6X80 mm Capillary 900 mm 10A 400V	
006826	Three-phase thermostat 350°C Bulb Ø6X79 mm Capillary 1500 mm 20A 400V	
051643	Three-phase thermostat 350°C Bulb Ø6X159 mm Capillary 940 mm 20A 400V	
051454	Three-phase thermostat 350°C Bulb Ø6X160 mm Capillary 940 mm 10A 400V	
0C0270	Three-phase thermostat 350°C Bulb Ø3X190 mm Capillary 900 mm 10A 400V	



Three-phase





Code	Spare Part Description	Picture
004919	Three-phase thermostat 350°C Bulb Ø3X190 mm Capillary 1120 mm 10A 400V	
004600	Three-phase thermostat 360°C Bulb Ø6X79 mm Capillary 1200 mm 0.5A 12V	
OS2623	SAFETY THERMOSTAT	

Flexible gas pipes - UNI-EN14800 compliant




Code	Spare Part Description	Picture
OS1026	S/steel flexible gas pipe 316L with SMOOTH sheath UNI-EN14800 compliant Ø 1/2" FF swivel, L= 500 mm	
OS1005	S/steel flexible gas pipe 316L with SMOOTH sheath UNI-EN14800 compliant Ø 1/2" FF swivel, L= 1000 mm	
OS1008	S/steel flexible gas pipe 316L with SMOOTH sheath UNI-EN14800 compliant Ø 1/2" FF swivel, L= 1500 mm	
OS1003	S/steel flexible gas pipe 316L with SMOOTH sheath UNI-EN14800 compliant Ø 1/2" FF swivel, L= 2000 mm	



Flexible gas pipes - UNI-EN14800 compliant

Code	Spare Part Description	Picture
OS1025	S/steel flexible gas pipe 316L with SMOOTH sheath UNI-EN14800 compliant Ø 1/2" MF swivel, L= 500 mm	
OS1006	S/steel flexible gas pipe 316L with SMOOTH sheath UNI-EN14800 compliant Ø 1/2" MF swivel, L= 1000 mm	
OS1007	S/steel flexible gas pipe 316L with SMOOTH sheath UNI-EN14800 compliant Ø 1/2" MF swivel, L= 1500 mm	
OS1015	S/steel flexible gas pipe 316L with SMOOTH sheath UNI-EN14800 compliant Ø 1/2" MF swivel, L= 2000 mm	

Flexible-extensible gas pipes - UNI-11353 compliant






Code	Spare Part Description	Picture
OS1258	Flexible-extensible s/steel gas pipe 316L with CORRUGATED sheath UNI-11353 compliant Ø 3/4" FF swivel, L= 500÷1000mm	
OS1259	Flexible-extensible s/steel gas pipe 316L with CORRUGATED sheath UNI-11353 compliant Ø 3/4" FF swivel, L= 1000÷2000mm	
OC1074	Gas pressure regulator dim. mm 75x85x71	



Flexible-extensible gas pipes - UNI-11353 compliant





Code	Spare Part Description	Picture
0C6506	Gas adapter from $\frac{3}{4}$ " to $\frac{1}{2}$ "	

MINISIT series



Code	Spare Part Description	Picture
052068	MINISIT gas valve Adjustment range 100°-340°C Inlet Ø1/2"F outlet Ø3/8"F Cap.length 1050 mm nick. Bulb Ø4x72 mm Complete with knob and cover	
053368	MINISIT gas valve adjustment range 50°-190°C inlet Ø1/2"F outlet Ø3/8"F cap. length 1200 mm nick. bulb Ø5x95 mm	
056688	MINISIT gas valve adjustment range 110°-190°C inlet Ø1/2"F outlet Ø3/8"F cap. length 1050 mm nick. bulb Ø6x105 mm	
056689	MINISIT gas valve Adjustment range 110°-190°C inlet Ø1/2"F outlet Ø3/8"F thermocouple connection M9x1 cap.length 1050 mm nick. bulb Ø6x105 mm complete with knob, cover, connections and various accessories	
056833	MINISIT gas valve adjustment range 100°-340°C inlet Ø1/2"F outlet Ø3/8"F cap. length 1050 mm nick. bulb Ø5x70 mm	



MINISIT series



Code	Spare Part Description	Picture
0G2402	MINISIT gas valve Adjustment range 100°-340°C Inlet Ø1/2" F outlet Ø3/8" F Cap.length 1050 mm nick. Bulb Ø4x72 mm	
054267	MINISIT gas valve adjustment range 50°-190°C inlet Ø1/2" F outlet Ø3/8" F cap. length 1200 mm nick. bulb Ø5x95 mm	
003655	MINISIT gas valve adjustment range 110°-190°C inlet Ø1/2" F outlet Ø3/8" F cap. length 1050 mm nick. bulb Ø6x105 mm	
058496	MINISIT gas valve Adjustment range 110°-190°C Inlet Ø1/2" F outlet Ø3/8" F Thermocouple connection M9x1 Cap.length 1050 mm nick. Bulb Ø6x105 mm	

EUROSIT series

Code	Spare Part Description	Picture
003334	EUROSIT gas valve adjustment range 110°-190°C inlet Ø3/8" F outlet Ø3/8" F cap. length 1000 mm bulb Ø4x202 mm	
056009	Sealing plug For inlet and outlet 3/8"	



EUROSIT series

Code	Spare Part Description	Picture
0C6235	EUROSIT gas valve adjustment range 80-320°C inlet Ø3/8"F outlet Ø3/8"F thermocouple connection M9x1 cap. length 1000 mm bulb Ø4x72 mm	
0G2294	EUROSIT oven gas valve Adjustment range 100°-340°C Inlet Ø3/8"F outlet Ø3/8"F Thermocouple connection M9x1 cap.length 1050 mm Bulb Ø4x72 mm	

MINISIT, EUROSIT accessories

Code	Spare Part Description	Picture
0C8410	Piezo igniter Model MINISIT with cover Faston for ignition 6.35x0.8 mm	
054268	MINISIT knob	
0C8450	Piezo igniter Model MINISIT Male faston Ø 2.4 mm For Ø 22 mm hole	
054271	MINISIT sealing ring For valve MINISIT 60-200°C Capillary length 1200 mm bulb Ø5x95mm nick.	
0CB766	Thermostatic element for valve MINISIT 60-200°C Capillary length 1200 mm bulb Ø5x95mm nick	





MINISIT, EUROSIT accessories




Code	Spare Part Description	Picture
0CB767	Thermostatic element for valve MINISIT 100-200°C Capillary length 1050 mm bulb Ø6x105 mm	
056592	Thermostatic element for valve MINISIT 100-340°C Capillary length 1050 mm bulb Ø5x70 mm nick.	
052671	Double cone for pipe Ø16mm for MINISIT and PEL 23 (h 9mm)	
052833	Connector and double cone Ø 4 mm	
052834	Connector and double cone Ø 6 mm	
056587	Magnetic group For valve "MINISIT" For code 052431-052068	
056009	Sealing plug For inlet and outlet 3/8"	
052668	Connection for double cone Ø 16 mm MINISIT	




MINISIT, EUROSIT accessories

Code	Spare Part Description	Picture
056835	Inlet elbow 1/2" for MINISIT	
054270	Outlet elbow 3/8" for MINISIT	

ELETTROSIT series






Code	Spare Part Description	Picture
057543	ELETTROSIT gas valve inlet Ø3/4"F outlet Ø3/4"F power supply 230V 50Hz long buttons pilot connection and side thermocouple	
054437	ELETTROSIT gas valve Inlet Ø3/4"F outlet Ø3/4"F Power supply 24V 50Hz Pilot connection and lower thermocouple 11/32" with minimum adj. screw Ø2 mm	
0A2035	ELETTROSIT gas valve Inlet Ø3/4"F outlet Ø3/4"F Power supply 230V 50Hz Pilot connection and lower thermocouple	

NOVA series


Code	Spare Part Description	Picture
055446	820 NOVA gas valve inlet-outlet Ø1/2" F thermocouple connection M9x1 power supply 230V 50Hz	



NOVA series

Code	Spare Part Description	Picture
006182	820 NOVA gas valve Inlet-outlet Ø1/2" F Power supply 230V 60Hz Thermocouple connection M9x1	
059473	822 NOVA gas valve Inlet-outlet Ø1/2" FF Power supply 230V 50 Hz	
002903	820 NOVA gas valve inlet-outlet Ø1/2" F power supply 230V 50Hz without slow ignition level	
002606	820 NOVA mV gas valve inlet-outlet Ø1/2" FF thermocouple connection M9x1 power supply via thermopile with two wires	
0C2408	822 NOVA gas valve Inlet-outlet Ø1/2" FF Thermocouple connection M9x1 Pressure adj. range 5÷50 mbar Power supply 24V 50 Hz Ambient temperature 0÷70 °C	

TANDEM-SIGMA series



Code	Spare Part Description	Picture
002714	836 TANDEM gas valve Inlet-outlet Ø1/2" F Power supply 230V 50Hz - 27mA rectified Pressure adj. range 2÷50 mbar Ambient temperature 0÷60 °C	



TANDEM-SIGMA series

Code	Spare Part Description	Picture
OK5838	830 TANDEM gas valve Inlet-outlet Ø1/2" F Power supply 230V 50Hz Flow regulator blind screw Ambient temperature 0÷60 °C	
OC7600	840 SIGMA gas valve Inlet-outlet Ø 3/4" M Power supply 230V 50Hz Pressure adj. range 2-50mbar	
OC9642	Double valve coil 840 SIGMA 230V 50Hz	
002340	830 TANDEM gas valve Inlet-outlet Ø1/2" F Power supply 230V 50Hz Pressure adj. range 3÷50 mbar Ambient temperature 0÷60 °C	
005526	830 TANDEM gas valve Inlet-outlet Ø1/2" F Pressure adj. range 3÷50 mbar Power supply 24V 50Hz Ambient temperature 0÷60 °C	

ELETTROSIT, NOVA, TANDEM, SIGMA accessories

Code	Spare Part Description	Picture
056589	Magnetic group	
OK3020	Valve coil SIT 820 NOVA 220÷240 V 50 Hz	





ELETTROSIT, NOVA, TANDEM, SIGMA accessories





Code	Spare Part Description	Picture
059305	Gas valve extension	
059326	Gas valve gasket	
003209	Protection seal Tap	
0C8085	Electrical connector	
054539	Ignition contact electr. without cables for ELETTROSIT, SIT 820 NOVA	
056601	Ignition contact electr. with cable 920 mm For ELETTROSIT and SIT 820 NOVA	
002452	Valve coil 830 Tandem	



ELETTROSIT, NOVA, TANDEM, SIGMA accessories




Code	Spare Part Description	Picture
003704	Valve button cover (knob) Ø 30 mm	
002607	Thermopile 588 mm 588 mm	

MERTIK series




Code	Spare Part Description	Picture
0C5249	Mertik gas valve 30-110°C thermocouple connection M9x1 connections 3/8" ignition cable/bulb and capillary	
0C5248	Mertik gas valve 110-190°C thermocouple connection M9x1 connections 3/8" ignition cable/bulb and capillary	
0C5245	Mertik gas valve 100-340°C thermocouple connection M9x1 connections 3/8" ignition cable/bulb and capillary	
006574	Mertik gas valve 110-190°C Thermocouple connection M9x1 Connections 3/8" Ignition cable/bulb and capillary for fryer HD 900	



MERTIK series

Code	Spare Part Description	Picture
0C5250	Mertik gas valve 55-280°C thermocouple connection M9x1 connections 3/8" ignition cable/bulb and capillary	
0C5246	Mertik gas valve 100-340°C thermocouple connection M9x1 connections 3/8" ignition cable/bulb and capillary	
0C5247	Mertik gas valve 100-340°C thermocouple connection M9x1 connections 3/8" ignition cable/bulb and capillary	

MERTIK accessories

Code	Spare Part Description	Picture
006465	Mertik knob seal dim. Ø 39 mm h 4.8 mm	
0C0625	Sealing plug inlet and outlet 3/8	
0C5400	Valve knob adapter	



MERTIK accessories

Code	Spare Part Description	Picture
0C6134	Minimum adj. Screw without hole	
0C7190	Ignition cable for Mertik valves L=1550 mm faston for ignition Ø 2.4 mm faston for spark plug Ø 4 mm	
0G8684	Magnet unit suitable for Mertik L=32 mm Ø top: 14 mm Ø bottom: 19 mm	
0C5481	Minimum adj. screw Ø 0.80 mm	
006466	Minimum adj. screw Ø 0.90 mm	
006467	Minimum adj. screw Ø 1.00 mm	



MERTIK accessories

Code	Spare Part Description	Picture
006651	Minimum adj. screw Ø 1.10 mm	
006652	Minimum adj. screw Ø 1.25 mm	
006475	Minimum adj. screw Ø 1.30 mm	
0C1734	Minimum adj. screw Ø 1.50 mm	
006463	Minimum adj. screw Ø 1.60 mm	
0C4156	Minimum adj. screw Ø 1.75 mm	



MERTIK accessories


Code	Spare Part Description	Picture
0C3587	Minimum adj. screw Ø 1.80 mm	
006653	Minimum adj. screw Ø 1.90 mm	
006654	Minimum adj. screw Ø 2.00 mm	
006472	Minimum adj. screw Ø 2.25 mm	
006473	Minimum adj. screw Ø 2.40 mm	
0C1735	Minimum adj. screw Ø 2.60 mm	

Valves for water, gas and steam

Code	Spare Part Description	Picture
004486	Water ball valve Ø1/2" MF Aluminum lever,PN25 Heavy duty series	
OCA947	Water ball valve Ø1" FF Aluminum lever, PN40 Heavy duty series	
002033	Water ball valve 1/2" FF. Aluminum lever, PN50	
056843	Water ball valve 3/8" FF Aluminum butterfly, PN40	
OK7222	Gas/water ball valve Ø3/4" FF Aluminum butterfly PN40 heavy duty series DIN-DVGW approved	
0A5258	Water ball valve Ø3/8" MF Aluminum lever,PN40 Heavy duty series	
OC9658	Water ball valve Ø3/8" FF Aluminum butterfly complete with pin, nut and bracket	
OS2530	Air valve Water valve Ø3 / 4 " . 3 ways, aluminum lever	




Valves for water, gas and steam





Code	Spare Part Description	Picture
058647	Water ball valve ½" FF PN40 pin 10x7,5mm	
0S0143	Angle steam valve Hexagonal type with connection 1" 1/4F	
008019	Angle safety group for steam Ø 1"1/4M Calibration pressure 0.5 bar Safety valve with spring device Complete with accessories for valve	
017055	Pressure gauge for pots Ø 1/4" M Ø 1/4" M In chromed brass Ø 52.5 mm with adapter Ø 3/8" Scale 0 to 1 bar	
0S0141	Pressure gauge holder tap Ø 3/8 M	
038020	Angle steam valve Round type with connection 1"M	
0S2411	Verticale safety group for steam Ø 3/4" Calibration pressure 0.5 bar Safety valve with spring device Complete with accessories for valve with pressure gauge valve H 185 mm	



Valves for water, gas and steam


Code	Spare Part Description	Picture
051566	Depression valve Ø 3/8"	
OK3442	VACUUM VALVE 3/4"	

Extractor fans, regulators and filters

Code	Spare Part Description	Picture
OS0708	Centrifugal fan DDM 7/7 with double suction with impeller with forward curved blades directly coupled. Complete with intake protection grill. 184W 1400 rpm 4 poles 1 speed Power supply 230V single-phase 50 Hz	
OS0709	Centrifugal fan DDM 9/9 with double suction with impeller with forward curved blades directly coupled. Complete with intake protection grill. 550W 1400 rpm 4 poles 1 speed Power supply 230V single-phase 50 Hz	
OPE621	Centrifugal fan DDM 7/7 with double suction with impeller with forward curved blades directly coupled. Complete with intake protection grill. 300W 1400 rpm 4 poles 1 speed; power supply 230V single-phase 50 Hz	
032279	Speed regulator Single-phase IP55 - Power 1170 W - Max 6 AMP - dim. 135x74x73h mm	



Extractor fans, regulators and filters

Code	Spare Part Description	Picture
OS0710	Speed regulator Single-phase IP55 - Power 1700 W - Max 8 AMP - dim. 160x80x95h mm	
OPR284	Feet for DD 7/7	
OPR285	Feet for DD 9/9	
OPR286	Flange for DD 7/7	
OPR287	Flange for DD 9/9	
OPE616	Centrifugal fan DA 10/8 with double suction with impeller with forward curved blades directly coupled. Complete with intake protection grill. 550W 1400 rpm 4 poles 1 speed; power supply 230V single-phase 50 Hz	
032986	Speed regulator Single-phase IP55 - Power 1700 W - Max 8 AMP - dim. 170x105x82h mm	
OS1021	Mesh filter in AISI 304 for extractor hoods s/steel. Frame formed internally of 6 layers s/steel (4 corrugated layers and 2 flat layers) dim. 350x500x22 mm	
OS0052	Mesh filter in AISI 304 for extractor hoods s/steel. Frame formed internally of 6 layers s/steel (4 corrugated layers and 2 flat layers) dim. 400x250x22 mm	





Extractor fans, regulators and filters

Code	Spare Part Description	Picture
OS0050	Mesh filter in AISI 304 for extractor hoods s/steel. Frame formed internally of 6 layers s/steel (4 corrugated layers and 2 flat layers) dim. 400x400x22 mm	
OS0049	Mesh filter in AISI 304 for extractor hoods s/steel. Frame formed internally of 6 layers s/steel (4 corrugated layers and 2 flat layers) dim. 400x500x22 mm	
OS2575	Mesh filter in AISI 304 for extractor hoods s/steel. Frame formed internally of 6 layers, s/steel (4 corrugated layers and 2 flat layers) dim. 500x500x22 mm	
OS1814	Active carbon In 25 kg bag B.E.T. surface 750 m2/g	
032267	Dedalus labyrinth filter In AISI 304 for extractor hoods dim. 400x250x30 mm	
032268	Dedalus labyrinth filter In AISI 304 for extractor hoods dim. 400x350x30 mm	
032269	Dedalus labyrinth filter In AISI 304 for extractor hoods dim. 400x500x30 mm	
OS2402	Labyrinth filter in AISI 304 for extractor hoods dim. 400x250x22 mm	
OS2403	Labyrinth filter in AISI 304 for extractor hoods dim. 400x350x22 mm	



Extractor fans, regulators and filters








Code	Spare Part Description	Picture
0S2404	Labyrinth filter in AISI 304 for extractor hoods dim. 400x400x22 mm	
0S2405	Labyrinth filter in AISI 304 for extractor hoods dim. 400x500x22 mm	

Hermetic condensing units

Code	Spare Part Description	Picture
OS0762	Hermetic condensing units R134A, HMBP, capillary expansion device, cooling capacity at amb. temp. +32°C dim. 450x300x270 mm Connections: In: 6 Out: 10	
OS0764	Hermetic condensing units R134A, HMBP, expansion valve, cooling capacity at amb. temp. +32°C dim. 450x300x270 mm Connections: In: 6 Out: 10	
OS0765	Hermetic condensing units R134A, HMBP, expansion valve, cooling capacity at amb. temp. +32°C dim. 480x330x295 mm Connections: In: 6 Out: 10	
OS2187	Hermetic condensing units R134A, HMBP, expansion valve, cooling capacity at amb. temp. +32°C dim. 490x385x295 mm Connections: In: 6 Out: 10	
OS0770	Hermetic condensing units R404A, HMBP, capillary expansion device, cooling capacity at amb. temp. +32°C dim. 450x300x270 mm Connections: In: 6 Out: 10	
OS0771	Hermetic condensing units R404A, HMBP, capillary expansion device, cooling capacity at amb. temp. +32°C dim. 480x330x295 mm Connections: In: 6 Out: 10	
OS0772	Hermetic condensing units R404A, HMBP, capillary expansion device, cooling capacity at amb. temp. +32°C dim. 480x330x295 mm Connections: In: 6 Out: 10	




Hermetic condensing units

Code	Spare Part Description	Picture
OS0980	Hermetic condensing units R404A, HMBP, capillary expansion device, cooling capacity at amb. temp. +32°C dim. 500x330x297 mm Connections: In: 6 Out: 10	
OS1906	Hermetic condensing units R404A, HMBP, expansion valve, cooling capacity at amb. temp. +32°C dim. 450x300x270 mm Connections: In: 6 Out: 10	
OS0774	Hermetic condensing units R404A, HMBP, expansion valve, cooling capacity at amb. temp. +32°C dim. 450x300x270 mm Connections: In: 6 Out: 10	
OS0775	Hermetic condensing units R404A, HMBP, expansion valve, cooling capacity at amb. temp. +32°C dim. 480x330x295 mm Connections: In: 6 Out: 10	
OS0776	Hermetic condensing units R404A, HMBP, expansion valve, cooling capacity at amb. temp. +32°C dim. 480x330x295 mm Connections: In: 6 Out: 10	
OS2471	Hermetic condensing units R404A, HMBP, expansion valve, cooling capacity at amb. temp. +32°C dim. 490x385x295 mm Connections: In: 6 Out: 10	
OS1664	Hermetic condensing units R404A, HMBP, expansion valve, cooling capacity at amb. temp. +32°C dim. 490x385x295 mm Connections: In: 6 Out: 10	








Hermetic condensing units

Code	Spare Part Description	Picture
OS1033	Hermetic condensing units R404A, HMBP, expansion valve, cooling capacity at amb. temp. +32°C dim. 490x385x345 mm Connections: In: 6 Out: 10	
OS1388	Hermetic condensing units R404A, HMBP, expansion valve, cooling capacity at amb. temp. +32°C dim. 490x385x345 mm Connections: In: 10 Out: 12	
OS1387	Hermetic condensing units R404A, HMBP, expansion valve, cooling capacity at amb. temp. +32°C dim. 490x700x346 mm Connections: In: 10 Out: 12	
OS0982	Hermetic condensing units R404A, LBP, capillary expansion device, cooling capacity at amb. temp. +32°C dim. 480x330x295 mm Connections: In: 6 Out: 10	
OS0983	Hermetic condensing units R404A, LBP, expansion valve, cooling capacity at amb. temp. +32°C dim. 500x330x295 mm Connections: In: 6 Out: 10	
OS2117	Hermetic condensing units R404A, LBP, expansion valve, cooling capacity at amb. temp. +32°C dim. 500x330x295 mm Connections: In: 6 Out: 10	
OS2217	Hermetic condensing units R404A, LBP, expansion valve, cooling capacity at amb. temp. +32°C dim. 490x385x345 mm Connections: In: 10 Out: 12	




Hermetic condensing units

Code	Spare Part Description	Picture
OS1625	Hermetic condensing units R404A, LBP, expansion valve, cooling capacity at amb. temp. +32°C dim. 490x700x346 mm Connections: In: 10 Out: 12	
OS0766	Hermetic condensing units R134A, HMBP, expansion valve, cooling capacity at amb. temp. +43°C dim. 425x340x245 mm Connections: In: 1/4" Out: 3/8"	
OS0767	Hermetic condensing units R134A, HMBP, expansion valve, cooling capacity at amb. temp. +43°C dim. 425x350x270 mm Connections: In: 1/4" Out: 3/8"	
OS0768	Hermetic condensing units R134A, HMBP, expansion valve, cooling capacity at amb. temp. +43°C dim. 425x350x270 mm Connections: In: 1/4" Out: 3/8"	
OS0777	Hermetic condensing units R404A, HMBP, expansion valve, cooling capacity at amb. temp. +43°C dim. 425x330x245 mm Connections: In: 1/4" Out: 3/8"	
OS0778	Hermetic condensing units R404A, HMBP, expansion valve, cooling capacity at amb. temp. +43°C dim. 450x355x270 mm Connections: In: 1/4" Out: 3/8"	
OS0779	Hermetic condensing units R404A, HMBP, expansion valve, cooling capacity at amb. temp. +43°C dim. 425x355x270 mm Connections: In: 1/4" Out: 3/8"	



Hermetic condensing units

Code	Spare Part Description	Picture
0S0783	Hermetic condensing units R404A, LBP, expansion valve, cooling capacity at amb. temp. +43°C dim. 545x425x350 mm Connections: In: 3/8 Out: 5/8	

Hermetic compressors

Code	Spare Part Description	Picture
093267	Hermetic compressor R134a HMBP Model: EMT6144Z Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 5,20 Motor type: CSIR	
093207	Hermetic compressor R134a HMBP Model: EMT6160Z Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 6,76 Motor type: CSIR	
093206	Hermetic compressor R134a HMBP Model: EMT6170Z Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 7,69 Motor type: CSIR	
093379	Hermetic compressor R134a HMBP Model: NEK6187Z Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 10,00 Motor type: CSIR	



Hermetic compressors

Code	Spare Part Description	Picture
093297	Hermetic compressor R134a HMBP Model: NEK6210Z Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 14,30 Motor type: CSIR	
093484	Hermetic compressor R134a HMBP Model: NEK6214Z Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 14,30 Motor type: CSIR	
092312	Hermetic compressor R134a HMBP Model: NT6215Z Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 17,40 Motor type: CSIR	
093454	Hermetic compressor R134a HMBP Model: NJ6220Z Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 26,20 Motor type: CSIR	
093474	Hermetic compressor R134a HMBP Model: NJ6226Z Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 34,37 Motor type: CSR	
092337	Hermetic compressor R404a/R507 HMBP Model: EMT6144GK Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 3,97 Motor type: CSIR	






Hermetic compressors

Code	Spare Part Description	Picture
0S1499	Hermetic compressor R404a/R507 HMBP Model: EMT6152GK Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 4,50 Motor type: CSIR	
093208	Hermetic compressor R404a/R507 HMBP Model: EMT6165GK Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 5,20 Motor type: CSIR	
093373	Hermetic compressor R404a/R507 HMBP Model: NEK6181GK Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 7,28 Motor type: CSIR	
093377	Hermetic compressor R404a/R507 HMBP Model: NEK6181GK Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 7,28 Motor type: CSIR	
091161	Hermetic compressor R404a/R507 HMBP Model: NEK6213GK Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 12,12 Motor type: CSIR	
092239	Hermetic compressor R404a/R507 HMBP Model: NEK6217GK Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 14,30 Motor type: CSIR	



Hermetic compressors

Code	Spare Part Description	Picture
0S1824	Hermetic compressor R404a/R507 HMBP Model: NJ9226GK Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 21,70 Motor type: CSIR	
093426	Hermetic compressor R290 MBP/HMBP/LBP Model: EMT6152U Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 5,19 Power HP: 1/4 Motor type: CSIR Field of application: MBP	
093425	Hermetic compressor R290 MBP/HMBP/LBP Model: EMT6144U Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 4,50 Power HP: 1/5 Motor type: CSIR Field of application: HMBP	
0S2611	Hermetic compressor R290 MBP/HMBP/LBP Model: NEK2150U Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 13,54 Power HP: 1/2 Motor type: CSIR Field of application: LBP	
0S1922	Hermetic compressor R290 MBP/HMBP/LBP Model: NEK2160U Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 16,80 Power HP: 3/4 Motor type: CSR Field of application: LBP	
093727	Hermetic compressor R290 MBP/HMBP/LBP Model: NT2160U Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 17,40 Power HP: 3/4 Motor type: CSR Field of application: LBP	



Hermetic compressors

Code	Spare Part Description	Picture
0S1960	Hermetic compressor R290 MBP/HMBP/LBP Model: NT2170U Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 20,40 Power HP: 3/4 Motor type: CSR Field of application: LBP	
0S2612	Hermetic compressor R290 MBP/HMBP/LBP Model: SC21CNX2A Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 20,95 Power HP: 1 Motor type: CSIR Field of application: LBP	
0S2613	Hermetic compressor R290 MBP/HMBP/LBP Model: TL5CN Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 5,08 Power HP: 1/5 Motor type: CSIR Field of application: LMBP	
0S1936	Hermetic compressor R600a LBP Model: HVY57AA Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 5,73 Power HP: 1/9 Motor type: RSIR Field of application: LBP	
0S2098	Hermetic compressor R600a LBP Model: EMT40CLP Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 7,23 Power HP: 1/8 Motor type: RSIR Field of application: LBP	
0S1959	Hermetic compressor R600a LBP Model: HQM80AA Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 8,10 Power HP: 1/7 Motor type: RSIR Field of application: LBP	



Hermetic compressors

Code	Spare Part Description	Picture
0S2531	Hermetic compressor R600a LBP Model: N1112Y Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm3): 8,10 Power HP: 1/5 Motor type: RSCR Field of application: LBP	
0S2186	Hermetic compressor R600a LBP Model: EMX40CLC Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm3): 7,23 Power HP: 1/7 Motor type: RSCR Field of application: LBP	
0S2614	Hermetic compressor R600a LBP Model: EMX55CLC Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm3): 9,04 Power HP: 1/6 Motor type: RSCR Field of application: LBP	
0S2615	Hermetic compressor R600a LBP Model: EMYE70CLP Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm3): 11,14 Power HP: 1/4 Motor type: RSCR Field of application: LBP	
093374	Hermetic compressor R404a/R507 LBP Model: NEK2134GK Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm3): 8,78 Motor type: ---	
093630	Hermetic compressor R404a/R507 LBP Model: NEK2150GK Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm3): 12,12 Motor type: ---	









Hermetic compressors

Code	Spare Part Description	Picture
093787	Hermetic compressor R404a/R507 LBP Model: NT2168GK Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm3): 14,50 Motor type: ---	
092785	Hermetic compressor R404a/R507 LBP Model: NT2178GK Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm3): 17,40 Motor type: ---	
093735	Hermetic compressor R404a/R507 LBP Model: NT2180GK Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm3): 20,40 Motor type: ---	
093424	Hermetic compressor R404a/R507 LBP Model: NT2192GK Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm3): 22,40 Motor type: ---	
084076	Hermetic compressor R404a/R507 LBP Model: NJ2192GK Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm3): 26,00 Motor type: ---	
085097	Hermetic compressor R404a/R507 LBP Model: NT2180GK Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm3): 20,40 Motor type: ---	



Hermetic compressors

Code	Spare Part Description	Picture
085501	Hermetic compressor R134a HMBP Model: GL45TB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm3): 4,50 Power HP: 1/6 Motor type: CSIR Rubbers and spacers code 0S0604 not included	
085876	Hermetic compressor R134a HMBP Model: GL60TB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm3): 5,67 Power HP: 1/5 Motor type: CSIR Rubbers and spacers code 0S0604 not included	
083735	Hermetic compressor R134a HMBP Model: GL80TB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm3): 7,57 Power HP: 1/5 Motor type: CSIR Rubbers and spacers code 0S0604 not included	
083718	Hermetic compressor R134a HMBP Model: GL90TB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm3): 8,85 Power HP: 1/4 Motor type: CSIR Rubbers and spacers code 0S0604 not included	
083752	Hermetic compressor R134a HMBP Model: GP12TB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm3): 12,00 Power HP: 3/8 Motor type: CSIR Rubbers and spacers code 0S0604 not included	
083728	Hermetic compressor R134a HMBP Model: GP14TB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm3): 14,00 Power HP: 3/8 Motor type: CSIR Rubbers and spacers code 0S0604 not included	



Hermetic compressors

Code	Spare Part Description	Picture
091575	Hermetic compressor R134a HMBP Model: GX18TB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 18,40 Power HP: 1/2 Motor type: CSIR	
083989	Hermetic compressor R134a HMBP Model: GS26TB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 25,93 Power HP: 3/4 Motor type: CSR	
084763	Hermetic compressor R134a HMBP Model: GS34TB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 34,42 Power HP: 1 Motor type: CSR	
OT3259	Hermetic compressor R404a/R507 HMBP Model: ML45TB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 4,50 Power HP: 1/5 Motor type: CSIR	
089170	Hermetic compressor R404a/R507 HMBP Model: ML60TB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 5,67 Power HP: 1/4 Motor type: CSIR Rubbers and spacers code OS0604 not included	
092288	Hermetic compressor R404a/R507 HMBP Model: ML80TB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 7,57 Power HP: 3/8 Motor type: CSIR	



Hermetic compressors

Code	Spare Part Description	Picture
OT3290	Hermetic compressor R404a/R507 HMBP Model: ML90TB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 8,85 Power HP: 3/8 Motor type: CSIR Rubbers and spacers code OS0604 not included	
OT3291	Hermetic compressor R404a/R507 HMBP Model: MP14TB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 14,00 Power HP: 1/2 Motor type: CSR Rubbers and spacers code OS0604 not included	
OT3261	Hermetic compressor R404a/R507 HMBP Model: MX18TB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 18,39 Power HP: 7/8 Motor type: CSR Rubbers and spacers code OS0604 not included	
OA9615	Hermetic compressor R404a/R507 LBP Model: MP14FB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 14,00 Power HP: 1/2 Motor type: CSIR Rubbers and spacers code OS0604 not included	
091221	Hermetic compressor R404a/R507 LBP Model: MX18FB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 18,4 Power HP: 5/8 Motor type: CSR	
092289	Hermetic compressor R404a/R507 LBP Model: MX23FB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 23,2 Power HP: 7/8 Motor type: CSR	






Hermetic compressors


Code	Spare Part Description	Picture
0A9727	Hermetic compressor R404a/R507 LBP Model: MS34FB Power supply (Volt/Ph/Hz): 220-240/1/50 Displacement (cm ³): 34,42 Power HP: 1 Motor type: CSR	
0A8764	Start capacitor F: 50 F Voltage: 260 V Hz: 50Hz	
092331	Start capacitor F: 48 F Voltage: 330 V Hz: 50Hz	
082640	Compressor accessories F: 80 F Voltage: 330 V Hz: 50/60Hz	
0A9228	Start capacitor F: 72/88 F Voltage: 330 V Hz: 50/60Hz	
083449	Compressor accessories F: 88/108 F Voltage: 330 V Hz: 50/60Hz	
099747	Start capacitor F: 88/108 F Voltage: 330 V Hz: 50/60Hz	
087385	Compressor accessories F: 130/156 F Voltage: 330 V Hz: 50/60Hz	



Hermetic compressors






Code	Spare Part Description	Picture
083406	Compressor accessories F: 5 F Voltage: 420V Hz: 50/60Hz	
083156	Compressor accessories F: 16F Voltage: 400V Hz: 50/60Hz	
087201	Compressor accessories F: 20 F Voltage: 450V Hz: 50/60Hz	
0S0604	Compressor accessories	

Digital temperature controllers

Code	Spare Part Description	Picture
0S1642	Digital temperature controller Model: ICPLUS 902 NTC-PTC Power supply (V): 12 Input: 1 NTC / PTC Output: 1 RELAY Ext. Dimensions LxHxD (mm): 78,6x37x59 Hole size LxH (mm): 71x29	
0S1644	Digital temperature controller Model: ICPLUS 902 J/K PT100 Power supply (V): 12 Input: 1 PT100 Output: 1 RELAY Ext. Dimensions LxHxD (mm): 78,6x37x59 Hole size LxH (mm): 71x29	





Digital temperature controllers

Code	Spare Part Description	Picture
OS1645	Digital temperature controller Model: ICPLUS 902 J/K PT100 Power supply (V): 24 Input: 1 PT100 Output: 1 RELAY Ext. Dimensions LxHxD (mm): 78,6x37x59 Hole size LxH (mm): 71x29	
OS1643	Digital temperature controller Model: ICPLUS 915 NTC-PTC Power supply (V): 230 Input: 1 NTC / PTC Output: 1 RELAY Ext. Dimensions LxHxD (mm): 78,6x37x59 Hole size LxH (mm): 71x29	
OS1743	Digital temperature controller Model: IDPLUS 902 NTC-PTC Power supply (V): 12 Input: 1 NTC / PTC / PT1000 Output: 1 RELAY Ext. Dimensions LxHxD (mm): 74x32x59 Hole size LxH (mm): 71x29	
OS1742	Digital temperature controller Model: IDPLUS 902 NTC-PTC Power supply (V): 230 Input: 1 NTC / PTC / PT1000 Output: 1 RELAY Ext. Dimensions LxHxD (mm): 74x32x59 Hole size LxH (mm): 71x29	
OS1453	Digital temperature controller Model: IDPLUS 961 NTC-PTC Power supply (V): 230 Input: 2 NTC / PTC / PT1000 Output: 1 RELAY Ext. Dimensions LxHxD (mm): 74x32x59 Hole size LxH (mm): 71x29	
OS2136	Digital temperature controller Model: IDPLUS 971 NTC-PTC Power supply (V): 230 Input: 2 NTC / PTC / PT1000 Output: 1 RELAY Ext. Dimensions LxHxD (mm): 74x32x59 Hole size LxH (mm): 71x29	
OS1454	Digital temperature controller Model: IDPLUS 974 NTC-PTC Power supply (V): 230 Input: 2 NTC / PTC / PT1000 Output: 3 RELAY Ext. Dimensions LxHxD (mm): 74x32x59 Hole size LxH (mm): 71x29	






Digital temperature controllers



Code	Spare Part Description	Picture
0G8687	Digital temperature controller Model: IDPLUS 974 NTC-PTC Power supply (V): 12 Input: 2 NTC / PTC / PT1000 Output: 3 RELAY Ext. Dimensions LxHxD (mm): 74x32x59	
090074	Digital temperature controller Model: IS 972 LX Output: telephone connection with EWEM 233 Dimensions LxHxD (mm): 74x32x30	
099224	Digital temperature controller Model: EWEM 233 Power supply (V): 230 Input: 2 NTC / PTC Output: 3 RELAY Dimensions LxHxD (mm): 70x85x53	
099221	Digital temperature controller Model: IS 974 LX Output: telephone connection with EWEM 243 Dimensions LxHxD (mm): 74x32x30	
091189	Digital temperature controller Model: EWEM 243 Power supply (V): 230 Input: 2 NTC / PTC Output: 4 RELAY Dimensions LxHxD (mm): 70x85x53	
091207	Digital temperature controller Model: 10-pole connection cable Dimensions LxHxD (mm): 1000 mm	
0S1891	Digital temperature controller Model: EMPLUS600 Power supply (V): 230 Input: 1 NTC / PTC Dimensions LxHxD (mm): 74x32x59 Dimensions LxH (mm): 71x29	
092235	Digital temperature controller Model IR33 - IRELF0EN22 Analogue inputs For 2 probes: PTC/NTC Digital output: 3 outputs on relay 250v (two 8A, one 5A) Serial port output: TTL connections on Phoenix connector not included dim. 71x29mm drilling template dim. 76.2x34.4xdepth 65mm Power sup	



Digital temperature controllers










Code	Spare Part Description	Picture
091642	Digital temperature controller Model IR33 - IRELC0HN21 Analogue inputs For 2 probes: PTC/NTC Digital output: 4 outputs on relay 250v (one 12A two 8A, one 4A) serial port output: TTL connections on Phoenix connector not included dim. 71x29mm drilling template dim. 76.2x34.4xdepth 65mm Power supply 230v (+/-10%) 50/60Hz	
091609	Digital temperature controller Model IR33 - IRELF0EN21 Analogue inputs For 2 probes: PTC/NTC Digital output: 3 outputs on relay 250v (two 8A, one 5A) Serial port output: TTL connections on Phoenix connector not included dim. 71x29mm drilling template dim. 76.2x34.4xdepth 65mm Power supply 230v (+/-10%) 50/60Hz	
092355	Digital temperature controller Model IR33 - IRELF0HN21 Analogue inputs For 2 probes: PTC/NTC Digital output: 3 outputs on relay 250v (two 4A one 12A) Serial port output: TTL Connections on Phoenix connector not included dim. 71x29mm drilling template dim. 76.2x34.4xdepth 79mm Power sup	

Temperature controller accessories

Code	Spare Part Description	Picture
092597	Front cover IR33 complete	
091684	5-way connector pitch 5.08 screw connection 90° num. (from 8 to 12)	










Temperature controller accessories

Code	Spare Part Description	Picture
092662	8-way connector pitch 5.08 screw connection 90°C num. (from 1 to 8)	
092663	3-way connector pitch 5.08 screw connection straight num. (from 13 to 15)	
091682	4-way connector pitch 5.08 screw connection 90°C num. (from 9 to 12)	
092665	5-way connector pitch 5.08 screw connection 90°C num.	
092664	7-way connector pitch 5.08 screw connection straight	
092360	NTC sensor for IR series length 2000 mm	
099743	3-way connector small screw connection 90°C	
099742	2-way connector pitch 5.08 screw connection 90°C	
099740	7-way connector pitch 5.08 screw connection 90°C	




Temperature controller accessories






Code	Spare Part Description	Picture
088998	Connector 3 positions Itch 5.08 screw Connection 90°C	
099741	5-way connector pitch 5.08 screw Connection 90°C	
092174	Silicone cable With bulb 6x20 mm AISI304 Terminal with stripped wires Length 2000 mm	
092178	Silicone cable with bulb 6x40 mm AISI304 Terminal with stripped wires Length 1500 mm	
096125	Silicone cable with bulb 6x40 mm AISI304 Terminal with stripped wires Length 3000 mm	
092176	Silicone cable with bulb 6x20 mm AISI304 Terminal with stripped wires Length 4000 mm	
092182	Silicone cable with bulb 6x40 mm AISI304 Terminal with stripped wires Length 2000 mm	



Temperature controller accessories





Code	Spare Part Description	Picture
083833	Transformer for temperature controllers 12 V power supply: 220/12 V-3 VA dim. 44x45x33 mm	

Anti-acid filter driers





Code	Spare Part Description	Picture
OS1900	Anti-acid filter drier Type: 4305/2 Connections SAE FLARE: 1/4" Volume (cm³): 80 PS (bar): 45 TS (°C), min: -40 TS (°C), max: +60	
OS1823	Anti-acid filter drier Type: 4305/3 Connections SAE FLARE: 3/8" Volume (cm³): 80 PS (bar): 45 TS (°C), min: -45 TS (°C), max: +60	
OS2211	Anti-acid filter drier Type: 4308/2 Connections SAE FLARE: 1/4" Volume (cm³): 130 PS (bar): 45 TS (°C), min: -40 TS (°C), max: +60	
OS1498	Anti-acid filter drier Type: 4308/3 Connections SAE FLARE: 3/8" Volume (cm³): 130 PS (bar): 45 TS (°C), min: -40 TS (°C), max: +60	
OS2212	Anti-acid filter drier Type: 4316/3 Connections SAE FLARE: 3/8" Volume (cm³): 250 PS (bar): 45 TS (°C), min: -40 TS (°C), max: +60	



Anti-acid filter driers





Code	Spare Part Description	Picture
0S2213	Anti-acid filter drier Type: 4316/4 Connections SAE FLARE: 1/2" Volume (cm³): 250 PS (bar): 45 TS (°C), min: -40 TS (°C), max: +60	
092142	Anti-acid filter drier Type: DML 304 Connections SAE FLARE: 1/2" Volume (cm³): 330 PS (bar): 46 TS (°C), min: -40 TS (°C), max: +70	
089791	Anti-acid filter drier Type: DML 305 Connections SAE FLARE: 3/8" Volume (cm³): 330 PS (bar): 46 TS (°C), min: -40 TS (°C), max: +70	
089669	Anti-acid filter drier Type: 4303/2S Connections ODS Ø (in-mm): 1/4" Connections ODM Ø (in-mm): 3/8" Volume (cm³): 50 PS (bar): 45 TS (°C), min: - 40 TS (°C), max: + 80	
0S1497	Anti-acid filter drier Type: 4308/M10S Connections ODS Ø (in-mm): 10 Connections ODM Ø (in-mm): 12 Volume (cm³): 130 PS (bar): 45 TS (°C), min: - 40 TS (°C), max: + 80	
092143	Anti-acid filter drier Type: DML307S Connections ODS Ø (in-mm): 22 Volume (cm³): 330 PS (bar): 46 TS (°C), min: - 40 TS (°C), max: + 70	

Thermostatic valves and orifices

Code	Spare Part Description	Picture
083758	Thermostatic valve Valve type: TN2 Pressure equalization: int. ½" Capillary length (m): 1,5 Connections Flare inlet: 3/8" Flare outlet: ½" Operating range Range N -40 to + 10°C: without MOP Range NM -40 to -5°C: - Range NL -40 to - 15°C: - Danfoss code: 068Z3542 Refrigerant gas: R134a	
OL2378	Thermostatic valve Valve type: TEN2 Pressure equalization: ext. ½" x ¼" Capillary length (m): 1,5 Connections Flare inlet: 3/8" Flare outlet: ½" Operating range Range N -40 to + 10°C: without MOP Range NM -40 to -5°C: - Range NL -40 to - 15°C: - Danfoss code: 068Z3348 Refrigerant gas: R134a	
OS1391	Thermostatic valve Valve type: TS2 Pressure equalization: int. ½" Capillary length (m): 1,5 Connections Flare inlet: 3/8" Flare outlet: ½" Operating range Range N -40 to + 10°C: without MOP Range NM -40 to -5°C: - Range NL -40 to - 15°C: - Danfoss code: 068Z3400 Refrigerant gas: R404a/R507	
OS1393	Thermostatic valve Valve type: TES2 Pressure equalization: ext. ½" x ¼" Capillary length (m): 1,5 Connections Flare inlet: 3/8" Flare outlet: ½" Operating range Range N -40 to + 10°C: without MOP Range NM -40 to -5°C: - Range NL -40 to - 15°C: - Danfoss code: 068Z3403 Refrigerant gas: R404a/R507	



Thermostatic valves and orifices

Code	Spare Part Description	Picture
0A9508	Thermostatic expansion valve Valve type: TS2 Pressure equalization: - Capillary length (m): 1,5 Connections Flare inlet: 3/8" Flare outlet: 1/2" Operating range Range N -40 to + 10°C: Range NM -40 to -5°C: Range NL -40 to - 15°C: MOP -10°C Danfoss code: 068Z3408 Refrigerant gas: R404a/R507	
OS1932	Thermostatic valve Valve type: TEX2 Pressure equalization: ext. 12mm x 6mm Capillary length (m): 1,5 Connections Flare inlet: 3/8" Flare outlet ODF: 1/2" Operating range Range N -40 to + 10°C: without MOP Range NM -40 to -5°C: - Range NL -40 to - 15°C: - Danfoss code: 068Z3305 Refrigerant gas: R22	
OKW895	Thermostatic valve Valve type: TN2 Pressure equalization: int. 1/2" Capillary length (m): 1,5 Connections Flare inlet: 3/8" Flare outlet ODF: 1/2" Operating range Range N -40 to + 10°C: without MOP Range NM -40 to -5°C: - Range NL -40 to - 15°C: - Danfoss code: 068Z3383 Refrigerant gas: R134a	
OT5187	Thermostatic valve Valve type: TES2 Pressure equalization: ext. 1/2" x 1/4" Capillary length (m): 1,5 Connections Flare inlet: 3/8" Flare outlet ODF: 1/2" Operating range Range N -40 to + 10°C: without MOP Range NM -40 to -5°C: - Range NL -40 to - 15°C: - Danfoss code: 068Z3415 Refrigerant gas: R404a/R507	





Thermostatic valves and orifices





Code	Spare Part Description	Picture
OT6225	Thermostatic valve Valve type: TES3 Pressure equalization: ext. ½" x ¼" Capillary length (m): 1,5 Connections Flare inlet: 3/8" Flare outlet ODF: ½" Operating range Range N -40 to + 10°C: - Range NM -40 to -5°C: - Range NL -40 to - 15°C: MOP -10°C Danfoss code: 068Z3430 Refrigerant gas: R404a/R507	
OS2333	Thermostatic valve Valve type: T2-TE2 Orifice type: 0X Danfoss code: 068-2002	
084084	Thermostatic valve Valve type: T2-TE2 Orifice type: 00 Danfoss code: 068-2003	
083016	Thermostatic valve Valve type: T2-TE2 Orifice type: 01 Danfoss code: 068-2010	
083404	Thermostatic valve Valve type: T2-TE2 Orifice type: 02 Danfoss code: 068-2015	
OS2334	Thermostatic valve Valve type: T2-TE2 Orifice type: 03 Danfoss code: 068-2006	
OL2379	Thermostatic valve Valve type: T2-TE2 Orifice type: 04 Danfoss code: 068-2007	
OT5168	Thermostatic valve Valve type: T2-TE2 Orifice type: 05 Danfoss code: 068-2008	



Thermostatic valves and orifices


Code	Spare Part Description	Picture
084941	ORIFICE	
0T5186	VALVE TEN 2 R134A	

Fans and timers






Code	Spare Part Description	Picture
094755	Timer Bigatti SB 3.82 Daily cycle from 1 to 12 Defrosts Adjustable fan delay INTC/PTC Power supply 230V 50Hz dim.mm 72x88x70h	
0S0562	Pentavalent motorfan. 5 different types of fixing with cable Rpm 1300/1550 Input/output power 16/65W 230/240 V 50-60Hz	
0S0563	Pentavalent motorfan. 5 different types of fixing with cable Rpm 1300/1550 Input/output power 25/95W 230/240 V 50-60Hz	
0S0561	Pentavalent motorfan. 5 different types of fixing with cable Rpm 1300/1550 Input/output power 10/38W 230/240 V 50-60Hz	



Fans and timers

Code	Spare Part Description	Picture
0S1119	Pentavalent motorfan 5 different types of fixing with cable Rpm 1300/1550 Input/output power 18/73W 230/240 V 50-60Hz	

Cold room accessories

Code	Spare Part Description	Picture
092602	Ventilated crawl space profile for cold rooms dim. mm 40x70 length 1860 mm	
092604	Ventilated crawl space profile for cold rooms dim. mm 40x70 length 2660 mm	
092606	Ventilated crawl space profile for cold rooms dim. mm 40x70 length 3460 mm	
092603	Ventilated crawl space profile for cold rooms dim. mm 40x70 length 2260 mm	
092605	Ventilated crawl space profile for cold rooms dim. mm 40x70 length 3060 mm	

Contactors

Code	Spare Part Description	Picture
OKV051	Contactor Model: K1-09D01 Coil supply: 400V/50Hz Contacts: 3 NO Nominal load AC3 400V: 9A / 4kW Nominal load AC1 690V: 20A Aux. Cont.: 1 NC Aux. cont. Amperage AC15 400V: 2A	
088557	Contactor Model: K1-09D10 Coil supply: 230V/50Hz Contacts: 3 NO Nominal load AC3 400V: 9A / 4kW Nominal load AC1 690V: 20A Aux. Cont.: 1 NO Aux. cont. Amperage AC15 400V: 2A	
OKZ813	Contactor Model: K2-09A10 Coil supply: 24V/50Hz Contacts: 3 NO Nominal load AC3 400V: 9A / 4kW Nominal load AC1 690V: 25A Aux. Cont.: 1 NO Aux. cont. Amperage AC15 400V: 4A	
OH7051	Contactor Model: K2-12A00-40 Coil supply: 230V/50Hz Contacts: 4 NO Nominal load AC3 400V: 12A / 5,5kW Nominal load AC1 690V: 25A Aux. cont. Amperage AC15 400V: -	
OK3383	Contactor Model: K2-12A01 Coil supply: 230V/50Hz Contacts: 3 NO Nominal load AC3 400V: 12A / 5,5kW Nominal load AC1 690V: 25A Aux. Cont.: 1 NC Aux. cont. Amperage AC15 400V: 4A	
006879	Contactor Model: K2-12A10 Coil supply: 230V/50Hz Contacts: 3 NO Nominal load AC3 400V: 12A / 5,5kW Nominal load AC1 690V: 25A Aux. Cont.: 1 NO Aux. cont. Amperage AC15 400V: 4A	









Contactors

Code	Spare Part Description	Picture
OK3968	Contactor Model: K2-12A10 Coil supply: 24V/50Hz Contacts: 3 NO Nominal load AC3 400V: 12A / 5,5kW Nominal load AC1 690V: 25A Aux. Cont.: 1 NO Aux. cont. Amperage AC15 400V: 4A	
OKJ216	Contactor Model: K2-12A10 Coil supply: 400V/50Hz Contacts: 3 NO Nominal load AC3 400V: 12A / 5,5kW Nominal load AC1 690V: 25A Aux. Cont.: 1 NO Aux. cont. Amperage AC15 400V: 4A	
OKZ812	Contactor Model: K3-18A10 Coil supply: 24V/50Hz Contacts: 3 NO Nominal load AC3 400V: 16A / 7,5kW Nominal load AC1 690V: 25A Aux. Cont.: 1 NO Aux. cont. Amperage AC15 400V: 4A	
OK3385	Contactor Model: K2-23A00-40 Coil supply: 230V/50Hz Contacts: 4 NO Nominal load AC3 400V: 23A / 11kW Nominal load AC1 690V: 45A Aux. Cont.: - Aux. cont. Amperage AC15 400V: -	
OK3384	Contactor Model: K2-23A01 Coil supply: 230V/50Hz Contacts: 3 NO Nominal load AC3 400V: 23A / 11kW Nominal load AC1 690V: 45A Aux. Cont.: 1 NC Aux. cont. Amperage AC15 400V: 4A	
OC9763	Contactor Model: K2-23A01 Coil supply: 230V/50Hz Contacts: 3 NO Nominal load AC3 400V: 23A / 11kW Nominal load AC1 690V: 45A Aux. Cont.: 1 NO Aux. cont. Amperage AC15 400V: 4A	









Contactors

Code	Spare Part Description	Picture
OK9124	<p>Contactor Model: K2-23A10 Coil supply: 24V/50Hz Contacts: 3 NO Nominal load AC3 400V: 23A / 11kW Nominal load AC1 690V: 45A Aux. Cont.: 1 NO Aux. cont. Amperage AC15 400V: 4A</p>	
OKJ217	<p>Contactor Model: K2-23A10 Coil supply: 400V/50Hz Contacts: 3 NO Nominal load AC3 400V: 23A / 11kW Nominal load AC1 690V: 45A Aux. Cont.: 1 NO Aux. cont. Amperage AC15 400V: 4A</p>	
OC2247	<p>Contactor Model: K2-30A00-40 Coil supply: 230V/50Hz Contacts: 4 NO Nominal load AC3 400V: 30A / 15kW Nominal load AC1 690V: 50A Aux. Cont.: - Aux. cont. Amperage AC15 400V: -</p>	
OKV658	<p>Contactor Model: K2-30A10 Coil supply: 230V/50Hz Contacts: 3 NO Nominal load AC3 400V: 30A / 15kW Nominal load AC1 690V: 50A Aux. Cont.: 1NO Aux. cont. Amperage AC15 400V: 4A</p>	
OK9134	<p>Contactor Model: K3-07A40 Coil supply: 230V/50Hz Contacts: - Nominal load AC3 400V: - Nominal load AC1 690V: - Aux. Cont.: 4NO Aux. cont. Amperage AC15 400V: 4A</p>	
OC7622	<p>Contactor Model: K3-10A00-40 Coil supply: 230V/50Hz Contacts: 4NO Nominal load AC3 400V: 10A / 4kW Nominal load AC1 690V: - Aux. cont. Amperage AC15 400V: -</p>	









Contactors

Code	Spare Part Description	Picture
OL0285	Contactor Model: K3-10A01 Coil supply: 230V/50Hz Contacts: 3 NO Nominal load AC3 400V: 10A / 4kW Nominal load AC1 690V: 25A Aux. Cont.: 1NC Aux. cont. Amperage AC15 400V: 4A	
088477	Contactor Model: K3-10A10 Coil supply: 230V/50Hz Contacts: 3 NO Nominal load AC3 400V: 10A / 4kW Nominal load AC1 690V: 25A Aux. Cont.: 1NO Aux. cont. Amperage AC15 400V: 4A	
OL0354	Contactor Model: K3-14A10 Coil supply: 230V/50Hz Contacts: 3 NO Nominal load AC3 400V: 14A / 5,5kW Nominal load AC1 690V: 25A Aux. Cont.: 1NO Aux. cont. Amperage AC15 400V: 4A	
OL0360	Contactor Model: K3-14A10 Coil supply: 24V/50Hz Contacts: 3 NO Nominal load AC3 400V: 14A / 5,5kW Nominal load AC1 690V: 25A Aux. Cont.: 1NO Aux. cont. Amperage AC15 400V: 4A	
OK9132	Contactor Model: K3-22A10 Coil supply: 230V/50Hz Contacts: 3 NO Nominal load AC3 400V: 22A / 11kW Nominal load AC1 690V: 32A Aux. Cont.: 1NO Aux. cont. Amperage AC15 400V: 2A	
OL0355	Contactor Model: K3-24A00 Coil supply: 230V/50Hz Contacts: 3 NO Nominal load AC3 400V: 24A / 11kW Nominal load AC1 690V: 50A Aux. cont. Amperage AC15 400V: -	



Contactors

Code	Spare Part Description	Picture
0L0361	<p>Contactor Model: K3-24A00 Coil supply: 24V/50Hz Contacts: 3 NO Nominal load AC3 400V: 24A / 11kW Nominal load AC1 690V: 50A Aux. cont. Amperage AC15 400V: -</p>	
007080	<p>Contactor Model: K3-32A00 Coil supply: 230V/50Hz Contacts: 3 NO Nominal load AC3 400V: 32A / 15kW Nominal load AC1 690V: 65A Aux. Cont.: - Aux. cont. Amperage AC15 400V: -</p>	
007104	<p>Contactor Model: K3-40A00 Coil supply: 230V/50Hz Contacts: 3 NO Nominal load AC3 400V: 40A / 18,5kW Nominal load AC1 690V: 80A Aux. Cont.: - Aux. cont. Amperage AC15 400V: -</p>	
0C2244	<p>Contactor Model: K3-50A00 Coil supply: 230V/50Hz Contacts: 3 NO Nominal load AC3 400V: 50A / 22kW Nominal load AC1 690V: 110A Aux. Cont.: - Aux. cont. Amperage AC15 400V: -</p>	
0H6545	<p>Contactor Model: TP3250-2S2Ö Coil supply: 230V/50Hz Aux. Cont.: 2NO / 2NC Aux. cont. Amperage AC15 400V: 1,5kW</p>	
0H6544	<p>Contactor Model: TP3250-3S1Ö Coil supply: 230V/50Hz Aux. Cont.: 3NO / 1NC Aux. cont. Amperage AC15 400V: 1,5kW</p>	




Contactors






Code	Spare Part Description	Picture
0H6541	Contactor Model: TP3250-4S Coil supply: 230V/50Hz Aux. Cont.: 4NO Aux. cont. Amperage AC15 400V: 1,5kW	
0K8700	Contactor Model: HA01 red Auxiliary Cont: 1NC Auxiliary contact amperage AC15 400V: 3A	
048497	Contactor Model: HA10 green Auxiliary Cont: 1NO Auxiliary contact amperage AC15 400V: 3A	
0G4291	Contactor Model: HB11 Auxiliary Cont: 1NO / 1NC Auxiliary contact amperage AC15 400V: 2A	
047046	Contactor Model: HN01 red Auxiliary Cont: 1NC Auxiliary contact amperage AC15 400V: 2A	
046995	Contactor Model: HN10 green Auxiliary Cont: 1NO Auxiliary contact amperage AC15 400V: 2A	



Contactors




Code	Spare Part Description	Picture
0H7049	CONTACTOR; 220-240V 50HZ/240-264V 60HZ	

Internal dispensers for dishwashers



Code	Spare Part Description	Picture
0L4295	Rinse aid dispenser Flow adjustment screw from 0 to 4 cm ³ /cycle complete with hose connectors bottom filter with bushing in steel and tube.	
0HA055	Rinse aid dispenser type 1000	
0L3200	Rinse aid dispenser flow adjustment screw from 0 to 4 cm ³ /cycle	
0HA056	Rinse aid dispenser type 3000 with filter	
0S2285	Rinse aid peristaltic pump Model PG 0.4 Flow rate: 0.4 l/h Pressure: 3 bar Power supply: 230 V - 50/60 Hz Complete with: 4 m PE tube 4x6, filter and bottom weight, rinse aid injection valve, ROHS certification	



Internal dispensers for dishwashers




Code	Spare Part Description	Picture
OS0706	Rinse aid peristaltic pump model NBR 0.4 flow rate reg. t/p: 0.4 l/h pressure: 3bar Power supply: 230V- 50Hz complete with: - 2 m suction pipe - 2 m delivery pipe, s/steel bottom weight and filter, injection connection with nonreturn valve for rinse aid - ROHS certification	
OS1986	Detergent peristaltic pump model PG 3 flow rate: 3 l/h pressure: 0.1 bar Power supply: 230V - 50/60 Hz complete with: 4 m PE tube 4x6, filter and bottom weight, passwall ROHS certification	
OS1987	Detergent peristaltic pump model NBR 3 flow rate reg. t/p : 3 l/h pressure: 0.1 bar Power supply: 230V - 50 Hz complete with pipes and connections ROHS certification	

Accessories for internal dispensers


Code	Spare Part Description	Picture
OR0081	Membrane for dispenser type 3000	
OHA092	Membrane for dispenser type 1000	



Accessories for internal dispensers





Code	Spare Part Description	Picture
OR0083	Valve for 1000/3000 set of 5 pcs	
OHA067	Suction filter For dispenser type 3000	
OE3584	Cord for tray conveyor belt with core Ø cord 15 mm (sold by linear metre)	
OHB073	Cord for tray conveyor belt with core Ø cord 12 mm (sold by linear metre)	
OS1230	Cord for tray conveyor belt without core Ø cord 15 mm (sold by linear metre)	

External dispensers for dishwashers

Code	Spare Part Description	Picture
OS0669	Peristaltic pump for detergent. Model PR4 with analogic dosing regulation. Squeeze tubes made in santoprene used as accessory for the dishwashers without built-in dosing systems - easy regulation Supplied with fixing bracket, injection connection, suction tube, outlet tube and filter - power consumption: 3,5w - power supply: 230V, 50Hz - pressure: 0,1 bar - flow: 0,6 - 4l/h Compatible with: glasswasher, undercounter, front loading, hood type, rack type without built-in dosing system	



External dispensers for dishwashers

Code	Spare Part Description	Picture
OS0670	<p>Fixed speed peristaltic pump for detergent. Model PR6 with analogic dosing regulation by conductivity probe, squeeze tubes made in santoprene</p> <ul style="list-style-type: none"> - used as accessory for the dishwashers without built-in dosing systems - easy regulation <p>Supplied with fixing bracket, injection, connection, suction tube, outlet tube filter and conductivity probe</p> <ul style="list-style-type: none"> - power consumption: 3,5w - power supply: 230V, 50Hz - pressure: 0,1 bar - flow: 6l/h <p>Compatible with: glasswasher, undercounter, front loading, hood type, rack type without built-in dosing system</p>	
OS0671	<p>Peristaltic pump for rinse aid. Model PR1 with analogic dosing regulation tubes made in sekobil</p> <ul style="list-style-type: none"> - used as accessory for the dishwashers without built-in dosing systems - easy regulation <p>Supplied with fixing bracket, injection connection with non-return valve, suction tube, outlet tube, filter, pipe connection of "fi" 6-8 mm, for single tank machines</p> <ul style="list-style-type: none"> - power consumption: 3,5w - power supply: 230V, 50Hz - pressure: 3 bar - flow: 0,2 - 1l/h <p>Compatible with: glasswasher, undercounter, front loading, hood type, rack type without built-in dosing system</p>	
OU1032	<p>Dosing pump G200 230V 50Hz; detergent flow rate 0.777g/sec, max flow rate 2 l/h</p>	
OS0672	<p>Dosing system TWINDOSE 40 microprocessor control with LCD display Detergent dosing - conductivity or timed Rinse aid dosing - speed or timed Detergent pump: santoprene tube flow rate 12.5 l/h Rinse aid pump: SekoBril tube flow rate 2.5 l/h 3 bar Max absorp. 20 W Switching power supply from 80 to 265 Vac 50Hz for tunnel machines</p>	

Accessories for external dispensers







Code	Spare Part Description	Picture
0S0674	Injection connection in steel detergent tank inlet (PR4 and PA6)	
0S0675	Low-profile injection connection detergent tank inlet (PR4 and PA6) lot 5pcs	
049358	Injection connection with non-return valve for rinse aid (PR1)	
0S1249	Fitting for rinse aid injector PR1 Pack of 5 pcs	
0S0677	Suction lance with level probe for Twindose 40 with non-return valve in EPDM. used on all products except those based on chlorine sanitiser.	
0S0676	Suction lance with level probe for Twindose 40 with non-return valve in FPM used on products based on chlorine sanitiser	
049419	Santoprene tube for detergent	
0S2122	Seko rinse aid tube connections for dispenser 0S2285 3X8mm with BCK PVDF	



Accessories for external dispensers





Code	Spare Part Description	Picture
049418	Sekobril tube for rinse aid	
0S2121	Santoprene tube for detergent with BCK PVDF connection for dispenser 0S1986 6.25X10.65mm	
049801	Detergent injector	
OL2071	Injector fixing ring	
049359	SUCTION HOSE; 4000 MM	
0S2100	TUBE; 4X6MM;SET 50 MT. DET.; GREY	
OL0481	Tube L=2660 mm; ØE=6 mm; Blue	
0S2101	TUBE; 4X6MM;SET 50 MT BRILL.;LIGHT/BLU	
0S1028	INOX WEIGHT WITH FILTER; KIT	

Faston connection


Code	Spare Part Description	Picture
055350	Single solenoid valve 90° Inlet Ø 3/4" free Outlet Ø 10 mm Blue reducer 1 l/min Max temperature 90°C Coil 220/240 V 50/60 Hz	
055444	Double solenoid valve 90° Inlet Ø 3/4" free Outlet Ø 10 mm Blue reducer 1 l/min Max temperature 90°C Coil 220/240 V 50/60 Hz	
002712	Triple solenoid valve 90° Inlet Ø 3/4" free Outlet Ø 10 mm Red reducer 0.25 l/min Max temperature 90°C Coil 220/240 V 50/60 Hz	
048178	Single solenoid valve 90° Inlet Ø 3/4" 20 l/min Outlet Ø 14 mm free Max temperature 90°C Coil 220/240 V 50/60 Hz	
0E5070	Solenoid valve 24V single 180° Inlet Ø 3/4" free Outlet Ø 14mm free Max temperature 90°C Coil 24 V 50 Hz	
002753	Single solenoid valve 180° Inlet Ø 3/4" free Outlet Ø 10 mm Blue reducer 1 l/min Max temperature 90°C Coil 220/240 V 50/60 Hz	



Faston connection







Code	Spare Part Description	Picture
047536	Double solenoid valve 180° Inlet Ø 3/4" 20 l/min Outlet Ø 10 mm Black reducer 5 l/min Max temperature 90°C Coil 220/240 V 50/60 Hz	
0F0001	Triple solenoid valve 180° Inlet Ø 3/4" outlet Ø 10 mm Yellow reducer 2.5 l/min - Red 0.25 l/min Max temperature 90°C Coil 220/240 V 50/60 Hz	
049230	Double solenoid valve 90° Inlet Ø 3/4" 14 l/min Outlet Ø 14 mm free Max temperature 90°C Coil 220/240 V 50/60 Hz	
048180	Solenoid valve 24V double 180° Inlet Ø 3/4" free Outlet Ø 14mm free Max temperature 90°C Coil 24 V 50 Hz	

P5 connection

Code	Spare Part Description	Picture
0C1933	Single solenoid valve 90° Inlet Ø 3/4" outlet Ø 10 mm Supply connection P5 blue Max temperature 90°C Coil 220/240 V 50/60 Hz	







P5 connection



Code	Spare Part Description	Picture
0C6137	Double solenoid valve 90° Inlet Ø 3/4" outlet Ø 10 mm Reducer 8 l/min - 0.6 l/min Supply connection P5 blue-orange Max temperature 90°C Coil 220/240 V 50/60 Hz	
0C2240	Triple solenoid valve 90° Inlet Ø 3/4" outlet Ø 10 mm Reducer 1.2 l/min-0.25 l/min Supply connection P5 orange-grey-blue Max temperature 90°C Coil 220/240 V 50/60 Hz	
049626	Single solenoid valve 90° Inlet Ø 3/4" 10 l/min Outlet Ø 14 mm free Supply connection P5 orange Max temperature 90°C Coil 220/240 V 50/60 Hz	
049439	Solenoid valve Double outlet 90° Inlet Ø 3/4" 20 l/min Outlet Ø 14 mm free Supply connection P5 orange-green Max temperature 90°C Coil 220/240 V 50/60 Hz	
0C3254	Single solenoid valve 180° Inlet Ø 3/4" outlet Ø 10 mm Supply connection P5 blue Max temperature 90°C Coil 220/240 V 50/60 Hz	
0C5517	Double solenoid valve 180° Inlet Ø 3/4" outlet Ø 10 mm Reducer 5 l/min - 0.25 l/min Supply connection P5 orange-grey Max temperature 90°C Coil 220/240 V 50/60 Hz	



P5 connection

Code	Spare Part Description	Picture
0C1934	Triple solenoid valve 180° inlet Ø 3/4" outlet Ø 10 mm Reducer 1.2 l/min- 0.25 l/min Supply connection P5 orange-grey-blue Max temperature 90°C Coil 220/240 V 50/60 Hz	
0L3446	Single solenoid valve 180° Inlet Ø 3/4" outlet Ø 14 mm Supply connection P5 orange Max temperature 90°C Coil 220/240 V 50/60 Hz	
049668	Solenoid valve Double outlet 180° Inlet Ø 3/4" 20 l/min Outlet Ø 14 mm free Supply connection P5 orange-green Max temperature 90°C Coil 220/240 V 50/60 Hz	
0L3444	Solenoid valve Triple outlet 90° Inlet Ø 3/4" outlet Ø 14 mm Reducer red 0.25 l/min - white Supply connection P5 orange-green-white Max temperature 90°C Coil 220/240 V 50/60 Hz	

Brass solenoid valves - 2-way

Code	Spare Part Description	Picture
0C1148	Solenoid valve, 2-way 1/2" FF For water min/max temperature -10/+90°C min/max pressure 0.2 / 16 bar Coil type BDV 230/240V 50-60Hz 16VA	
068464	Solenoid valve, 2-way 1/2" FF for water min/max temperature -10 / +90°C min/max pressure 0.35 / 12 bar Coil type ZB10A 24V 50-60Hz 4W	



Brass solenoid valves - 2-way

Code	Spare Part Description	Picture
OK5341	Solenoid valve, 2-way 1/4" FF for water min/max temperature -10 / +90°C min/max pressure 0.35 / 20 bar Coil type ZA10A 9W 230V 50Hz 14VA	
OC1121	Solenoid valve, 2-way 3/4" FF For water min/max temperature -10 / +90°C min/max pressure 0.2 / 16 bar Coil type BDA 220/230V 50-60Hz 14.5VA	
OC2390	Solenoid valve, 2-way 1/2"-1.1-4.5 For water min/max temperature -10 / +90°C min/max pressure 0 / 6 bar Coil type ZA34A 230V 50Hz 14VA	
OE2200	Solenoid valve, 2-way 3/4" F for water/steam min/max temperature -10 / +140°C min/max pressure 0.35 / 3.5 bar Coil type MXX-HT 24V 50Hz	
OE5974	Solenoid valve, 2-way 3/4" FF for water/steam min/max temperature -10 / +140°C Steam pressure min/max 0.35 / 3.5 bar Hot water pressure min/max 0.35 / 10 bar Coil type MXX-HT 230V 50Hz 10,5W	
OL1481	Solenoid valve, 2-way 3/4" FF for steam min/max temperature +60 / +170°C min/max pressure 0.4 / 6 bar Coil type Z534A 24V 50-60Hz 14VA	
OL0537	Solenoid valve, 2-way 3/8" FF for water min/max temperature -10 / +90°C min/max pressure 0.35 / 16 bar Coil type ZB14A 230V 50-60Hz 12VA	
OL2656	Solenoid valve, 2-way 3/8" FF for water min/max temperature -10 / +140°C min/max pressure 0.35 / 16 bar Coil type ZB14Y 208-240V 50-60Hz 12VA	



Brass solenoid valves - 2-way



Code	Spare Part Description	Picture
0L2850	Solenoid valve, 2-way 3/8" FF for water min/max temperature -10 / +140°C min/max pressure 0.35 /16 bar Coil type ZB10A 240V 50-60Hz 12VA 4W	
OK8129	Solenoid valve, 2-way 3/4" FF for water/steam min/max temperature -10 / +140°C Steam pressure min/max 0.35 /3.5 bar Hot water pressure min/max 0.35 /10 bar Coil type MXX-HT 24V 60Hz 10,5W	
OL1482	Solenoid valve, 2-way 3/4" FF for steam min/max temperature +60 / +170°C min/max pressure 0.4 /6 bar Coil type Z534A 230V 50-60Hz 14VA	
OL2516	Solenoid valve, 2-way 3/8" FF for water min/max temperature -10 / +140°C min/max pressure 0.35 /16 bar Coil type ZB14A 24V 50-60Hz 12VA 4W	
OL2857	Solenoid valve, 2-way 3/8" FF for water min/max temperature -10 / +140°C min/max pressure 0.35 /20 bar Coil type ZB14A 200V 50-60Hz 12VA	
OL1409	Solenoid valve, 2-way 3/8" FF for water min/max temperature 0 / +140°C min/max pressure 0.35 /16bar coil type ZB14A 24V 50-60Hz 12VA 4W	
OL0423	Solenoid valve, 2-way 3/8" FF for water min/max temperature 0 / +140°C min/max pressure 0.35 /16 bar Coil type ZB14A 230V 50-60Hz 12VA 4W	
003778	Solenoid valve, 2-way 3/4" FF for water min/max temperature 0 / +130°C min/max pressure 0.3 /10 bar Coil type BA2 24V AC 50-60Hz 11VA	

Coils for solenoid valves





Code	Spare Part Description	Picture
OS2268	Magnetic coil type Z610A 230V 50-60Hz	
OS1612	Magnetic coil type Z610A 24VAC 10VA 50-60Hz	
OPRE91	Magnetic coil type ZA34A 230V 50HZ 14VA Housing Ø 14mm For solenoid valve 0C2390	
OCA882	Magnetic coil Type BC2 for solenoid valve 003778	
OS2269	Magnetic coil type ZB10A 230V 50-60Hz 4W	
OS2270	Magnetic coil type ZB10A 24V 50-60Hz 4W	



Coils for solenoid valves

Code	Spare Part Description	Picture
0CA930	Magnetic coil type BA2 24V AC 50Hz 11VA For solenoid valve 003778	
0KA481	Magnetic valve repair kit	

Spare parts - taps and valves


Code	Spare Part Description	Picture
0S1238	Cartridge for single lever taps Euro type Square connection 10x10.5	
0S0346	Cartridge for single lever taps CX42 type Square connection 8x7 and 9x9 for mixer taps 037616 and 037617	
0S2218	Cartridge for single lever taps Euro type for shower set 0S0956 and 0S0894 Square connection 10x10.5	
0S1239	Cartridge for single lever taps AX38 type Square connection 10x10.5	



Spare parts - taps and valves








Code	Spare Part Description	Picture
OS0146	U type spout Ø18X300M	
OS0344	Spout L= 250mm	
OS0134	Tap valve 1/2" for single/double hole group and water column code OS0350 broach connection 8x20	
OS0106	Tap valve for fork groups Ø 3/4"	
OS0063	Tap valves 3/4" for single and double hole groups	
OS0343	Black clinical lever	

Traps - drains - overflows

Code	Spare Part Description	Picture
OS1335	Single trap Ø 1 1/2 in plastic	






Traps - drains - overflows




Code	Spare Part Description	Picture
069821	Single trap Ø 2" in plastic	
0S0905	Double trap Ø 1½" in plastic	
033601	Double trap Ø 2" in plastic	
0C9489	Overflow pipe Ø 40 mm in Stainless Steel H=180 mm	
069656	Overflow pipe Ø 40 mm in chromed brass H=295 mm	
049759	Overflow pipe Ø 50 mm In chromed brass H=280 mm	
0S0119	Overflow pipe Ø 50 mm in s/steel H=270 mm	
0S0118	Overflow pipe Ø 50 mm in chromed brass H=295 mm	
069654	Drain Ø 40 mm in chromed brass connection 1 1/2 "	



Traps - drains - overflows







Code	Spare Part Description	Picture
069816	Drain Ø 50 mm in chromed brass connection 2"	
033607	Drain Ø 2" Plastic frame with steel filter. Connection 2"	
0S1319	Drain Ø 2" Plastic frame and steel filter. 1 1/2" connection with adapter from 2"	

Water inlet and drain hoses

Code	Spare Part Description	Picture
OL1887	Smooth rubber inlet hose int. Ø 10 mm ext. Ø 17 mm Brass ring Yellow zinc plated Ø 3/4"FF Working pressure 10bar Temperature 90°C Connections: straight+90° Length 2000 mm, to WRAS	
OC8316	Rubber inlet hose int. Ø 10mm ext. Ø 16mm nylon ring Ø 3/4"FF Working pressure 10bar Temperature 90°C Connections: straight+90° length 1500 mm to WRAS and VDE	
061488	Gasket Ø 3/4"	



Water inlet and drain hoses

Code	Spare Part Description	Picture
OL1031	Smooth rubber inlet hose; length 2000 mm To WRC Ø 3/4"FF int. Ø 15 mm ext. Ø 25 mm Nickel plated brass ring Max pressure 25bar Temperature 100°C Straight connections	
OS2210	Smooth rubber inlet hose; length 2500 mm To WRC Ø 3/4"FF int. Ø 15 mm ext. Ø 25 mm Nickel plated brass ring Max pressure 25bar Temperature 100°C Straight connections	
OS2214	Smooth rubber inlet hose; length 3000 mm To WRC Ø 3/4"FF int. Ø 15 mm ext. Ø 25 mm Nickel plated brass ring Max pressure 25bar Temperature 100°C Straight connections	
OC3359	S/steel braided inlet hose int. Ø 19 mm, ext. Ø 28 mm nickel plated brass ring Ø 3/4"FF max pressure 25bar, temperature 100°C connections: straight length 2000 mm	
060933	Smooth rubber inlet hose int. Ø 13mm ext. Ø 25mm brass ring nickel plated Ø 3/4"FF Working pressure 10bar Temperature 90°C connections: straight length 1500 mm	
OC8327	Rubber inlet hose int. Ø 13mm ext. Ø 20mm nylon ring Ø 3/4"FF Working pressure 10bar Temperature 90°C Connections: straight+90° length 2100 mm to WRAS and VDE	









Water inlet and drain hoses

Code	Spare Part Description	Picture
069571	S/steel braided inlet hose int. Ø 10 mm, ext. Ø 14 mm Nickel plated brass ring Ø 3/4"FF Max pressure 25bar Temperature 100°C Connections: straight+90° Length 1500 mm	
0S0733	S/steel braided inlet hose; length 1500 mm int. Ø 13mm, ext. Ø 19mm Nickel plated brass ring Ø 3/4"FF Working pressure 10bar Temperature 100°C Connections: straight+90°	
049540	S/steel braided inlet hose; length 2100 mm int. Ø 13mm, ext. Ø 19mm Nickel plated brass ring Ø 3/4"FF Working pressure 10bar Temperature 100°C Connections: straight+90°	
0S1231	S/steel braided inlet hose int. Ø 19 mm, ext. Ø 28 mm Nickel plated brass ring Ø 3/4"FF Max pressure 25bar, Temperature 100°C Connections straight+90° Length 1500 mm	
OL0639	S/steel hose 18/10 fFor shower set Transparent PVC cover Swivel connections Ø1/2" FF L=1050 mm	
OL0644	S/steel hose 18/10 L=1200 mm	
0S1095	S/steel hose 18/10 for shower set Transparent PVC cover Swivel connections Ø1/2" MF L=1050 mm	
0S1094	S/steel hose 18/10 L=1200 mm	



Water inlet and drain hoses




Code	Spare Part Description	Picture
047894	Drain pipe Plastic PVC Impact resistant strengthening spiral Resistant to high temperatures and chemical aggression, smooth inner surface, int. sleeve Ø 58 int. pipe Ø 40 Length 1000 mm	
048818	Drain pipe Plastic PVC Impact resistant strengthening spiral Resistant to high temperatures and chemical aggression, smooth inner surface int. sleeve Ø 35/40, int. pipe Ø 35 Length 1600 mm	
OS1155	S/steel spiral hose Swivel connections Ø1/2" FF L=1050 mm	
OL4552	Flexible drain pipe in polypropylene int. sleeve Ø 35/40, int. pipe Ø 22.5 Length 1600 mm	
047465	Drain pipe Plastic PVC Impact resistant strengthening spiral Resistant to high temperatures and chemical aggression, smooth inner surface int. sleeve Ø 35/40, int. pipe Ø 35 Length 1000 mm	
048845	PVC pump drain pipe Special model Resistant to temp. max 80°C and chemical aggression, int. sleeve Ø 18/28 int. pipe Ø18 Length 2100 mm	
OS2682	DRAIN PIPE	

Pressure switch - 1 level

Code	Spare Part Description	Picture
OPRQ12	PRESSURE SWITCH; 28-12;FC	
OPRAC3	PRESSURE SWITCH; 1 LIVELLO 35/17MBA	
OPRG28	PRESSURE SWITCH	
OS2723	PRESSURE SWITCH	
OPRZ46	PRESSURE SWITCH; 1LIV 55/30	
069434	PRESSURE SWITCH	
049485	PRESSURE SWITCH; KIT; LEV. 55/22	
OPRAD3	PRESSURE SWITCH; 60-25 (P) LB LS	
OPRA7E	PRESSURE SWITCH	
OPRY05	PRESSURE SWITCH; 35/90	
046601	PRESSURE SWITCH; KIT	
OPRX78	PRESSURE SWITCH; TYPE 110/60	
OG2646	PRESSURE SWITCH	
OS2724	PRESSURE SWITCH	
OPRG23	PRESSURE SWITCH; 105/125	
046653	PRESSURE SWITCH; LEV.160/80; KIT	




Pressure switch - 1 level



Code	Spare Part Description	Picture
OPRPDX	PRESSURE SWITCH	
OPRX71	PRESSURE SWITCH; TYPE 180/70	
048267	PRESSURE SWITCH;1 LEV.; LEV.240/130; KIT	
OS2725	PRESSURE SWITCH	
075660	PRESSURE SWITCH	
OS2355	PRESSURE SWITCH	
OKZ785	PRESSURE SWITCH	
OKZ786	PRESSURE SWITCH	
049881	PRESSURE SWITCH;TYPE 760;CALIB.=60/20-11	
049058	PRESSURE SWITCH; CALIBRATION = 110/55	
049775	PRESSURE SWITCH	
049620	PRESSURE SWITCH; CALIB.= 250/130-390	



Pressure switch - 1 level

Code	Spare Part Description	Picture
0C0872	PRESSURE SWITCH	

Pressure switch - 2 levels





Code	Spare Part Description	Picture
0S2726	PRESSURE SWITCH	
ORT319	PRESSURE SWITCH	
OK7149	PRESSURE SWITCH; LEV. 40/10-112/85	
OE3731	PRESSURE SWITCH; LEV. 40/15-55/35	
OK7146	PRESSURE SWITCH; LEV. 60/20-100/30	
049361	PRESSURE SWITCH	
OE5671	PRESSURE SWITCH	
049081	PRESSURE SWITCH	
0S2727	PRESSURE SWITCH	
ORT108	PRESSURE SWITCH; FOR FX	
ORT313	PRESSURE SWITCH	
0S2728	PRESSURE SWITCH	

Automatic water softeners

Code	Spare Part Description	Picture
OS1945	Automatic softener with ALIA valve, capacity 0,6 kg. AISI 304 cylinder: 5 lt Cationic resins for cylinder: 3,5 lt Max flow rate: 1500 lt/h Brine: 10 kg Salt for regener. Cycle: 0,6 kg Supply power: 230V 50/60 Hz Water conn.: Ø 3/4" G Min/max pressure: 2-8 bar Temp. Water supply: 4-30°C WxDxH (mm): 230x360x515	
OS1946	Automatic softener with ALIA valve, capacity 1 kg. AISI 304 cylinder: 8 lt Cationic resins for cylinder: 5,6 lt Max flow rate: 1500 lt/h Brine: 20 kg Salt for regener. Cycle: 1,0 kg Supply power: 230V 50/60 Hz Water conn.: Ø 3/4" G Min/max pressure: 2-8 bar Temp. Water supply: 4-30°C WxDxH (mm): 250x460x540	
OS1947	Automatic softener with ALIA valve, capacity 1,5 kg. AISI 304 cylinder: 12 lt Cationic resins for cylinder: 8,5 lt Max flow rate: 1500 lt/h Brine: 25 kg Salt for regener. Cycle: 1,5 kg Supply power: 230V 50/60 Hz Water conn.: Ø 3/4" G Min/max pressure: 2-8 bar Temp. Water supply: 4-30°C WxDxH (mm): 285x405x595	
OS2457	Automatic softeners GIX TIMED with Autotrol. AISI 304 cylinder: 5 lt Cationic resins for cylinder: 3,5 lt Max flow rate: 1500 lt/h Brine: 10 kg Salt for regener. Cycle: 0,6 kg Supply power: 230V 50/60 Hz Water conn.: Ø 3/4" G Min/max pressure: 2-8 bar Temp. Water supply: 4-25°C WxDxH (mm): 230x385x515	
OS1079	Automatic softeners GIX TIMED with Autotrol. AISI 304 cylinder: 8 lt Cationic resins for cylinder: 5,6 lt Max flow rate: 1500 lt/h Brine: 20 kg Salt for regener. Cycle: 1,0 kg Supply power: 230V 50/60 Hz Water conn.: Ø 3/4" G Min/max pressure: 2-8 bar Temp. Water supply: 4-25°C WxDxH (mm): 245x450x540	







Automatic water softeners

Code	Spare Part Description	Picture
002454	Automatic softeners GIX TIMED with Autotrol. AISI 304 cylinder: 8 lt Cationic resins for cylinder: 5,6 lt Max flow rate: 1500 lt/h Brine: 20 kg Salt for regener. Cycle: 1,0 kg Supply power: 230V 50/60 Hz Water conn.: Ø 3/4" G Min/max pressure: 2-8 bar Temp. Water supply: 4-25°C Coated with stainless steel panels WxDxH (mm): 245x450x540	
0S2458	Automatic softeners GIX TIMED with Autotrol. AISI 304 cylinder: 12 lt Cationic resins for cylinder: 8,5 lt Max flow rate: 1500 lt/h Brine: 25 kg Salt for regener. Cycle: 1,4 kg Supply power: 230V 50/60 Hz Water conn.: Ø 3/4" G Min/max pressure: 2-8 bar Temp. Water supply: 4-25°C WxDxH (mm): 285x425x650	
0S2694	Timed Automatic water softeners with housing, with Autotrol valve 255 Logix 740 12 lt	
0S2695	Water Softner MAXI with housing, with AUTOTROL valve 255 Logix 740, max. flow rate 1500lt/h, 230V 50/60Hz, 24lt fiberglass cylinder with 17lt of cationic resins suitable for softening, salt container 50kg, Ø 3/4" water connection, min/max pressure 2-8 b	
0S2459	Automatic softeners LARGE SERIES VOLUMETRIC with valve, Autotrol 255 Logix 760. Fibreglass cylinder: 50 lt 10"x44" Cationic resins for cylinder: 35 lt Max flow rate: 1500 lt/h Brine: 120 kg Salt for regener. Cycle: 7,2 kg Supply power: 230V 50/60 Hz Water conn.: Ø 3/4" G Min/max pressure: 2-8 bar Temp. Water supply: 4-25°C ØxH (mm): 271x1300 Cylinder ØxH (mm): 541x810 Brine	







Automatic water softeners

Code	Spare Part Description	Picture
OS2460	Automatic softeners LARGE SERIES VOLUMETRIC with valve, Autotrol 255 Logix 760. Fibreglass cylinder: 84 lt 13"x44" Cationic resins for cylinder: 59 lt Max flow rate: 1500 lt/h Brine: 120 kg Salt for regener. Cycle: 12,2 kg Supply power: 230V 50/60 Hz Water conn.: Ø 3/4" G Min/max pressure: 2-8 bar Temp. Water supply: 4-25°C ØxH (mm): 360x1300 Cylinder ØxH (mm): 541x810 Brine	
OS2461	Automatic softeners LARGE SERIES PERFORMA VOLUMETRIC with valve. Fibreglass cylinder: 24 lt 8"x35" Cationic resins for cylinder: 17 lt Max flow rate: 4000 lt/h Brine: 80 kg Salt for regener. Cycle: 2,7 kg Supply power: 230V 50/60 Hz Water conn.: Ø 3/4" G Min/max pressure: 2-8 bar Temp. Water supply: 4-25°C ØxH (mm): 219x1060 Cylinder ØxH (mm): 480x660 Brine	
OS2462	Automatic softeners LARGE SERIES PERFORMA VOLUMETRIC with valve. Fibreglass cylinder: 50 lt 10"x44" Cationic resins for cylinder: 35 lt Max flow rate: 4000 lt/h Brine: 120 kg Salt for regener. Cycle: 7,2 kg Supply power: 230V 50/60 Hz Water conn.: Ø 3/4" G Min/max pressure: 2-8 bar Temp. Water supply: 4-25°C ØxH (mm): 271x1300 Cylinder ØxH (mm): 541x810 Brine	
OS2463	Automatic softeners LARGE SERIES PERFORMA VOLUMETRIC with valve. Fibreglass cylinder: 84 lt 13"x44" Cationic resins for cylinder: 59 lt Max flow rate: 4000 lt/h Brine: 120 kg Salt for regener. Cycle: 12,2 kg Supply power: 230V 50/60 Hz Water conn.: Ø 3/4" G Min/max pressure: 2-8 bar Temp. Water supply: 4-25°C ØxH (mm): 360x1300 Cylinder ØxH (mm): 541x810 Brine	



Automatic water softeners





Code	Spare Part Description	Picture
OS2464	Automatic softeners LARGE SERIES PERFORMA TIMED with valve. Fibreglass cylinder: 24 lt 8"x35" Cationic resins for cylinder: 17 lt Max flow rate: 4000 lt/h Brine: 80 kg Salt for regener. Cycle: 2,7 kg Supply power: 230V 50/60 Hz Water conn.: Ø 3/4" G Min/max pressure: 2-8 bar Temp. Water supply: 4-25°C ØxH (mm): 219x1060 Cylinder ØxH (mm): 480x660 Brine	
OS2325	Automatic water softener Fibreglass cylinder: 50 lt 10"x44" Cationic resins for cylinder: 35 lt Max flow rate: 4000 lt/h Brine: 120 kg Salt for regener. Cycle: 7,2 kg Supply power: 230V 50/60 Hz Water conn.: Ø 3/4" G Min/max pressure: 2-8 bar Temp. Water supply: 4-25°C LxDxH: Cylinder: Ø271x1300mm Brine: Ø541x810mm	
OS2326	Automatic water softener Fibreglass cylinder: 84 lt 13"x44" Cationic resins for cylinder: 59 lt Max flow rate: 4000 lt/h Brine: 120 kg Salt for regener. Cycle: 12,2 kg Supply power: 230V 50/60 Hz Water conn.: Ø 3/4" G Min/max pressure: 2-8 bar Temp. Water supply: 4-25°C LxDxH: Cylinder: Ø360x1300mm Brine: Ø541x810mm	
OS2696	WATER SOFTENER	
OS2697	Automatic softeners TIMED cruisers with Autotrol 255 valve Logix 760 24lt	
OS2536	WATER SOFTENER	
OS2534	WATER SOFTENER	



Automatic water softeners


Code	Spare Part Description	Picture
OS2535	WATER SOFTENER	
OS2503	AUTOMATIC WATER SOFTENER	
OS2599	WATER SOFTENER	
OS2537	WATER SOFTENER	

Manual water softeners

Code	Spare Part Description	Picture
OC1903	Manual water softeners. AISI 304 cylinder: 8 lt Cationic resins for cylinder: 5,6 lt Max flow rate: 1000 lt/h Salt for regener. Cycle: 1,0 kg Water conn.: Ø 3/4" G Min/max pressure: 1-8 bar Temp. Water supply: 8-25°C ØxH (mm): 190x400	
OS0330	Manual water softener AISI 304 cylinder: 12 lt Cationic resins for cylinder: 8,4 lt Max flow rate: 1000 lt/h Salt for regener. Cycle: 1,5 kg Water conn.: Ø 3/4" G Min/max pressure: 1-8 bar Temp. Water supply: 8-25°C LxDxH: Ø190x515 mm	
OS0329	Manual water softener AISI 304 cylinder: 20 lt Cationic resins for cylinder: 14 lt Max flow rate: 1000 lt/h Salt for regener. Cycle: 2,5 kg Water conn.: Ø 3/4" G Min/max pressure: 1-8 bar Temp. Water supply: 8-25°C LxDxH: Ø190x900 mm	
OS1074	Manual water softeners "by pass". AISI 304 cylinder: 8 lt Cationic resins for cylinder: 5,6 lt Max flow rate: 1000 lt/h Salt for regener. Cycle: 1,0 kg Water conn.: Ø 3/4" G Min/max pressure: 1-8 bar Temp. Water supply: 8-25°C ØxH (mm): 190x400	



Manual water softeners








Code	Spare Part Description	Picture
OS1076	Manual water softeners "by pass". AISI 304 cylinder: 12 lt Cationic resins for cylinder: 8,4 lt Max flow rate: 1000 lt/h Salt for regener. Cycle: 1,5 kg Water conn.: Ø 3/4" G Min/max pressure: 1-8 bar Temp. Water supply: 8-25°C ØxH (mm): 190x500	

Water softeners consumables

Code	Spare Part Description	Picture
OL1140	Water filter NK111. With wound cartridge 50m. Recommended for manual water softeners Ø5". Coupling 3/8" G	
OL1141	Water filter NK112. With wound cartridge 50m Recommended for manual water softeners Ø 5". Coupling 3/4" G	
OS1027	Wound cartridge 5" 50µm Ø 61 H 127 mm For OL1140 and OL1141	
OS2250	Carbon block cartridge 5m for OL1140 and OL1141	





Water softeners consumables




Code	Spare Part Description	Picture
OS1423	Complete filter NK223C with carbon block cartridge 5m. Recommended for manual water softeners Ø 9, Coupling 1/2" G m/f	
OS1029	Wound cartridge 9" 50µm Ø 61 H 247 mm For OS1423	
005480	Carbon block cartridge 5m. For OS1423	
OS2165	Salt for water softener 25 kg package	
OS2191	Cationic Resin. Suitable for all softeners with use of resin, of any capacity 5 kg package (lt 6,14)	
OS2192	Cationic Resin. Suitable for all softeners with use of resin, of any capacity 10 kg package (lt 12,28)	
OS0333	Cationic Resin. Suitable for all softeners with use of resin, of any capacity 25 kg package (lt 30,71)	
OS1090	Resin sanitiser for automatic water softeners. Resin disinfection device for Autotrol 255 Logix valve with salt alarm. Water softeners codes OS1079-OS1083-OS1089.	



Water softeners consumables


Code	Spare Part Description	Picture
002453	Resin sanitizer for water softener	
OS2245	Watertight pH/EC/TDS/ Temperature meter – scale EC/ TDS low. Pocket watertight instrument for : - pH/EC/TDS/ (3999 µS/cm, 2000 ppm) - temperature 0: 60°C - scale EC/TDS low Floating watertight body. Replaceable pH electrode with renewable fibre junction with a large display with two levels of reading and auto shutoff in case of inactivity. The instrument comes complete with protective hood, electrode replacement key, batteries and instructions. Dim.mm 163 x 40 x 26 mm Weight: 100 g	

Purity C Quell ST

Code	Spare Part Description	Picture
OS1628	Purity C 150 Quell ST System. Capacity 2408 l at 10° dH with bypass 40% (coffee machines) Capacity 1656 l at 10° dH with bypass 10% (ovens) working temp. 4°C-30°C min/max pressure 2-8.6 bar Head connections 3/8" Complete with digital flow meter (OS2555), water hardness test (OS1701) and Head with bypass (OS1638) ØxH (mm): 117x417	
OS1629	Purity C 300 Quell ST System. Capacity 4000 l at 10° dH with bypass 40% (coffee machines) Capacity 2750 l at 10° dH with bypass 10% (ovens) working temp. 4°C-30°C min/max pressure 2-8.6 bar Head connections 3/8" Complete with digital flow meter (OS2555), water hardness test (OS1701) and Head with bypass (OS1638) ØxH (mm): 125x464	
OS1630	Purity C 500 Quell ST system. Capacity 6800 l at 10° dH with bypass 40% (breakfast) Capacity 4675 l at 10° dH with bypass 10% (ovens) working temp. 4°C-30°C min/max pressure 2-8.6 bar Head connections 3/8" Complete with digital flow meter (OS2555), water hardness test (OS1701) and Head with bypass (OS1638) ØxH (mm): 149x553	



Purity C Quell ST

Code	Spare Part Description	Picture
OS1631	Purity C 1100 Quell ST System. Capacity 11,500 l at 10° dH with bypass 40% (breakfasts) Capacity 7906 l at 10° dH with bypass 10% (ovens) working temp. 4°C-30°C min/max pressure 2-8.6 bar Head connections 3/8" Complete with digital flow meter (OS2555), water hardness test (OS1701) and Head with bypass (OS1638) ØxH (mm): 184x553	

Purity C Quell ST System accessories and replacement cartridges




Code	Spare Part Description	Picture
OS1054	Cartridge Purity C 150 Quell ST	
OS1055	Cartridge Purity C 300 Quell ST	
OS1056	Cartridge Purity C 500 Quell ST	
OS1708	Cartridge. Purity C 1100 Quell ST	





Purity C Quell ST System accessories and replacement cartridges

Code	Spare Part Description	Picture
OS1892	Service cartridge Purity C for cleaning, disinfection and descaling of equipment directly connected. Ø 125 mm - H 233 mm Maximum cartridge capacity 0.5 l Operating pressure 0.5-8.6 bar Temp. water inlet 4-30 ° C The cartridge does not include the head OS1638	
OS1638	Head with bypass. Variable 0%-70% and rinsing valves male connections 3/8"	
OS2123	Brita PURITY C reduction kit. 3/4"-3/8" Set of 2 pieces	
OS2555	Digital volumetric litre counter Flow meter 100-100A Flow rate 10-100 l/h temp. 4°C - 30°C max 8 bar Indicates the remaining litres the filtration system can treat Battery powered	
OS2132	Cartridge. Filter Purity C 1000 AC Ideal for vending machines for cold and hot drinks	
OS2226	Cartridge. Set of 20 cartridges Purity C 1000 AC	

Purity STEAM for OVENS


Code	Spare Part Description	Picture
OS1632	Purity STEAM 450 filter. With MDU -litre counter system included Capacity 3,680 l at 10° dH with bypass at pos.1 Working temp. 4°C-30°C Max press. 6.9 bar Inlet/outlet head connections G1" - G3/4" ØxH (mm): 249x408	
OS1633	Purity STEAM 600 filter. With MDU -litre counter system included Capacity 5,771 l at 10° dH with bypass at pos.1 Working temp. 4°C-30°C Max press. 6.9 bar Inlet/outlet head connections G1" - G3/4" ØxH (mm): 249x520	
OS1634	Purity STEAM 1200 filter. With MDU -litre counter system included Capacity 10,800 l at 10° dH with bypass at pos.1 Working temp. 4°C-30°C Max press. 6.9 bar Inlet/outlet head connections G1" - G3/4" ØxH (mm): 249x550	

Purity STEAM System accessories and replacement cartridges



Code	Spare Part Description	Picture
OS1635	Purity STEAM 450 cartridge	
OS1636	Purity STEAM 600 cartridge	




Purity STEAM System accessories and replacement cartridges

Code	Spare Part Description	Picture
0S1637	Purity STEAM 1200 cartridge	

Purity C STEAM for ovens



Code	Spare Part Description	Picture
0S2491	PURITY C 500 STEAM kit. Complete with cartridge (0S2490) and head (0S2489)	
0S2492	PURITY C 1100 STEAM kit. Complete with cartridge (0S2488) and head (0S2489)	

Accessories Purity C STEAM for ovens and replacement cartridges



Code	Spare Part Description	Picture
0S2490	Cartridge PURITY C 500 STEAM.	








Accessories Purity C STEAM for ovens and replacement cartridges

Code	Spare Part Description	Picture
OS2488	Cartridge PURITY C 1100 STEAM	
OS2489	Head PURITY C STEAM. 3/8" M	


Purity Clean and Clean Extra

Code	Spare Part Description	Picture
OS0801	PURITY 1200 CLEAN filter system. With PARTIAL demineralisation including filter cartridge. Connections: inlet G1"- outlet G3/4" Min./max inlet pressure: 2-6 bar Working temperature 4°-60°C Capacity: 13.000 l at 10° KH	
OS0803	PURITY 1200 EXTRA filter system. With TOTAL demineralisation including filter cartridge. Connections: inlet G1"- outlet G3/4" Min./max inlet pressure: 2-6 bar Working temperature 4°-60°C Capacity: 5.000 l at 10° KH	

Purity CLEAN and CLEAN EXTRA System accessories and replacement cartridges



Code	Spare Part Description	Picture
0S0802	PURITY 1200 CLEAN cartridge	
0S0804	PURITY 1200 CLEAN EXTRA cartridge	
0S1223	Head for Purity CLEAN and CLEAN EXTRA with bypass	
0S2555	Digital volumetric litre counter Flow meter 100-100A Flow rate 10-100 l/h temp. 4°C - 30°C max 8 bar Indicates the remaining litres the filtration system can treat Battery powered	
0S2556	Digital volumetric litre counter Flow meter 100-700A Flow rate 100-700 l/h	

Purity AquaQuell System accessories and replacement cartridges




Code	Spare Part Description	Picture
0S0797	Purity AquaQuell 450 cartridge	



Purity AquaQuell System accessories and replacement cartridges

Code	Spare Part Description	Picture
OS0798	Purity AquaQuell 600 cartridge	
OS0683	Purity AquaQuell 1200 cartridge.	

Reverse osmosis filtration system with atmospheric boiler


Code	Spare Part Description	Picture
OS1822	Reverse osmosis filter. Supply voltage: 220 ... 240 V / 1N ph / 50/60 Hz Power consumption 0.18kw Feed water pressure: 1 - 4 bar Water temperature of power supply: 5-35 ° C Water inlet pipe dimensions: 3/4"	
OS1821	Replacement filter cartridge for osmosis	
OPRY39	Container for filter membrane 3012 Connection 1/4 "- 3/8" (membrane not included)	



Reverse osmosis filtration system with atmospheric boiler



Code	Spare Part Description	Picture
OL1140	Water filter NK111. With wound cartridge 50m. Recommended for manual water softeners Ø5". Coupling 3/8" G	
OS2250	Carbon block cartridge 5m for OL1140 and OL1141	
OPRAH2	Wheels for reverse osmosis filter Kit of 4 pcs	
OS1826	Head with wall bracket	
OS1848	Filter membrane 3012. 300 GPD	

Spare parts for reverse osmosis filter RO600C








Code	Spare Part Description	Picture
OS0730	Descaler kit. For osmosis membrane cleaning. Complete with 2 carbon filters and 1 descaling agent. 200gr	
OS0728	Carbon filter for RO600C	



Spare parts for reverse osmosis filter RO600C

Code	Spare Part Description	Picture
0S0735	Pump filter with membranes For RO400/600"	
0S0738	Pump kit RO600	
0S0736	Protective bushing	
0S0737	Motor RO600 23V	





Work tools

Code	Spare Part Description	Picture
0S2578	<p>Tool trolley case (tools excluded). Case in thick polypropylene, injection moulded. Very high resistance to corrosive substances, impacts and high and low temperatures. Injection moulding allows a constant thickness of the material to be obtained, especially in the corners.</p> <p>General characteristics:</p> <ul style="list-style-type: none"> - 2 metal cover support arms - 2 locks with key - 3 metal rear hinges - bottom with removable adjustable separators - rubber covered ergonomic handle - name tag - document holder area - arranged for third extra panel <p>Dim. mm 465x255x352 (LxDxH)</p>	
0S1288	<p>Kit of assorted tools</p> <p>Tools sold separately. For the list of available tools please look at the Genuine Replacement Parts Catalogue.</p>	
0G6126	THERMA nozzle wrench s/steel used to remove/fit nozzles on pilot burners of Therma hobs	
0W4857 94081008	TENSION ARM	
006956	<p>Round cord welder</p> <p>Polycord Tool useful and necessary for welding cords of tray belt conveyors with Ø min from 2mm to 15mm</p> <p>Voltage 230V, 50Hz</p> <p>dim. 420x140x115h Weight 0.68 Kg</p> <p>(also hire on request, contact the Head Office directly for the procedure)</p>	
OST071	Crimping plier for connector lugs	
OCB287	Cavity fan extractor kit for SkyLine Ovens	

Maintenance stickers






Code	Spare Part Description	Picture
OS2601	1 Set of maintenance stickers Electrolux Professional 50 sheets/750 stickers Ø 35mm	
OS2336	1 Set of maintenance stickers Essentia 50 sheets/750 stickers Ø 35mm	

Gas measuring instruments





Code	Spare Part Description	Picture
OS2342	<p>Testo 324-Pressure and leakage measurement on gas and water pipes. All measurements for gas and water pipes in one instrument. High-resolution color graphic display. Simple menu structure. Easy operation thanks to singlehose connection. Case with gas-feed appliance Integrated pressure set-up.</p> <p>The kit contains:</p> <ul style="list-style-type: none"> - Case - 100x240 Vca power supply - Threaded tire holder connector 1/8G (psc) - Threaded hose connector 1/4 G (1pcs) - Silicone tube set (2pcs) 	
OS0970	<p>Testo 312-4 gas pressure gauge. Instrument for all leak testing of gas/water systems, DVGW approved for gas control and regulation, delivery return temperature and ionisation currents, with sound alarm. Recording measured values and data transfer using. Easyheat PC software</p> <p>Technical data:</p> <ul style="list-style-type: none"> - measuring ranges from - 200...+200hPa (resolution 0.01 hPa) - working temperature +5...+45°C - weight 600 g - dim.mm 219x68x50h <p>Complete with flexible tube kit</p>	
OS0390	<p>Flexible thermocouple in fibreglass Length 1500 mm (use only with adapter OS1019) measuring range -50 ÷ +400°C</p>	
OS1019	Adapter for thermocouple	




Gas measuring instruments

Code	Spare Part Description	Picture
OS0969	High pressure probe 0...25 bar for Testo 312-4 For pressure tests on water/gas systems	
OS2231	High pressure connection 3/8 "and 3/4"	
OS2232	High pressure connection 1/2" and 1	
OS2233	Flexible 2 m with quick coupling FF	
OS0917	Testo 316-1 Combustion gas leak detector. The instrument also detects slight gas leaks. Complete with optical and acoustic alarm when limits are exceeded, flexible probe for hard to reach pipes, topsafe case against dirt and impacts (optional). Recommended during installation and maintenance Battery life > 5 h dim. 190 x 57 x 42 mm	
OS0918	Testo 317-3 digital carbon monoxide detector. The instrument signals the presence of CO concentrations. Complete with acoustic and visual alarm, leather case, headphones, wrist strap, autotest function, sampler. Recommended during installation and maintenance. Battery life 150 h (with non-active acoustic signal) Working temperature - 5...+ 45 °C	
OS2109	Testo 270 Tester for cooking oil. Instrument for measuring the quality and temperature of the oil. Oil working temp. + 40... + 200 °C. IP 65 protection rating, waterproof and washable under running water. Battery life approx. 25h (500 measurements). Complete with washable case	
OS1486	Reference oil for setting and calibration of cooking oil tester testo 270 (1 x 100 ml)	
OS2651	Tester for cooking oil. Avoid using spent oil for food preparation through the electronic oil control system, ensuring sustainable operations, cost savings and preventing health risks.	

Pocket Testo series




Code	Spare Part Description	Picture
OS0830	Testo 410-2 Vane anemometer Measurer of air velocity with propeller sensor Ø40mm, relative humidity and amb. Temperature. Measuring range from 0.4 to 20m/s; from 0 to 100% RH and from -10 to + 50 °C Including protective hood, test protocol and batteries	
OS2108	Testo 510 gas micromanometer. Differential pressure gauge with temperature compensated sensor. Measuring range from 0 to 100 hPa. Including protective hood, test protocol and batteries.	
OS2470	Testo 606-2 - Moisture Meter, Air Temperature and Humidity. Allows you to measure the moisture content in wood and building materials - and the surrounding environment too. Which means that storage and drying conditions of goods are quickly and easily checked. Measuring range from -10 °C to + 50 °C. Batteries: 2 AAA (included)	
OS0831	Testo 460 revolution counter Instrument for measuring the rotation speed with protective hood, test protocol. Measuring range from 100 to 29,999 rpm. Batteries included	
OS0832	Testo 810 Surface Thermometer for air and surfaces with infrared sensor and laser pointer. Measuring range: air from -10 to +50 °C, IR surfaces from -30 to +300°C. Including protective hood, test protocol and batteries	

Refrigeration measuring instruments

Code	Spare Part Description	Picture
OS2110	Testo 550 BLUETOOTH digital analyser. Comprising: 2 temperature inputs, 2 pressure inputs, 3-way valve battery, 30 types of refrigerant E996 with saturation curves. Measurement: high and low pressure, overheating and subcooling with external temperature probe calculates DT, System leak test displays vacuum measured, backlit display, backlit sight glass complete with test protocol. Measuring ranges: low pressure from 0 to 60 bar; high pressure from 0 to 60 bar; Temperature from -50°C to +150°C; pressure accuracy ± 0.5% fs. Complete with 2 clip temperature probes for temperature measurements on pipes from Ø 6 to 35mm. Measuring range from -40°C to +125° C - NTC, rigid ABS case with shaped interior with BLUETOOTH (free Testo refrigeration app)	







Refrigeration measuring instruments


Code	Spare Part Description	Picture
OS1283	<p>Testo 570-2 digital manometric group. The Testo 570-2 digital manometric group replaces many tools and measuring instruments needed for daily work on cooling systems and heat pumps: it measures, analyses and documents pressure, temperature, flow and vacuum measurement; values and saves all the data, from commissioning to service and maintenance, for the error analysis of a system. Data memory up to 999 hours of recordings. "EasyKool" software gives the measurement data in an easy to understand way</p> <ul style="list-style-type: none"> - Print reports - The current 40 refrigerant fluids are already recorded in the instrument with possibility of free update. - High and low pressure fast measurement, automatically calculating temperatures - Three inputs for connection of temperature probes - Integrated vacuum measurement - Automatic heat pump mode <p>Measuring ranges: 50 bar; Temperature: from -50°C to +150°C; Vacuum: from -1 to 0 bar Accuracy: pressure +/-0.5% fullscale value (class 0.5) Complete with two clip temperature probes, "EasyKool" PC software, USB data cable, rigid ABS case with shaped interior, power supply, calibration protocol and batteries</p>	
OS2378	<p>Testo 557 digital manifold kit with integrated Bluetooth connectivity with the testo Refrigeration App. The instrument can clearly read measurement data, such as automatic calculations of superheat, sub-cool and vacuum readings, on a Smartphone or Tablet, allowing you to work more quickly and convenient. The kit features an external vacuum probe for faster and more reliable evacuations and is suitable for all refrigeration systems or heat pumps. This compact manifold has a 4-way valve block, large backlit display and sight glass. Two NTC thermistor clamp probes provide superior accuracy of simultaneous, real-time superheat and sub-cooling readings.</p> <ul style="list-style-type: none"> - Battery life of 250 hours - Measuring range temperature: -50 to + 150 °C - Measuring range pressure: -1 to 60 bar - Measuring range vacuum: 0 to 20000 micron - Accuracy Vacuum: ± (10 micron + 10 % of mv) (100 to 1000 micron) <p>Complete with digital manifold with Bluetooth, 2 x clamp probes, external vacuum probe, batteries, case and certificate of conformity.</p>	
OS1122	<p>Mini Data logger 174T kit. The instrument controls the temperature of food, ensuring constant monitoring of the cold chain. With the help of software it is possible to program and read the temperature datalogger, and analyse the data on PC. For this purpose, Testo offers a ComSoft Basic software version downloadable free of charge. Complete with USB interface for data transfer to PC, wall mount, battery (2 x CR 2032 lithium) and test protocol. Data memory for 16,000 temperature values. Waterproof according to IP 65, HACCP compliant and certified according to EN 12830</p> <ul style="list-style-type: none"> - Measuring range from -30 to + 70°C - Accuracy ± 0.5 °C - Resolution 0.1 °C - Measuring cycle 1min-24h - dim. mm 60 x 38 x 18.5 	



Refrigeration measuring instruments






Code	Spare Part Description	Picture
OS1126	Mini Data logger 174T. Complete with wall mount, batteries (2 x CR 2032 lithium) and test protocol	
OS1984	Data Logger SAVERIS 2 T2 WI-FI (WLAN) with display for measuring temperature, two ports for connection of NTC, temperature probes or external port contacts, includes: USB cable, wall mount, batteries and calibration protocol. Measuring range : -50... +150°C Memory 10,000 measurement values/channel Dim. mm 95 x 75 x 30.5"	
OS1985	Aluminum tube probe - IP65 Measuring range: -30.. +90°C Stretched fixed cable 2400mm	
OS1745	Refrigerant gas leak detector. Leak detector for all the most common refrigerant gases: R134a, R22, R404a, H2; all the most common refrigerant gases such as CFC, HCFC, HFC. Sensitivity 4 g/year according to EN 14624 and E35-422; optical and acoustic alarm, sensor control, user-replaceable sensor. Complete with test protocol, rigid ABS case with shaped interior dim. 190 x 57 x 42 mm	
OS0837	Testo 316-4 Refrigerant gas leak detector. Leak detector for all the most common refrigerant gases: R134a, R22, R404a, R290, R600, H2, all the most common refrigerant gases such as CFC, HCFC, HFC sensitivity 3 g/year according to EN 14624 and E35-422 long-life sensor, optical and acoustic alarm, sensor control, user replaceable sensor, headphone input, supplied with rechargeable batteries dim. 190 x 57 x 42 mm Complete with: - Mains power supply - Headphones - Rigid ABS case with shaped interior	
OS1265	Refrigerant change sensor for all the most common refrigerant gases: CFC, HCFC, HFC	

Electricity measuring instruments-miscell

Code	Spare Part Description	Picture
OS1282	FLUKE 117 digital multimeter complete with multifunction measurements, cables and shockproof shell, measuring range Volts: 2V÷700 Volt (AC), measuring range Amperes 20mA÷20A(AC)	








Electricity measuring instruments-miscell

Code	Spare Part Description	Picture
OS1456	FLUKE 323 current clamp Measuring range Current AC: Range 400.0 A Voltage AC/DC: Range 600.0 V Resistance: Range 400.0 -4000 Continuity ≤ 70 Max wire diameter 30 mm (600MCM) Complete with test leads, soft case and manual dim.mm 207 x 75 x 34	
OS2267	Thermometer. Testo 926 digital food thermometer with official ACCREDIA/LAT calibration certificate, ACCREDIA certification is foreseen for the instrument with air probe on 4 points: -30°; +10°C; +100°C; +240°C. The instrument is complete with air probe Measuring range -50° ... +400°C Dim. mm 182 x 64 x 40	
OS1722	LCR 878B inductance meter. The portable instrument quickly and accurately detects inductance, capacitance and resistance. Applications include passive component resolution, electronic assembly and quality control (sorting component). Resolution with 40,000 counts on the primary display and 10,000 counts on the secondary display. Maximum capacity measurement: 20mF. Maximum resistance measurement: 10 M. Maximum inductance measurement: 1000H. Visible and audible tolerance modes. Data hold and memory recording and min/max/average. USB interface (COM virtual). Complete with: Banana to alligator leads, 9V battery, mini USB interface cable, manual dim.190 x 90 x 41mm	
OS0838	Testo 925 thermocouple digital thermometer. Thermometer with one channel arranged for K TYPE probes, 3-digit LCD display. Measuring range: from -50° to +1000°C, backlit display, possibility of printing measured data and connecting additional probe via radio. Complete with zip case and air probe -50° +400°(thermocouple K) dim.mm 182 x 65 x 40	
OS1152	Probe for flat surface -60°..+400°C (0602.1993)	
OS1158	Water immersion-penetration probe -50°..+400°C (code 0602.1293)	
OS1400	Ultrasonic probe for mixed surface -50°..+300°C (code 0602.0393)	





Electricity measuring instruments-miscell




Code	Spare Part Description	Picture
OS0390	Flexible thermocouple in fibreglass Length 1500 mm (use only with adapter OS1019) measuring range -50 ÷ +400°C	
OS1401	Surface waterproof probe with small measuring terminal (TC type K) -60°....+1000°C	
OS1118	Microwave detector TX2000. Tool for microwave leakage detection, strong and compact, with a single RF power measuring range designed to operate in the frequency range 2.45 GHz. The instrument is calibrated and provided with international calibration certificate. Length (including spacer) 230 mm Max depth 42 mm Width 44 mm Weight (without battery) 80 gr Power supply 9 Volt PP3 Battery Rated current 10 mA Nom. operating frequency 2.45 GHz Calibration accuracy +/- 1dB on all polaris. Input response RF detection range 0 - 10 mW/cm2	
OS2400	Plastic case for holding measuring instruments and accessories dim: 500 x 380 x 140 mm	
OK7904	Water liter counter	
OS0971	Laser distance meter. Ideal for measuring distances and determining surfaces and volumes. Complete with case and batteries Technical data: • measuring capacity from 50 mm to 100 mt. • min. displayed unit 1mm • weight 150 g • dim. mm 135x50x31	



Electricity measuring instruments-miscell

Code	Spare Part Description	Picture
OS0478	Water pressure gauge (feed water pressure) black ABS casing • impact-resistant resin glass • brass precision movement • red needle • threaded connection: R 1/4" (Gas) • diameter 63 mm • conforms to ISPEL standards • measuring range: 0÷10 bar • tolerance: ± 0.20 bar	
OS0480	Gas pressure gauge (feed gas pressure) measuring range: 0÷60 mmbar tolerance:± 5%	

Water analysis

Code	Spare Part Description	Picture
OS0483	TT method water analysis case complete with: • Conductivity/pH meter code OS0481 • Manual chloride analysis tool (approx. 200 tests) code OS0585 • Manual hardness analysis tool (approx. 300 tests) code OS0586 • Plastic case code OS2400	
OS0586	Manual hardness analysis tool (approx. 300 tests) with TT method complete with: • two 25 ml flasks reagent H1 • two 85 ml flasks reagent H2 • one measuring cup 5÷10 ml • one Dispenser 5 ml • one Titrator for hardness in °D	
OS2245	Watertight pH/EC/TDS/ Temperature meter – scale EC/ TDS low. Pocket watertight instrument for : - pH/EC/TDS/ (3999 µS/cm, 2000 ppm) - temperature 0: 60°C - scale EC/TDS low Floating watertight body. Replaceable pH electrode with renewable fibre junction with a large display with two levels of reading and auto shutoff in case of inactivity. The instrument comes complete with protective hood, electrode replacement key, batteries and instructions. Dim.mm 163 x 40 x 26 mm Weight: 100 g	




Water analysis




Code	Spare Part Description	Picture
OS2255	Spare - replacement pH electrode cartridge	
OS0585	Manual chloride analysis tool (approx. 200 tests) with TT method complete with: • one 20 ml flask reagent CL1 • one 28 ml flask reagent CL2 • two 88 ml flasks reagent CL3 • one. measuring cup 5÷10 ml • one 5 ml dispenser • one chloride titrator in ml/l	
OS2246	Buffer solution pH 7.01 HI70007P 25 sachets (20 ml)	
OS2247	Buffer solution pH 4.01 HI70004P 25 sachets (20 ml)	
OS2248	Conductivity solution 1413 µS/cm HI70031P 25 sachets (20 ml)	
OS1707	Solution TDS 1382 ppm HI70032P 25 sachets (20 ml)	





Water analysis

Code	Spare Part Description	Picture
OS0481	Conductivity/pH meter complete with probe and buffer solutions Measuring range: 50÷ 2000 µS/cm	


Electrolux Professional SkyLine ovens chemicals

Code	Spare Part Description	Picture
OS2395	C22 Cleaning tabs. Cleaning powder in single use tabs for SkyLine ovens. Professional detergent for for new generation ovens with automatic washing system. Suitable for all types of water Package: 100 tabs buckets - 65 gr. each tab	
OS2392	C23 Cleaning powder. Cleaning powder in single use bags for SkyLine ovens. Professional detergent for new generation ovens with automatic washing system. Suitable for all types of water Package: 100 bags bucket; 65 gr. Each	
OS2394	C25 Rinse & Descale tabs. Professional rinse and descale 2 in 1 in single use tabs for SkyLine ovens. Professional chemical agent for new generation ovens with automatic washing system. Suitable for all types of water. Package: 50 tabs buckets; 30 gr. each tab	

Electrolux Professional chemicals for professional ovens






Code	Spare Part Description	Picture
OS2282	C20 Extra Strong Detergent for ovens. - Detergent for ovens with automatic washing system - Tested and validated by Electrolux Professional Labs for best appliance performance, compatibility and durability - High degreasing power for ovens with integrated washing cycle - Environmental friendly chemical formula - EDTA free Compatible with: ovens with automatic cleaning system Pack of 2 x 5 liter can	
OS2283	C21 Extra Strong Rinse aid for ovens. - Rinse aid for ovens with automatic washing system - Tested and validated by Electrolux Professional Labs for best appliance performance, compatibility and durability - Quick drying and perfect shining cavity for ovens with integrated washing cycle - Environmental friendly Eco product by use of vegetable origin surfactants Pack of 2 x 5 liter can	

Electrolux Professional chemicals

Code	Spare Part Description	Picture
OS2092	C11 Detergent for dishwashers. - Ideal for all types of crockery: ceramic, porcelain, glass, crystal and metal - It is very functional for removing caffeine and theine deposits from cups and teapots - Its delicate aroma helps minimize the unpleasant odour which can sometimes be found in dishwashers - Highly recommended for restaurants preparing fish and sea food - Particularly suitable for hard and medium hard water Compatible with: glasswasher, undercounter, front loading, hood type, rack type Package: one pack of 2 cans of 5lt.	
OS2281	C11 Detergent for dishwashers. - Ideal for all types of crockery: ceramic, porcelain, glass, crystal and metal - It is very functional for removing caffeine and theine deposits from cups and teapots. - Its delicate aroma helps minimize the unpleasant odour which can sometimes be found in dishwashers. - Highly recommended for restaurants preparing fish and sea food. - Particularly suitable for hard and medium hard water Compatible with: glasswasher, undercounter, front loading, hood type, rack type Package: 1 can of 20lt.	






Electrolux Professional chemicals



Code	Spare Part Description	Picture
OS2094	<p>C12 Rinse aid for dishwashers.</p> <ul style="list-style-type: none"> - Brightener additive for crockery rinsing in the dishwasher - Guarantees sparkling clean and dry crockery - Use of vegetable origin surfactants - Ideal for ceramics, porcelain, glass and crystal Specific formula for hard water and medium hard waters <p>Compatible with: glasswasher, undercounter, front loading, hood type, rack type</p> <p>Package: one pack of 2 cans of 5lt.</p>	
OS2093	<p>"C13 ECO Detergent for dishwashers 1 pack with two 5lt tanks "</p>	
OS2280	<p>C13 ECO Detergent for dishwashers.</p> <ul style="list-style-type: none"> - Ideal for all type of crockery: ceramic, porcelain, glass, crystal and metals. It's special "Eco-Formula" free of phosphates, EDTA and NTA makes the product ecologically friendly with a very low environmental impact - Very efficient in case of dried food residues on all kind of dishes - Particularly suitable for soft water and recommended for dishwashing systems with osmosis or demineralisers <p>Compatible with: glasswasher, undercounter, front loading, hood type, rack type</p> <p>Package: 1 can of 20lt.</p>	
OS2095	<p>C14 Rinse aid Plus for dishwashers.</p> <ul style="list-style-type: none"> - Rinse additive for crockery rinsing in the dishwashers. Super concentrated formula recommended for soft water conditions - Offers a perfect drying without stains or any water trace, therefore highly recommended for glasses - Use of vegetable origin surfactants Ideal for dishes in glass, crystal, ceramics, porcelain <p>Compatible with: glasswasher, undercounter, front loading, hood type, rack type</p> <p>Package: one pack of 2 cans of 5lt.</p>	
OS1841	<p>C40 Degreaser for hot surfaces. Detergent active at high temperature for plates, grids, free cooking surfaces, fry tops and grills (max 175°C). Practical nozzle and spraying unit included</p> <p>Packing: 1 pack of 6x1 liter bottle</p>	



Electrolux Professional chemicals


Code	Spare Part Description	Picture
OS2292	C41 RAPID GREASE for Speedelight for cleaning of Speedelight hot plates (max 175°C). Practical nozzle and spraying unit included. 1 pack of six 1l bottles (Sprayer OS2331 included)	
OS2331	Sprayer for C41 RAPID GREASE with extension	
OS2362	C30 Multipurpose descaler. - effectively eliminates encrustations and scale from washing appliances and boilers of any professional equipment - the regular use of C30 Multipurpose descaler keeps the equipment always efficient, while slowing down the natural wear and tear - thanks to its low foaming power, C30 Multipurpose descaler is recommended for cleaning boilers and equipment with an automatic descaling device - the neutral fragrance makes its use more pleasant Compatible with: boilers and dishwashing equipment, glasswasher, undercounter, front loading, hood type, rack type Package: one pack of 2 cans of 5lt	

Detergents and Rinse Aids





Code	Spare Part Description	Picture
OS0842	Neutral liquid detergent TABOR LIMONE Manual dishwashing product 1 pack of four 5l tanks	
OS1574	Chlorinated liquid detergent TOPMATIC HERO for dishwashers. Removes the most stubborn of stains. Not suitable for soft metals. One 12 kg pack.	



Detergents and Rinse Aids





Code	Spare Part Description	Picture
OS0843	Solid detergent for dishwashers SOLID MEGA 1 pack of four 4.5 kg caps	

Degreasing and descaling products


Code	Spare Part Description	Picture
OS1414	Scented degreaser SGRASS CLEANER G8. Also usable on aluminum 1 pack of twelve 750ml bottles	
OS2384	Alkaline degreasing detergent REGAIN suitable for automatic cleaning of exhaust ventilation systems. 1 pack of two 5l tanks	
OS1299	Glass ceramic cleaner VITRO CARE. Removes food, grease and water on induction hobs, ceramic hobs. Concentrated, just a few drops are enough. 1 pack of twelve 250ml bottles	
OS2712	SANIALC ultra alcoholic detergent for surfaces and tissues. UN1170, CL3,II. 1 pack of six 750ml bottles.	



Degreasing and descaling products

Code	Spare Part Description	Picture
OS2308	Pickling agent for metals Sparkle. Product that allows you to instantly pickle, restore, clean and polish all metallic surfaces, making them immediately bright. Does not stain and prevents corrosion and oxidation. Instruction for use: - Spray the product on the surface using gloves as protection. - leave the product to act for a few minutes - rub with absorbent paper or cloth - ventilate the surrounding area during and after use	
OS0994	Ammonia-based cleaner SPRAY CLEANER for metal surfaces, ceramic tiles, glass. 1 pack of twelve 500ml cans	
OS0995	Polishing detergent SS POLISH & CLEANER for s/steel surfaces and other metals. 1 pack of twelve 500ml cans	
OS0060	Clean Spray detergent for removing grease, oil, grime from adhesive, silicone, wax, etc. One 500ml can	

Greases

Code	Spare Part Description	Picture
OS2277	Food-grade grease for taps with conical seal kg 1	






Greases




Code	Spare Part Description	Picture
OS1145	Food-grade grease for taps with conical seal 2 tubes g 45	
OS2118	Grease for taps with O-ring g 100 certification NSFH1	
003363	LUBRICANT; 500ML; UNI1950 II AEROSOLS	
OS0327	Lubricating grease for high temperatures. Suitable for bearings. One 1 kg pack	
OS0182	Grease for gas taps one 500 g pack	
OS0245	Grease for gas taps one 60 g tube	
OS1740	Spray lubricant for the food industry. Particularly suitable for equipment such as slicers, meat mincers, etc., also usable on aluminum, stainless steel and on all plastic materials. The product is not hazardous to health in case of contact and is non-toxic and harmless to the skin. One 300ml bottle	



Greases

Code	Spare Part Description	Picture
0C9506	Lubricating grease Anti-slip Aluminum One 500 g pack	
005256	Silicone compound conductive for FCV ovens applicable for boiler probes One 100 g tube	
0S2275	Grease for food contact for Speedelight One 50 g tube	
0D8030	Grease for food contact suitable for incidental contact with food; ideal for lubrication of mechanical devices (bearing, reducer, gear); water resistant. 1 400 g tube	

Sealants and insulators

Code	Spare Part Description	Picture
059611	One-component adhesive sealant for roofing leaks appliances, s/steel grey 310ml pack	
006083	Adhesive sealant for ovens seals 90ml pack	
0C0074	Polyurethane adhesive sealant PACTAN HT 6076 310ml pack	





Sealants and insulators




Code	Spare Part Description	Picture
OCB101	SILICONE SEALANT-RED RTV 106	
OCB051	Red silicone adhesive sealant for Speedelight Max temperature 300° C 300ml pack	
OS2680	Sika® Aktivator-205; Pretreatment agent 250 ml	
088313	Catalyst PRIMER 1015 PACTAN 500ml pack	
OD6223	Polyurethane adhesive for vitroceramic plates NOVASIL S 76 Ideal for thermaline induction 310ml pack	
OC0069	Spacer for glass ceramic Pack of 8 pcs	
OS1830	Eurover 2000 glass wool (roll) used to insulate ovens, pasta cooker tanks, pots etc. Covered on both sides with 15 micron aluminum foil Thickness 30 mm Density 30 kg/m3 Dim. 6000x850 mm	



Sealants and insulators



Code	Spare Part Description	Picture
006451	Aluminised tape Length 50m Width 50mm	
006101	Corrosion inhibitor kit Also used for gas indirect heat boiling pans 10 sachets of "trisodium phosphate" (5 pairs)	

Oil for vacuum packaging machines

Code	Spare Part Description	Picture
0S0939	Hydraulic oil ISO46 One 1l pack	
0S0940	Hydraulic oil ISO46 One 5l pack	
0S2607	Hydraulic oil ISO32 One 1l pack	
0S0941	Hydraulic oil ISO32 One 5l pack	



Oil for vacuum packaging machines

Code	Spare Part Description	Picture
0S0942	Hydraulic oil NORMAL100 One 5l pack	
0S2399	Granulate for cutlery dryer One 9 kg pack	



Excellence is central to everything we do.
By anticipating our customers' needs, we strive for
Excellence with our people, innovations, solutions and services.
To be the OnE making our customers' work-life easier,
more profitable – and truly sustainable every day.

Follow us on



www.electroluxprofessional.com

Excellence with the environment in mind

- ▶ All our factories are ISO 14001-certified
- ▶ All our solutions are designed for low consumption of water, energy, detergents and harmful emissions
- ▶ In recent years over 70% of our product features have been updated with the environmental needs of our customers in mind
- ▶ Our technology is RoHS and REACH compliant and over 95% recyclable
- ▶ Our products are 100% quality tested by experts

