

always with something extra



CLEAN

Excellent washing results regardless of working conditions thanks to:

- the CLEAR BLUE Filtering System
- the very powerful washing circuit
- the unique shape of the spray nozzles and rotating arms



EASY

Optimal visibility and easy operation both in corner and linear installations due to:

- the innovative angular position of the control panel
- the integrated LED display (on automatic models)



Description	EHT8TI	EHT8I	NHT8
Automatic hood	•		
WASH+SAFE CONTROL	•	•	
Sanitation guaranteed	•	•	•
Double skin insulated hood	•	•	
Electrical connection	400V/3N/50Hz convertible on site to 230V/1N or 230/3/50Hz	400V/3N/50Hz convertible on site to 230V/1N or 230/3/50Hz	400V/3N/50Hz convertible on site to 230V/1N or 230/3/50Hz
Number of cycles	3	3	3
Capacity (ETL Sanitation mode)	63 racks/hour 1134 dishes/hour	63 racks/hour 1134 dishes/hour	63 racks/hour 1134 dishes/hour
Capacity (High Productivity mode)*	80 racks/hour 1440 dishes/hour	80 racks/hour 1440 dishes/hour	80 racks/hour 1440 dishes/hour
External dimensions (wxdxh)	667x755x1567	752x755x1567	752x755x1547
External dimensions with ESD (wxdxh)	667x755x2264	752x755x2264	
Basket dimension (mm)	500x500	500x500	500x500
Wash tank capacity (lt.)	24	24	24
Wash pump power (kW)	0,8	0,8	0,8
Boiler power (kW)**	9	9	9
Water consumption (lt./cycle)	2	2	2
Total power (kW)***	9,9	9,9	9,9
Noise level (dBA)	< 63	< 63	< 68
Built-in rinse aid dispenser	•	•	•
Included baskets	1 basket for 18 plates 1 basket for cups 2 cutlery containers	1 basket for 18 plates 1 basket for cups 2 cutlery containers	1 basket for 18 plates 1 cutlery containers

Additional features	EHT8TI	EHT8I	NHT8
ZERO LIME Device	•	•	◦
ESD Energy Saving Device	•	•	
CLEAR BLUE Filtering System	•	•	◦
60Hz	◦	•	•
Built-in drain pump	•	•	◦
Built-in detergent dispenser & drain pump	◦	•	•
Built-in detergent dispenser	◦	•	•
Built-in detergent dispenser, drain pump & continuous water softener		•	•

* When connected to warm water supply (min. 50 °C)
 ** 6 kW when connected to warm water supply (at 65 °C)
 *** 6,9 kW when connected to warm water supply (at 65 °C)

• standard on selected models
 ◦ available as optional accessory or as special execution

www.electrolux.xx/foodservice
 Share more of our thinking at www.electrolux.com/professional

green&clean Hood Type Dishwashers



Thinking of you
Electrolux

green&clean



GREEN

Maximum savings are assured by:

- the low consumption of fresh water (2 lt./cycle)
- the highly efficient rinsing (-33% in running costs, less hot water used)
- the ENERGY SAVING device
- the ZERO LIME device



SAFE

Best-in-class sanitization and safety are guaranteed by:

- the WASH-SAFE CONTROL which provides a constant rinsing temperature of 84 °C, assuring perfect hygienic conditions and total detergent removal



- ▶ **Double skin hood** with sloped ceiling for improved rinsing performance, low noise level* and reduction in heat loss *(less than 63 dBA)



- **Slanted wash arms and ceiling** for maximum performance as wash water no longer drops on dishes after rinsing phase, guaranteeing optimal results



- ▶ **CLEAR BLUE Filtering System** maximizes washing performance and lowers running costs



- **24 liter pressed tank** in front of machine makes cleaning operations faster and easier



- ▶ **Continuous water softener** Provides spot-free results and reduces scale build-up. A sensor advises when the salt container needs refilling. Integrated to avoid overflowing during salt refilling

● Standard feature on all models.




- ▶ **ESD Energy Saving Device** Highly efficient. No need for additional ventilation. Increased savings as machine uses generated steam to pre-heat water



- ▶ **ZERO LIME Device** less energy consumption thanks to higher efficiency of heating elements. Lime-free nozzles for better rinsing results




- **IP25 protection** full protection against water jets and solid objects/animals (larger than 6 mm)



- **WASH-SAFE CONTROL** atmospheric circuit with cold water supply guarantees optimal washing performance and productivity



- **Angular position of the control panel** for easy operation of the machine whether in a corner or a linear installation



▶ Feature on selected models