



Description	EHT8TI	EHT8I	NHT8
Automatic hood	•		
WASH•SAFE CONTROL	•	•	
Sanitation guaranteed	•	•	•
Double skin insulated hood	•	•	
Electrical connection	400V/3N/50Hz convertible on site to 230V/1N or 230/3/50Hz	400V/3N/50Hz convertible on site to 230V/1N or 230/3/50Hz	400V/3N/50Hz convertible on site to 230V/1N or 230/3/50Hz
Number of cycles	3	3	3
Capacity (ETL Sanitation mode)	63 racks/hour 1134 dishes/hour	63 racks/hour 1134 dishes/hour	63 racks/hour 1134 dishes/hour
Capacity (High Productivity mode)*	80 racks/hour 1440 dishes/hour	80 racks/hour 1440 dishes/hour	80 racks/hour 1440 dishes/hour
External dimensions (wxdxh)	667x755x1567	752x755x1567	752x755x1547
External dimensions with ESD (wxdxh)	667x755x2264	752x755x2264	
Basket dimension (mm)	500x500	500x500	500x500
Wash tank capacity (lt.)	24	24	24
Wash pump power (kW)	0,8	0,8	0,8
Boiler power (kW)**	9	9	9
Water consumption (lt./cycle)	2	2	2
Total power (kW)***	9,9	9,9	9,9
Noise level (dBA)	< 63	< 63	< 68
Built-in rinse aid dispenser	•	•	•
Included baskets	1 basket for 18 plates 1 basket for cups 2 cutlery containers	1 basket for 18 plates 1 basket for cups 2 cutlery containers	1 basket for 18 plates 1 cutlery container

* When connected to warm water supply (min. 50 °C)

** 6 kW when connected to warm water supply (at 65 °C)

*** 6,9 kW when connected to warm water supply (at 65 °C)

Electrolux Professional

Viale Treviso, 15
Vallenoncello, 33170 Pordenone - Italy
phone: (+39) 0434 380 1
fax: (+39) 0434 380 201
e-mail: foodservice@electrolux.com

Share more of our thinking at www.electrolux.com/professional

green&clean Hood Type Dishwashers



Thinking of you
Electrolux

green&clean

always with something extra



GREEN

Maximum savings are assured by:

- the low consumption of fresh water (2 lt./cycle)
- the highly efficient rinsing (-33% in running costs, less hot water used)
- the ENERGY SAVING device
- the ZERO LIME device



CLEAN

Excellent washing results regardless of working conditions thanks to:

- the CLEAR BLUE Filtering System
- the very powerful washing circuit
- the unique shape of the spray nozzles and rotating arms



SAFE

Best-in-class sanitation and safety

are guaranteed by:

- the WASH-SAFE CONTROL which provides a constant rinsing temperature of 84 °C, assuring perfect hygienic conditions and total detergent removal



EASY


Optimal visibility and easy operation

both in corner and linear installations due to:


- the innovative angular position of the control panel
- the integrated LED display (on automatic models)



▶ Double skin hood



● Slanted wash arms and ceiling



▶ CLEAR BLUE Filtering System



● 24 liter pressed tank




▶ Continuous Water Softener



▶ ESD Energy Saving Device



▶ ZERO LIME Device



● IP25 protection



● WASH-SAFE CONTROL



● Angular position of the control panel

● Standard feature on all models

▶ Feature on selected models

