

Tumble dryer

D7-190

Features and benefits

- **Intelligent controller offers:**
 - Large display and one control knob for easy program selection
 - Language selection
 - Create new programs in your PC with the Laundry Program Manager, then transfer them to machines via USB port
 - Drying program packages optimized for Economy, Care and Time
 - Service program for adjustment of parameters
- High productivity – 2 full loads per hour
- Low energy consumption for optimal efficiency
- Reversible door hanging for a convenient laundry flow
- Easy access to vital parts from front and rear for simple servicing
- The coin version with Ecopower to avoid over drying of the garments and get a lower energy consumption
- Residual Moisture Control for an accurate drying result and a low energy consumption
- Reversing drum for less tangling of large items

Other options

- Stainless steel base frame, front and drum
- Payment: coinmeter with Ecopower, chipcard reader, CP connection
- Fresh air intake



Images shown are a representation of the product only and variations may occur.

Main specifications		D7-190	
Rated capacity, filling factor 1:18	kg / lb	10.6 / 23	
Rated capacity, filling factor 1:22	kg / lb	8.6 / 19	
Drum, volume	litre	190	
Drum, diameter	ø mm	680	
Heating alternatives:			
EI	kW	6.0 ² / 8.0	
Consumption data¹		EI 6.0 kW ²	EI 8.0 kW
Total time	Min	35	27
Energy consumption	kWh	3.45	3.53
Evaporation	g/min	102	129
Energy water evaporation	kWh/l	0.92	0.94

1. At rated capacity 1:22, 100% cotton load at 50% initial moisture dried to 0%.

2. Special requirement on request.

Produced according to ISO 9001 and ISO 14001.

Certified with CB certificate for Low Voltage Directive and S-mark according to the Machinery Directive. Protection class IP X4D.

Electrical connections					
Heating alternative	Main voltage	Hz	Heating power kW	Total power kW	Recommended fuse A
Electric heated	220–240V 1/1N~	50/60	6.0/8.0	6.4/8.4	32/50
	220–230V 3~	50/60	6.0/8.0	6.4/8.4	20/25
	220–240V 3~	50/60	6.0/8.0	6.4/8.4	16/25
	380–415V 3N/3~	50/60	6.0/8.0	6.4/8.4	10
	440V 3~	60	6.0/8.0	6.4/8.4	10/16
	480V 3~	60	6.0/8.0	6.4/8.4	10/16
	115V 3~	60	4.1	4.5	25

Air connections			D7-190
Air outlet	ø mm		125
Evacuated air, 6.0 kW	m³/h		270
Evacuated air, 8.0 kW	m³/h		290
Pressure drop, 6.0 kW	Max. Pa		380
Pressure drop, 8.0 kW	Max. Pa		350
Sound levels			
Sound power/pressure level at drying ¹			dB(A)
			67/53
Heat emission			
% of installed power, max			15
Shipping data ²			
Weight			net, kg
			99
Shipping volume			m³
			0.83
1. Operating panel		3. Electrical connection	
2. Door opening, ø 400 mm		4. Exhaust connection	

1. Sound power levels measured according to ISO 60704.
2. Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

