

Tumble dryer

D7-425S

Features and benefits

- High productivity – 2 full loads per hour per pocket
- Low energy consumption for optimal efficiency and economy
- Selection of temperature and time for easy operation
- Large door opening for easy loading and unloading
- Easy access to vital parts from front and rear for simple servicing
- The coin version with Ecopower to avoid over drying of the garments and get a lower energy consumption
- With Intelligent control:
 - Large and clear display for easy program selection
 - Easy access with user-friendly interface
 - Language selection
 - Service program for adjustment of parameters
 - USB connection

Other options

- Stainless steel front and drum
- Residual Moisture Control - RMC
- Reversing drum
- Payment: coinmeter with Ecopower, chipcard reader, central payment connection
- High altitude kit for gas heated tumble dryers (>610 m)



Images shown are a representation of the product only and variations may occur.

Main specifications ¹	D7-425S	
Rated capacity, filling factor 1:18	kg / lb	23.5 / 51.7
Rated capacity, filling factor 1:22	kg / lb	19.2 / 42.3
Drum, volume	litre	423
Drum, diameter	Ø mm	832
Heating alternatives:		
Gas	kW / BTU/h	27.5 / 94000
Consumption data²		
Total time	Gas	
Energy consumption	Min	22
Evaporation	kWh	10.2
Energy water evaporation	g/min	440
Max. pressure drop	kWh/l	1.06
	Pa	520

1. Value per pocket.

2. At rated capacity 1:22, 100% cotton load at 50% initial moisture dried to 0%.

Electrical connections					
Heating alternative	Main voltage	Hz	Heating power kW	Total power kW	Recommended fuse A
Gas heated	220-240V 3~	50/60	¹	1.3	10
	380-480V 3~	50/60	¹	1.5	10
	230-240V 1~	50	¹	1.5	10

1. Total power and recommended fuse does not depend on the heating power in those cases.

Gas and air connections ¹		D7-425S
Gas	ISO 7/1-R1	3/4"
Gas pressure, Natural gas	Pa mbar	2000-2500 20-25
Gas pressure, Propane	Pa mbar	2800-5000 28-50
Air outlet	Ø mm	200
Evacuated air	m ³ /h	1700
Pressure drop	Max. Pa	520

Sound levels	
Sound power/pressure level at drying ²	dB(A)

Heat emission	
% of installed power, max	15

Shipping data ³		
Weight	net, kg	440
Shipping volume	m ³	2.8
1. Operating panel	4. Gas connection	
2. Door opening, Ø 687 mm	5. Exhaust connection	
3. Electrical connection		

1. The default gas appliances are built to run on either GNH or LPG gas where shall be installed at not over than 610 m (2001 ft) high altitude otherwise a kit for high altitude must be installed to the machine. For the kit No. please refer to the spare parts list.

2. Sound power levels measured according to ISO 60704.

3. Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

