

# Drying cabinet

## DC6-14

Drying Cabinets have no mechanical action and are used to efficiently dry bulky items such as workwear/overalls/gloves and boots or delicate items such as silk and linen



### Priority on people

Ergonomic design, with user friendly positioning of door handle, control panel and suitable for disabled users

- Easy operation with 2 automatic drying programs, which will stop once the load is dry
- Braille script
- Large doors and opening angles for easy access
- One extensible hanger for easy loading/unloading
- Hanging ability in the short end for smaller garments
- Flexible installation with adjustable feet



### Outstanding productivity

Time saving when used instead of flat or hang drying. The door can be opened a short moment without stopping the drying process

### Safety

Option to activate child safety start lock



*Images shown are a representation of the product only and variations may occur.*

Main specifications <sup>1</sup>		DC6-14
Rated capacity	kg	10
Evaporation	g/min	95
Drying time	min	58
Energy consumption	kWh	9.0
Energy/load of linen	kWh/kg	0.82
Energy/water evaporated	kWh/l	1.49

1. Mixed cotton load centrifuged to 55% residual moisture.

Electrical connections					
Heating alternative	Main voltage	Hz	Heating power kW	Total power kW	Recommended fuse A
Electric heated machines	400V 3N -	50	9.0	9.1	16 slow-blow

Connections <sup>1</sup>		DC6-14
Air outlet	ø mm	200
Evacuated air	m <sup>3</sup> /h	400
Pressure drop	Max. Pa	0
Sound levels		
Sound power/pressure level at drying <sup>2</sup>	dB(A)	<70
Weight <sup>3</sup>		
	net, kg	175
1. Operating panel	3. Air outlet ø 200 mm	
2. Electrical connection		

1. Duct fan is required.  
2. Sound power levels measured according to ISO 60704.  
3. Applies to assembled drying cabinets.

Colour of front and side panels is silver grey and handle is dark blue.

