

Drying cabinet

DC6-4

Drying Cabinets have no mechanical action and are used to efficiently dry bulky items such as workwear/overalls/gloves and boots or delicate items such as silk and linen



Priority on people

Ergonomic design, with user friendly positioning of door handle, control panel and suitable for disabled users

- Easy operation with 2 automatic drying programs, which will stop once the load is dry
- Relief script
- Insulated doors for quiet operation and robust design
- 30 extensible hangers for easy loading/unloading
- Flexible installation with adjustable feet
- Reversible door - left or right hanging



Outstanding productivity

Time saving when used instead of flat or hang drying. The door can be opened a short moment without stopping the drying process

Safety

Option to activate child safety start lock

Accessories

Shoe rack to make it easier to dry shoes and boots.

Glove hanger for more efficient drying of gloves, hats etc.

- Shoe rack: 988704087, 432730568
- Glove hanger: 988704085, 432730569



Images shown are a representation of the product only and variations may occur.

Main specifications ¹		DC6-4
Rated capacity	kg	4
Evaporation	g/min	19
Drying time	min	105
Rated input	kW	1.5
Energy/load of linen	kWh/kg	0.6
Energy/water evaporated	kWh/l	1.27

1. Applies to 4 kg dry weight cotton with 50% residual moisture.

Electrical connections					
Heating alternative	Main voltage	Hz	Heating power kW	Total power kW	Recommended fuse A
Electric heated machines	230V 1-	50/60	1.5	1.5	10

Connections		DC6-4
Air outlet	ø mm	100
Evacuated air	m ³ /h	50

Sound levels	
Sound power/pressure level at drying ¹	dB(A)
	57/41

Weight	
	net, kg
1. Operating panel	2. Air outlet ²
	56

1. Sound power levels measured according to ISO 60704.
 2. Connected with supplied drive interruption and hose.

Colour of front and side panels is silver grey and handle is dark blue.

