

# Drying cabinet

## DC6-4

Drying Cabinets have no mechanical action and are used to efficiently dry bulky items such as workwear/overalls/gloves and boots or delicate items such as silk and linen



### Priority on people

Ergonomic design, with user friendly positioning of door handle, control panel and suitable for disabled users

- Easy operation with 2 automatic drying programs, which will stop once the load is dry
- Relief script
- Insulated doors for quiet operation and robust design
- 30 extensible hangers for easy loading/unloading
- Flexible installation with adjustable feet
- Reversible door - left or right hanging



### Outstanding productivity

Time saving when used instead of flat or hang drying. The door can be opened a short moment without stopping the drying process

### Safety

Option to activate child safety start lock

## Accessories

Shoe rack to make it easier to dry shoes and boots.

Glove hanger for more efficient drying of gloves, hats etc.

- Shoe rack: 988704087, 432730568
- Glove hanger: 988704085, 432730569



Images shown are a representation of the product only and variations may occur.

Main specifications <sup>1</sup>		DC6-4
Rated capacity	kg	4
Evaporation	g/min	19
Drying time	min	105
Energy consumption	kWh	1.5
Energy/load of linen	kWh/kg	0.6
Energy/water evaporated	kWh/l	1.27

1. At rated capacity 4 kg, 100% cotton load at 50% initial moisture dried to 0%

Electrical connections					
Heating alternative	Main voltage	Hz	Heating power kW	Total power kW	Recommended fuse A
Electric heated machines	230V 1-	50/60	1.5	1.5	10

Connections		DC6-4
Air outlet	ø mm	100
Evacuated air	m <sup>3</sup> /h	50
Sound levels		
Sound power/pressure level at drying <sup>1</sup>	dB(A)	58/43
Weight		
	net, kg	56
1. Operating panel	2. Air outlet <sup>2</sup>	

1. Sound power levels measured according to ISO 60704.  
 2. Connected with supplied drive interruption and hose.

Colour of front and side panels is silver grey and handle is dark blue.

