

# Drying cabinet

## DC6-8

Drying Cabinets have no mechanical action and are used to efficiently dry bulky items such as workwear/overalls/gloves and boots or delicate items such as silk and linen



### Priority on people

Ergonomic design, with user friendly positioning of door handle, control panel and suitable for disabled users

- Easy operation with 2 automatic drying programs, which will stop once the load is dry
- Relief script
- Insulated doors for quiet operation and robust design
- 18-20 extensible hangers for easy loading/unloading, reversable
- Flexible installation with adjustable feet



### Outstanding productivity

Time saving when used instead of flat or hang drying. The door can be opened a short moment without stopping the drying process

### Safety

Option to activate child safety start lock

## Accessories

Shoe rack to make it easier to dry shoes and boots.

Glove hanger for more efficient drying of gloves, hats etc.

Hanger which makes hanging of garments easier.

- Glove hanger: 988704088, 432730570
- Hanger: 988704089, 432731032



Images shown are a representation of the product only and variations may occur.

Main specifications <sup>1</sup>		DC6-8
Rated capacity	kg	8
Evaporation	g/min	84
Drying time	min	47
Rated input	kW	6.2
Energy/load of linen	kWh/kg	0.6
Energy/water evaporated	kWh/l	1.14

1. Applies to 8 kg dry weight cotton with 50% residual moisture.

Electrical connections					
Heating alternative	Main voltage	Hz	Heating power kW	Total power kW	Recommended fuse A
Electric heated machines	230V 1N-	50	6.0	6.2	30
	400V 3N-	50	6.0	6.2	10

Connections		DC6-8
Air outlet	∅ mm	125
Evacuated air	m <sup>3</sup> /h	200
Pressure drop <sup>1</sup>	Max. Pa	70
Sound levels		
Sound power/pressure level at drying <sup>2</sup>	dB(A)	<70
Weight		
	net, kg	134
1. Operating panel		3. Air outlet <sup>3</sup>
2. Electrical connections		

1. Corresponds to a 23 m straight wiring duct, with a diameter of 160 mm exhaust air connection approx. 70 m straight wiring duct.

2. Sound power levels measured according to ISO 60704.

3. Fixed connection to separate duct or general ventilation system.

Colour of front and side panels is silver grey and handle is dark blue.

