

Drying cabinet

DC6-8

Drying Cabinets have no mechanical action and are used to efficiently dry bulky items such as workwear/overalls/gloves and boots or delicate items such as silk and linen



Priority on people

Ergonomic design, with user friendly positioning of door handle, control panel and suitable for disabled users

- · Easy operation with 2 automatic drying programs, which will stop once the load is dry
- Relief scrip
- · Insulated doors for quiet operation and robust design
- 18-20 extensible hangers for easy loading/unloading, reversable
- · Flexible installation with adjustable feet



Outstanding productivity

Time saving when used instead of flat or hang drying. The door can be opened a short moment without stopping the drying process

Safety

Option to activate child safety start lock

Accessories

Shoe rack to make it easier to dry shoes and boots.

Glove hanger for more efficient drying of gloves, hats etc.

Hanger which makes hanging of garments easier.

- · Glove hanger: 988704088, 432730570
- · Hanger: 988704089, 432731032



Images shown are a representation of the product only and variations may occur.

Main specifications ¹		DC6-8		
Rated capacity	kg	8		
Evaporation	g/min	84		
Drying time	min	47		
Energy consumption	kWh	6.2		
Energy per load	kWh/kg	0.6		
Energy/water evaporated	kWh/I	1.14		

At rated capacity 8 kg, 100% cotton load at 50% initial moisture dried to 0%

Electrical connections						
Heating alternative	Main voltage	Hz	Heating power kW	Total power kW	Recommen- ded fuse A	
Electric heated machines	230V 1N~	50	6.0	6.2	30	
	400V 3N~	50	6.0	6.2	10	

	DC6-8
ø mm	125
m³/h	200
Max. Pa	70
dB(A)	69/55
net, kg	134
3. Air outlet ³	
	m³/h Max. Pa dB(A)



Corresponds to a 23 m straight wiring duct, with a diameter of 160 mm exhaust air connection approx. 70 m straight wiring duct.
Sound power levels measured according to ISO 60704.
Fixed connection to separate duct or general ventilation system.

Colour of front and side panels is silver grey and handle is dark blue.

