

Washer extractor

EUD-618CV



Exceptional savings and effortless use



Priority on people

Certified ergonomic design with a human-centered approach for an outstanding user experience

- ClarusVibe microprocessor and 7" color TS control: intuitive, fully editable programs, multi-language, on-screen statistics, fully controlling the detergent pumps
- Very easy connection to Jetsave and Dosave with one cable for power supply and one for dosing signals
- Simple connection to all generic pumps
- Connection to up to 15 pumps



Long-term savings

Innovative features designed for lowest possible water, energy and detergent consumption, to save money and time, and embrace a sustainable lifestyle

- Automatic Savings weighs the linen and adjusts the water level to the amount of linen, saving water and energy at less than full load
- Intelligent Dosing ensures that the precise amount of chemicals will be added automatically according to the weight of the load, saving chemicals
- Power Balance measures, corrects the unbalance and adjusts the G force in real time, maximizing the dewatering, saving money and time in the drying process



Pure control

Monitoring of the status of the equipment and performance from anywhere, allowing to take action to improve the business

- Washers connectable to OnE Laundry, the personal assistant for hygiene validation, process management and revenue management



Global Advanced Hygiene

Global Advanced Hygiene program package^I with proven log 6 reduction^{II} disinfection of textiles through the laundry process, fulfilling the criteria of all local approved standards

I. Programs available in the standard library of all products, excluding products for specific segments where water temperature is not controllable.

II. Log 6 reduction equals to 99,9999% viral infectivity reduction. The efficacy of reduction of SARS-CoV-2 and other pathogens in the process is confirmed by RISE (The Research Institute of Sweden) on the basis of Electrolux Professional laboratory data.



Images shown are a representation of the product only and variations may occur.

Main options and accessories

- Integrated Savings is measuring the load in real time, ensuring optimization of the load and maximum productivity. IS provides also extended machine lifetime through the unique overload protection function, as machine will not start if overloaded. In addition, it will reduce water and energy consumption at less than full load
- Connection to booking- /payment- system or coin meter

Main specifications		EUD-618CV			
Rated capacity, filling factor 1:9	kg/lb	8 / 18			
Drum, volume	litre/ft ³	75 / 2.6			
Drum, diameter	ø mm/inch	520 / 20 1/2			
Extraction	rpm	1245			
G-factor		450			
Standard heating alternatives	electricity, kW	5.4 / 7.5			
Low energy heating alternatives	electricity, kW	2.0 / 3.0			
	steam	x			
Consumption data "Warm" ¹	non-heated	x			
		EI		Steam ²	
		Full load, 8 kg / 18 lb	Half load, 3,75 kg / 8,3 lb ³	Full load, 8 kg / 18 lb	Half load, 3,75 kg / 8,3 lb ³
Total time	Min	25.5	24.5	25.5	24.5
Water consumption (cold+hot)	litre/gallon	52/14 + 4/1	34/9 + 3/1	56/15 + 0/0	37/10 + 0/0
Energy consumption (motor/heating/hot water)	kWh	0.1/0.55/0.25	0.1/0.35/0.2	0.1/-	0.1/-
Steam consumption	kg/lb	-	-	1.2/2.6	0.8/1.8
Residual moisture	%	50	51	50	51

1. Water temperature 59°F cold water and 149°C hot water.

2. Depending on steam pressure.

3. Programs with AS.

Electrical connections					
Heating alternative	Main voltage	Hz	Heating power kW	Total power kW	Recommended fuse ITCB A
Electric heated	208-240V 1-	60	2.0/3.0	5.2/3.4	15/20
	208-240V 1-	60	5.4/7.5	5.7/7.8	30/50
	208-240V 3-	60	2.0/3.0	5.2/3.4	15/15
	208-240V 3-	60	5.4/7.5	5.7/7.8	20/25
	440V 3-	60	5.4/7.5	5.7/7.8	15/15
	480V 3-	60	5.4/7.5	5.7/7.8	15/15
Non heated/Steam heated	120/440/480 1/3-	60	1	1.0	15
	208-240V 1-	60	1	0.9	15

1. Total power and recommended fuse does not depend on the heating power in those cases.

Water and steam connection		EUD-618CV
Water valves	DN/inch	20 / 3/4
Water pressure	psi	30-90
Capacity at 300 kPa / 44 psi	l/min / gallon/min	20 / 5
Drain valve	ø mm/inch	50 or 75 / 1 15/16 or 3
Draining capacity	l/min / gallon/min	170 / 45
Steam valve	DN/inch	15 / 1/2
Steam pressure	psi	40-90
Liquid detergent supplies		5

Floor requirements	
Frequency of the dynamic force	Hz 20.8
Floor load at max extraction	kN / lbs force 1.9 ± 0.5 / 417 ± 110

Sound levels	
Sound power/pressure level at extraction ¹	dB(A) 73/59
Sound power/pressure level at wash ¹	dB(A) 61/47

Heat emission	
% of installed power, max	5

Shipping data ²	
Weight	net, kg/lbs 158 / 348
Shipping volume	m ³ /ft ³ 0.81 / 29

Accessories	
Steel base	x
Hose kits for water or steam	x
Fluff collector	x

1. Display	7. Re-used water from tank/pump or Liquid detergent supply
2. Door opening ø 310 mm / 12 3/16 inch	8. Drain
3. Detergent box	9. Liquid detergent supply
4. Cold water	10. Electrical connection
5. Hot water	11. Steam connection
6. Cold/Hot water or Re-used water with network pressure (option)	

1. Sound power levels measured according to ISO 60704.

2. Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

Silver grey and dark blue color samples can be ordered on part number 472998313.

