

# Multi-Form Finishers

FFM1, FFM2



## Features and benefits

- Even distribution of steam moistens the fabric to remove creases
- For shirts and jackets/coats/labcoats/whitecoats processing
- Hot air blowing presses and dries the fabric
- Pneumatic front clamp holds the garment in place
- Adjustable air blowing baffle, suitable for various fabric types
- Available either for central steam (FFM1) or with built-in boiler (FFM2)
- Self-contained and integral steam boiler simplifies the installation (FFM2) and can operate a collar & cuffs press too, for a complete shirts group
- Air operated cuff clamp improves the sleeve finish

## Main options

- Water spray gun with support (FFM2)
- Water spray gun with support and condenser (FFM1)

Electrical connections		FFM1	FFM2
Voltage			
208-240V 3 AC 50/60 Hz	kW	2	29
400-415V 3N AC 50 Hz	kW	2	29

Steam and air connections		FFM1	FFM2
Steam	DN	15	-
Recommended steam pressure	kPa	500	-
Steam consumption	kg/h	25-30	-
Condensate	DN	15	-
Compressed air	DN	8	-
Recommended air pressure	kPa	700	700
Air consumption	l/h	150	150
Water supply	ømm	-	13
Boiler drain	DN	-	15

Shipping data <sup>1</sup>			
Weight	net, kg	196	218
	crated, kg	238	260
	boxed, kg	286	308

1. Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

Dimensions in mm	FFM1	FFM2
A	2000	2000
B	1600	1600
C	1700	1700
D	455	455
E	780	780
F	490	490
G	60	60
H	130	130
I	215	215
K	570	570
L	170	170
M	1000	1000

- |                          |  |
|--------------------------|--|
| 1. Control panel         | 5. Air connection                      |
| 2. Electrical connection | 6. Water drain (built-in boiler only)  |
| 3. Steam connection      | 7. Water supply (built-in boiler only) |
| 4. Condensate            |  |

