

Vacuum ironing tables

FIT2A, FIT2B



Model FIT2A shown

Features and benefits

- Heated to keep the working surface dry
- Utility shape for general purpose
- Integral vacuum fan holds the garment in place and dries the fabric after pressing
- Steam electric iron c/w separator versatile (only available for FIT2B)
- Integral boiler for simple installation (only available for FIT2B)

Main options

- Steam electric iron c/w separator (only available for FIT2A)
- Free standing boiler for simple installation (only available for FIT2A)
- Cold spotting gun(s) for removal of spots
- Steam gun for removal of spots
- Steam/air gun for removal of spots
- Sleeve arm for pressing awkward shapes
- Spotting arm for spotting
- Overhead gantry to support iron hoses
- Iron balancer reduces operator fatigue
- Light, illuminates the working area

Electrical connections		FIT2A	FIT2B
Voltage			
208-240V 1 AC 50/60 Hz	kW	0.85	-
208-240V 3 AC 50/60 Hz	kW	-	5.6
380-415V 3/3N AC 50/60 Hz	kW	-	5.6

Steam, air and vacuum connections		FIT2A	FIT2B
Steam	DN	10	-
Recommended steam pressure	kPa	400-600	200-250
Steam consumption	kg/h	4	-
Condensate	DN	15	-
Water supply	ø mm	-	12
Boiler drain	DN	-	10
Compressed air	DN	8	-
Recommended air pressure	kPa	500-700	600-700
Air consumption	l/min	300	300
Vacuum outlet	ø mm	100	100

Shipping data ¹			
Weight	net, kg	70	105
	crated, kg	100	135
	boxed, kg	140	175

1. Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

Dimensions in mm	FIT2A	FIT2B
A	1520	1600
B	435	470
C	920	920

1. Control panel
2. Electrical connection
3. Steam connection
4. Condensate
5. Air connection
6. Boiler drain
7. Water supply
8. Vacuum outlet

