

Vacuum ironing tables

FIT3A, FIT3B



Features and benefits

- Heated to keep the working surface dry
- Utility shape for general purpose
- Integral vacuum fan holds the garment in place and dries the fabric after pressing
- Height adjustable

Main options

- Steam electric iron c/w separator
- Integral boiler for simple installation
- Steam gun for removal of spots
- Steam/air gun for removal of spots
- Light, illuminates the working area
- Swinging arm with sleeves ironing shape
- Swinging arm with heated sleeves ironing shape
- Swinging arm with spotting shape plus receiving tank for liquids
- Light, illuminates the working area

Electrical connections		FIT3A	FIT3B
Voltage			
230V 1/N AC, 50 Hz	kW(A)	2.4 (16)	2.7 (16)
208-240V 1 AC, 60 Hz	kW(A)	2.4 (16)	2.7 (16)
Voltage, built-in boiler (3.3 kW)			
400V 3/N AC, 50 Hz	kW(A)	5.7 (10)	6.0 (10)
208-240V 3 AC, 60 Hz	kW(A)	5.7 (10)	6.0 (10)

Shipping data ¹			
Weight	net, kg	56	62
	crated, kg	71	77
Shipping volume	m ³	0.53	0.76

1. Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

Dimensions in mm		FIT3A	FIT3B
A		1390	1630
B		540	635
C		750-930	750-930
D		1100	1300
E		1290	1490
F		1020	1230
G		380-560	380-560
H		400	500
I		350	350
J		1000 (1200)	1000 (1200)

1. Control panel

2. Electrical connection

