

Laundry press, air operated collar and cuff FPA6-WC



Features and benefits

- High temperature polished head, dries the fabric and gives it a flat finish
- High pressure, achieves an excellent finish
- Adjustable pressure regulator, for pressing different fabrics
- Air operated, reduces operator fatigue
- Safety two button closing improves operator safety
- Padded buck reduces impressions
- Adjustable release timer, simplifies the operation and ensures consistent results

Main options

- Facilities that simplify the installation
 - Integral air compressor
 - Integral steam boiler

Electrical connections		Standard	Built-in boiler	Built-in air compressor
Voltage				
208-240V 1 AC 50/60 Hz (External boiler)	kW	0.2	-	1.1
208-240V 3 AC 50/60 Hz (Internal boiler)	kW	-	8.4	-
400-415V 3N AC 50/60 Hz (Internal boiler)	kW	-	10.4/12.4/15.4/ 18.4	-

Steam, air and vacuum connections				
Steam	DN	15	-	15
Recommended steam pressure	kPa	600	-	600
Steam consumption	kg/h	12-13	-	12-13
Condensate	DN	15	15	15
Compressed air	DN	10	10	-
Recommended air pressure	kPa	700	700	-
Air consumption	l/min	50	50	50
Boiler drain (Internal boiler)	DN	-	15	-

Shipping data ¹				
Weight	net, kg	300	300	300
	crated, kg	360	360	360
	boxed, kg	440	440	440

1. Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

Dimensions in mm			
A	970	970	970
B	1135	1135	1135
C	1220	1220	1220
D	1530	1530	1530
E	1070	1070	1070
F	780	780	780
G	445	445	445
H	190	190	190
I	150	150	150
K	505	505	505
L	300	300	300
<div> <div>1. Control panel</div> <div>2. Electrical connection</div> <div>3. Steam connection</div> <div>4. Condensate</div> <div>5. Air connection</div> <div>6. Boiler drain (built-in boiler only)</div> <div>7. Water supply (built-in boiler only)</div> </div>			

