

# Steam boiler

## FSB 3.3



### Features and benefits

- Capacity of 5 kg steam/h
- Steam boiler with electronic water level sensor, which ensures correct water level and long lifetime of the heating elements
- Standard with two steam irons
- Simple installation and maintenance

### Main options

- Pump (for water pressure less than 200 kPa) with or without feed tank
- Pivoting wheels
- Steam or steam/air spotting gun

Electrical connections		FSB 3.3
Voltage		
230V 1 AC 50/60 Hz	kW	3.3
208-240V 3 AC 50/60 Hz	kW	3.3
380-415V 3+N AC 50/60 Hz	kW	3.3
Boiler heating		
Steam output: 4.5 kg/h	kW	3.3

Steam outlet, drain and water connections		FSB 3.3
Working pressure	kPa	280
Pump	kW	0.3
Iron heating	kW	0.8
Water supply	Internal ø mm	13
Boiler drain	DN	15

Boiler details		
Vessel capacity	l	5

Shipping data <sup>1</sup>		
Weight	net, kg	73
	with packing, kg	78

1. Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

Dimensions in mm		FSB 3.3
A		420
B		380
C		1400
D		790

1. Water supply  
2. Overflow hose  
3. Tank breather pipe

