

Tumble dryer

TD6-6



Exceptional savings and effortless use



Priority on people

Certified ergonomic design with a human-centered approach for an outstanding user experience

- Reversible door hanging for a convenient laundry flow
- Easy access to vital parts from the top and rear for simple servicing
- Stainless steel drum



Long-term savings

Innovative features to save money and time, and embrace a sustainable lifestyle

- Residual Moisture Control for an accurate drying result and a low energy consumption



Pure control

Monitor your equipment and performance from anywhere, allowing to take action and to improve your business with OnE Laundry - the personal assistant for hygiene validation management, process management and revenue management (optional)



Outstanding productivity

- Reversing drum minimizes wrinkles and drying time to get an effective and even drying performance
- For optimal performance the room temperature should not exceed 25°C for the condensed version

Other options

- Stainless steel front
- Stainless steel base frame
- Connectable to booking-/payment system or coin meter
- Stacking frame for mounting TD6-6 on top of WH6-6
- Integrated condense system



Images shown are a representation of the product only and variations may occur.

Main specifications		TD6-6		Condense
Rated capacity, filling factor 1:22	kg / lb	6 / 13		6 / 13
Drum, volume	litre	130		130
Drum, diameter	ø mm	575		575
Heating alternatives:				
EI	kW	3.2 / 5.1		3.0
Consumption data¹		EI 3.2 kW	EI 5.1 kW	EI 3.0 kW
Total time	Min	62	41	63
Energy consumption, full load	kWh	3.05	3.02	3.3
Evaporation	g/min	48	73	47
Energy water evaporation	kWh/l	1.03	1.02	1.11

1. At rated capacity 1:22, 100% cotton load at 50% initial moisture dried to 0%.

Produced according to ISO 9001 and ISO 14001.

Certified with CB certificate for Low Voltage Directive and S-mark according to the Machinery Directive. Protection class IP X4D.

Electrical connections					
Heating alternative	Main voltage	Hz	Heating power kW	Total power kW	Recommended fuse A
Electric heating	220-240V 1-	50/60	3.2	3.5	16
	220-240V 3-	50/60	3.2/5.1	3.5/5.4	13/16
	380-415 3-	50/60	5.1	5.4	10
	440/480V 3-	60	5.1	5.4	10
Condense	220-240V 1-	50/60	3.0	3.3	16
	220-240V 3-	50/60	3.0	3.3	13
	380-415 3-	50/60	3.0	3.3	10
	440/480V 3-	60	3.0	3.3	10

Connections		TD6-6	Condense
Air outlet	∅ mm	100	-
Maximum air flow	m ³ /h	240	-
Condensate		-	1/2"
Maximum static back pressure	Pa	80	-
Sound levels			
Sound power/pressure level at drying ¹	dB(A)	67/53	67/53
Heat emission			
% of installed power, max		15	15
Shipping data ²			
Weight	net, kg	58	57
Shipping volume	m ³	0.51	0.63
1. Operating panel		4. Exhaust connection	
2. Door opening, ∅ 370 mm		5. Condense connection	
3. Electrical connection			

1. Sound power levels measured according to ISO 60704.
2. Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.
Silver grey and dark blue color samples can be ordered on part number 472998313.

