

Tumble dryer

TD7-8

Vented electric / gas

High-Performance Commercial Drying • Low operating cost • Built to Last

With an unmatched Drying Performance this exceptional professional tumble dryer deliver consistently high quality results from Swedish technology engineered for precision.

The winner takes it all

With the right combination together with our WP7 washer serie, you can reach unbelievable 15% energy saving in drying.



Longest lifetime: 40 000 cycles.

Durability is the new profit: the only investment that wins your trust cycle by cycle.



Optimized airflow and heating, tailored for electric, gas, and heat pump models, secures fast, reliable drying cycles.



Moisture Balance ensures accurate drying whilst saving energy, preventing over-drying and textile damage. (Optional).

OnE Connected

Monitor and control all the operations behind your laundry room, quantifying savings and productivity. Anytime. Anywhere.



Fully personalized 4.3" touch panel: UniVibe gives the operator an easy and smooth experience and you will have all the possibilities to adapt for your business requirements.



Looking for a low energy consumption tumble dryer? Please see our separate Product Data Sheet for more details.

Main specifications		TD7-8
Rated capacity, filling factor 1:15	kg / lb	9.0 / 19.8
Rated capacity, filling factor 1:18	kg / lb	7.5 / 16.5
Rated capacity, filling factor 1:22	kg / lb	6.1 / 13.4
Drum, volume	litre	135
Drum, diameter	ø mm	575
Heating alternatives:		
El	kW	3.0 / 4.5 / 6.0
Gas	kW / BTU/h	7.0 / 23900

Consumption data ¹		El 3.0 kW	El 4.5 kW	El 6.0 kW	Gas
Total time	min	57	40	30	30
Energy consumption	kWh	3.11	3.11	3.04	3.67
Evaporation	g/min	54	78	104	101
Energy water evaporation	kWh/l	1.01	1.01	0.99	1.20

1. At rated capacity 1:22, 100% cotton load at 50% initial moisture dried to 0%.






Electrical connections					
Heating alternative	Main voltage	Hz	Heating power kW	Total power kW	Recommended fuse A
Electric heated machines	220-240V 1/1N-	50/60	3.0/4.5/6.0	3.3/4.8/6.3	16/25/32
	220-240V 3~	50/60	4.5/6.0	4.8/6.3	13/20
	380-415V 3N/3~	50/60	4.5/6.0	4.8/6.3	10/10
	440/480V 3~	60	6.0	6.3	10
Gas heated machines	220-480V 1/1N/3/3N-	50/60	1	0.3	10

1. Total power and recommended fuse does not depend on the heating power in those cases.

Gas and air connections ¹		
Gas	ISO 7/1-R	1/2"
Gas pressure, Natural gas	Pa	2000
	mbar	20
Gas pressure, Propane	Pa	2800-5000
	mbar	28-50
Air outlet	ø mm	125
Evacuated air, electric, 3.0/4.5 kW	m ³ /h	150
Evacuated air, electric, 6.0 kW	m ³ /h	220
Evacuated air, gas, 7.0 kW	m ³ /h	280
Pressure drop, electric, 3.0/4.5 kW	Max. Pa	350
Pressure drop, electric, 6.0 kW	Max. Pa	270
Pressure drop, gas, 7.0 kW	Max. Pa	230

Sound levels	
Sound power/pressure level at drying ²	dB(A)
	63/48
Heat emission	
% of installed power, max	15
Shipping data ³	
Weight	net, kg
	109
Shipping volume	m ³
	0.81

1. The default gas appliances are built to run on either GNH or LPG gas where shall be installed at not over than 610 m (2001 ft) high altitude otherwise a kit for high altitude must be installed to the machine. For the kit No. please refer to the spare parts list.
2. Sound power levels measured according to ISO 60704.
3. Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.



Options and accessories

- Insulated glass door keeps the door cool on the outside and heat on the inside, so the room temperature is not affected
- Lagoon Advanced Care
- Door, front and side panels are available in stainless steel
- Connectable to booking-/payment system or coin meter
- Base and stacking kit available for a combination with washer but also dryer on dryer

