

# Drying cabinet

## DC6-10 with heat pump

**Drying Cabinets have no mechanical action and are used to efficiently dry bulky items such as workwear/overalls/gloves and boots or delicate items such as silk and linen**



### Priority on people

Ergonomic design, with user friendly positioning of door handle, control panel and suitable for disabled users

- Easy operation with 2 automatic drying programs, which will stop once the load is dry
- Braille script
- Insulated doors for quiet operation and robust design
- 20 extensible hangers for easy loading/unloading, reversible
- Flexible installation with adjustable feet



### Long-term savings

By using a Drying Cabinet with a Heat Pump, not only can you avoid exhaust connection you also achieve very low energy consumption. Comes with a built in condensing pump which can handle 0.5m pressure height



### Productivity

Time saving when used instead of flat or hang drying. The door can be opened a short moment without stopping the drying process

### Safety

Option to activate child safety start lock

### Other

- Shelf for flat drying
- Shelf for flat drying
- Built in work light



Main specifications		DC6-10
Rated capacity	kg	10
Evaporation*	g/min	55
Drying time cotton**	min	60
Heat pump	kW	2.6
Energy/load of linen	kWh/kg	0.31
Energy/water evaporated	kWh/l	0.62

\* Applies to 6.5 kg dry weight cotton with 50% residual moisture.

\*\* The drying cabinet reconditions 5 minutes after the textiles have dried.

<b>Electrical connection</b>		<b>DC6-10</b>
Voltage 220-240V 1AC 50-60 Hz		
Traditional thread locker	kW(A)	2.6 (13)
Automatic circuit breaker	kW(A)	2.6 (13)
<b>Refrigerant</b>		<b>R407C</b>
<b>Weight</b>		
	net, kg	205
<b>Sound level</b>		
Pressure level*	dB(A)	<70
<b>Heat emission</b>		
Average heat emission per drying cycle**		1.1
<b>Dimensions in mm</b>		
A	Width	1395
B	Depth	650
C	Height	1915
D		1930
E		15
F		1080
G		495
H		470
I		620
J		970
K		850
<b>1</b> Operating panel <b>2</b> Condensation nipple <b>3</b> 2.5 m connecting cable included		



Colour of front and side panels is silver grey and handle is dark blue.

\* Sound power levels measured according to ISO 60704.

\*\* For assistance with dimensioning necessary ventilation needs, contact authorized ventilation technician.

