

# Drying cabinet

## DC6-14 with heat pump

**Drying Cabinets have no mechanical action and are used to efficiently dry bulky items such as workwear/overalls/gloves and boots or delicate items such as silk and linen**



### Priority on people

Ergonomic design, with user friendly positioning of door handle, control panel and suitable for disabled users

- Easy operation with 2 automatic drying programs, which will stop once the load is dry
- The control panel has Braille for the visually impaired
- Large doors and opening angles for easy access
- One extensible hanger for easy loading/unloading
- Hanging ability in the short end for smaller garments
- Flexible installation with adjustable feet



### Long-term savings

By using a Drying Cabinet with a Heat Pump, not only can you avoid exhaust connection you can reach energy saving of 70% compared with an electric vented version. There are two options of heat pump version



### Productivity

Time saving when used instead of flat or hang drying. The door can be opened a short moment without stopping the drying process

### Safety

Option to activate child safety start lock



Main specifications		DC6-14
Rated capacity	kg	10
Evaporation*	g/min	80
Drying time cotton*	min	69
Heat pump	kW	2.6
Energy/load of linen	kWh/kg	0.22
Energy/water evaporated	kWh/l	0.40

\* Mixed cotton load centrifuged to 55% residual moisture.

<b>Electrical connection</b>		<b>DC6-14</b>
Voltage		
400V 3N AC 50 Hz	kW(A)	2.6(10)
<b>Sound level</b>		
Pressure level*	dB(A)	<70
<b>Heat emission</b>		
Average heat emission per drying cycle used to assess ventilation need**		kW
		1.2
<b>Weight</b>		
		net, kg
		250***
<b>Dimensions in mm</b>		
A	Width	1805
B	Depth	800
C	Height	1805
D		875
E		1560
F		900
G		2245
H		-
I		850
J		1180
1 Drain for condense water $\varnothing$ 32 mm		
2 Electrical connection		
3 Operating panel		



\* Sound power levels measured according to ISO 60704.

\*\* For assistance with dimensioning necessary ventilation needs, contact authorized ventilation technician.  
For sufficient ventilation all sources introducing heat need to be taken into account plus all other parameters effecting the ventilation need. Climate zone, building parameters, room size, etc.

\*\*\* Applies to assembled drying cabinets.

Colour of front and side panels is silver grey and handle is dark blue.

