

Rectangular Vacuum Ironing Tables

FIT5A, FIT5B



Features and benefits

- Heated, to keep the working surface dry
- Rectangular, has a large working area
- Two available sizes
- Integral vacuum fan holds the garment in place and dries the fabric after pressing

Main options

- Steam electric iron c/w separator versatile
- Integral steam boiler for simple installation
- Free standing boiler, for simple installation
- Overhead gantry to support iron hoses
- Iron balancer, reduces operator fatigue
- Light, illuminates the working area
- Wide range of swivelling buck shapes for specific pressing operations

| Electrical connections (including iron) | | FIT5A | FIT5B |
|--|------------|-------|-------|
| Voltage | | | |
| 200-240V 1 AC 50/60 Hz | kW | 2.8 | 3.8 |
| 208-240V 3 AC 50/60 Hz | kW | - | - |
| 300-415V 3/3N AC 50/60 Hz | kW | - | - |
| Voltage, built-in boiler (3.3kW) | | | |
| 208-240V 3 AC 50/60 Hz | kW | 6.1 | 7.1 |
| 380-415V 3/3N AC 50/60 Hz | kW | 6.1 | 7.1 |
| Steam, air and vacuum connection | | | |
| Steam | DN | 10 | 10 |
| Rec. steam pressure | kPa | 550 | 550 |
| Steam consumption | kg/h | 3-5 | 3-5 |
| Condensate | DN | 15 | 15 |
| Water supply | mm | 12 | 12 |
| Boiler drain | DN | 10 | 10 |
| Shipping data | | | |
| | net, kg | 150 | 150 |
| | crated, kg | 185 | 185 |
| | boxed, kg | 225 | 225 |
| Dimensions in mm | | | |
| A Width | | 1200 | 1600 |
| B Depth | | 700 | 850 |
| C Height | | 880 | 880 |
| D | | 860 | 860 |
| E | | 1410 | 1810 |
| F | | 620 | 620 |
| G | | 500 | 500 |
| H | | 1150 | 1150 |
| I | | 860 | 860 |
| 1 Control Panel 2 Electrical connection 3 Steam connection 4 Condensate 5 Water supply - internal boiler only 6 Boiler drain - internal boiler only | | | |

