

Electrical connections		FSU1	FSU2	FSU3
Voltage				
208-240V 1 AC 50/60 Hz	kW	0.25*	0.25***	0.25***
230/400-415V/3V 3N 50/60 Hz	kW	1.75**	1.75**	-
Steam, air and vacuum connection				
Steam	DN	-	-	15
Rec. steam pressure	kPa	-	-	400-500
Steam consumption	kg/h	-	-	5-10
Condensate	DN	-	-	15
Compressed air	DN	6	-	8
Rec. air pressure	kPa	500-700	-	500
Air consumption	l/min	100-200	-	100-150
Vacuum exhaust***	mm	Ø100	-	Ø100
Tank drain	DN	-	-	15
Central vacuum	mm	-	-	Ø70
Vacuum air consumption	m ³ /h	-	-	150
Vacuum depression	mm H ₂ O	-	-	140
Shipping data				
	net, kg	40	30	70
	crated, kg	70	60	100
	boxed, kg	100	90	130
Dimensions in mm				
A	Width	1440	1440	1440
B	Depth	700	700	420
C	Height	1650	-	-
D		920	920	920
E		420	420	900
F		520	520	-
1 Electrical connection 2 Steam connection 3 Condensate 4 Air connection 5 Vacuum outlet				

* Without compressor
 ** With compressor
 *** With vacuum

