

Traditional Form Finishers

FF1, FF2, FF3



Model FF1 shown

Features and benefits

- Even distribution of steam moistens the fabric to remove creases
- Hot air blowing presses and dries the fabric
- Front clamp, holds the garment in place
- Adjustable steam/air timers for a consistent finish
- Adjustable air blowing baffle, suitable for various fabric types
- Range of sleeves/clamps, improve the finishing
- Self contained and integral steam boiler simplifies the installation (only FF3)
- Air operated cuff clamp (jackets) improves the sleeve finish (only FF2)

Main options

- Range of forms for a wide variety of garments
- Water spray gun, ideal for heavily creased areas

Electrical connections		FF1	FF2	FF3
Voltage				
208-240V 3 AC 50/60 Hz	kW	1.7	1.7	alt 7.7
400-415V 3N AC 50 Hz	kW	1.7	1.7	9.7
				11.7
				13.7
Steam and Air connection				
Steam	DN	15	15	-
Rec. steam pressure	kPa	550	550	-
Steam consumption	kg/h	15-18	15-18	-
Condensate	DN	15	15	-
Compressed air	DN	-	8	-
Rec. air pressure	kPa	-	700	-
Air consumption	l/h	-	300	-
Water supply	∅ mm	-	-	12
Boiler drain	DN	-	-	15
Shipping data				
	net, kg	97	97	155
	crated, kg	137	137	195
	boxed, kg	175	175	235
Dimensions in mm				
A	Width	530	530	530
B	Depth	1200	1200	1470
C	Height	1370	1370	1490
D		230	230	350
E		970	970	1320
F		880	880	860
G		430	430	405
H		160	160	150
1	Control panel	5	Air connection	
2	Electrical connection	6	Water drain (built-in boiler only)	
3	Steam connection	7	Water supply (built-in boiler only)	
4	Condensate			

