

Wetcleaning Ironing Tables

FIT1-WC, FIT2-WC



Features and benefits

- Utility shape, for general purpose
- Integral vacuum fan holds the garment in place and dries the fabric
- Blowing from table eases finishing of light weight fabric and linings
- Table height adjustment ensures operator comfort
- Adjustment of blowing and vacuum strength
- Mobile, eases re-location
- Steam electric iron with Teflon shoe and silicon iron rest
- Steam gun for raising the nap of some fabrics
- Sleeve arm for ironing awkward shapes
- Shoulder buck for restoring the shape of washed jackets
- Overhead gantry to support iron hoses
- Light, illuminates the working area
- Swivelling iron rest for operator convenience
- Additional pedals (vac/blow) for dual side operation (for FIT1-WC)

Main options

- Integral steam boiler for self-contained installation (standard for FIT2-WC)
- Spotting arm eases the removal of stains (in alternative to the shoulder buck)

Electrical connections		FIT1-WC	FIT2-WC
Voltage			
400V 3N AC 50Hz	kW	2	6
208V-240V 3AC 60Hz	kW	2	6
Steam connection			
Steam	DN	8	-
Rec. steam pressure	psi	0.04-0.07	-
Steam consumption	lb/h	6.6	-
Condensate	DN	8	-
Shipping data			
net, kg/lbs		130/287	170/375
crated, kg/lbs		150/331	190/419
Dimensions in mm/inch			
A	Width	2135 / 84 1/16	2220 / 87 3/8
B	Depth	1435 / 56 1/2	1435 / 56 1/2
C	Height	1900 - 2080 / 74 13/16 - 81 7/8	1900 - 2080 / 74 13/16 - 81 7/8
D		815-995 / 32 1/16-39 3/16	815-995 / 32 1/16-39 3/16
E		1560 / 61 7/16	1560 / 61 7/16
F		1715 / 67 1/2	1855 / 73 1/16
1	Control panel	5	Pedals
2	Electrical connection	6	Steam gun
3	Steam connection	7	Shoulder buck
4	Condensate	8	Overhead lamp

