ALPENINOX

Cold Rooms 163x123 (-18/-20) - Remote Unit

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	



Short Form Specification

<u>Item No.</u>

Usable volume: 4.1 m3. Panel insulation in cyclopenthane (100mm thickness), with injected polyurethane foam, CFC and HCFC free. Wall and internal ceiling surfaces made of galvanized plastified steel with 120 micron nontoxic pvc coating. Internal floor in non-slip, plastic coated, galvanized steel sheet. Fast-fit centering system using new fasteners made of high resistant composite material. Rounded internal and external corners. Self-closing right-hinged door with magnetic door-gaskets; handle with lock and interior safety release. Internal lighting. Remote refrigeration unit for operation in ambient temperatures up to +43°C. Refrigerant R452a. Defrosting through heated gas with automatic re-evaporation of defrosting water. Control panel with: ON/OFF switch, internal lighting switch and digital control with HACCP and failure alarms.

Main Features

- Anti-slip walk-in floor.
- High hygiene standards and easy to clean thanks to rounded internal / external corners and radiused edges.
- Fast-fit centering system allows perfect alignment of the panels. These new fasteners are made of high resistant composite materials and guarantee perfect grip/sealing of all components.
- Conform to ruling European safety and hygiene standards and CE marked.
- HACCP monitoring is possible trough a serial port supplied on all models.
- Equipped with internal lighting (waterproof IP54) mounted on the refrigerating unit panel.
- Floor surface on which the cold room will be placed should be levelled if presenting irregularities or unevenness up to 1 cm.
- Control panel includes: luminous ON/OFF switch, internal light switch, cold room functioning indicator, defrost cycle indicator, temperature and thermostat control with digital display.
- New vacuum injection foaming allows significant and enhanced insulation and higher quality.
- Airtight panels connection, all sides of panels have PVC gasket foamed in place to assure airtight and secure fitting; any other sealing between panels on site is eliminated.
- Defrosting through heated gas with re-evaporation of defrosting water permits to reduce the total power installed, shorten defrosting time and limit the warming of the cold room. Dedicated drain hole is not needed.
- Right-hinged door is available as standard (left-hinged door on request) and constructed with smooth rounded profiles, cam-lift action hinges, airtight magnetic gasket and high insulation thus allowing to reduce energy and operating costs.
- Newly designed handle complete with lock and interior safety release to prevent entrapment when the door is accidentally locked from outside.
- Very short assembly time. Expert refrigeration knowledge is not required for installation.

Construction

- Panels are cladded inside and outside with anti-scratch galvanized plastified steel with 120 micron nontoxic pvc coating, polyurethane foam insulation, CFC and HCFC free.
- Whenever the cold room door is opened the microswitch switches on automatically the internal light and turns off the cooling fan.
- Split remote unit provided with 6m of precharged pipe.

APPROVAL:

ALPENINOX

Optional Accessories

- Kit for HACCP advanced connection for PNC 102021 cold rooms
- Graphic temperature recorder PNC 102025
- Plastic curtain for 65cm door clearance PNC 102027
- Datalogger cold room PNC 102030

- Door microswitch PNC 102441
- PNC 137090
- Shelving set, composed of aluminium uprights and 4 polyethylene louvered shelves, for 1630x1230 mm cold rooms, 2100 kg load

Cold Rooms 163x123 (-18/-20) - Remote Unit

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

ALPENINOX

Cold Rooms 163x123 (-18/-20) - Remote Unit



Front

Λ

Supply voltage: 102314 (NSEC838SRN) Total Watts:

230 V/1N ph/50 Hz 1.15 kW

1830 mm


1430 mm

2230 mm

1630 mm 280.5 kg 90.1 kg Pallet Case

Key Information:

External dimensions, Width:		
External dimensions, Depth:		
External dimensions, Height:		
Internal Dimensions, Width:		
Weight Packaging:		
Weight Packaging (2):		
Package 1 type:		
Package 2 type:		
Package 1 contents:		
Package 2 contents:		
-		



Cold Rooms 163x123 (-18/-20) - Remote Unit

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.