

ALPENINOX

Crio Smart 2 Half Door Digital Stainless Steel Refrigerator, 670lt (0/+6)

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



727431 (RE472HR60)

2-half door refrigerator 670L,
0+6°C, (R134A), digital,
stainless steel - UK plug

Main Features

- Digital control with cabinet temperature display and setting and manual activation of defrost cycle. Fully compliant HACCP digital controls include visible alarms.
- Optimized back to front forced air flow provide even temperature distribution and fast cooling in any conditions.
- Automatic defrost.
- Large storage area suitable to contain 2/1 GN grids or shelves on anti-tilt runners.
- Operating temperatures can be adjusted from 0 to +6 ° C to suit both meat and dairy storage requirements.
- Cabinet fitted with up to 75 mm thickness of cyclopentane insulation for best insulating performance with 100% environmental protection (thermal conductivity: 0,020 W/m*K).
- Hidden evaporator thus guaranteeing higher storage capacity and less corrosion problems.
- Automatic evaporation of the defrosting water by hot gas on the top for energy saving.
- Cleaning-free condenser: the structure of the wire frame condenser prevents dust and grease accumulation thus avoiding periodical cleaning operations and reducing energy consumption.
- Internal structure with numerous charging positions available to host grids, ensuring higher net capacity and a greater storage space.
- 60 mm-thick insulation covering the evaporator can be easily removed with a single operation.
- Removable triple-chamber balloon magnetic gasket to improve insulation and reduce energy consumption and ease of cleaning.
- Rilsan coated grids for improved protection.
- Connectivity ready for real time access to connected appliances from remote and data monitoring (requires optional accessory).

APPROVAL: _____

Construction

- Interior base with rounded corners, pressed from a single sheet.
- External back panel in galvanized steel.
- Anti-corrosion bottom avoids any damage that may be caused to the cabinet by aggressive detergents employed to clean the floors.
- Stainless steel runners and supports easily disassembled.
- Lockable door.
- Refrigerant type: R134a.
- Mounted on adjustable Stainless steel feet, with castors as an option.
- CFC and HCFC-free insulation.
- Door switch stops the fan when door is opened to avoid cold air exiting the cell, thus saving energy.
- Doors are self-closing and can be fully opened up to 180°.
- The rounded internal corners, the easily removable runners and grids allow for ease of cleaning and high hygiene standards.
- Delivered with UK plug.


Included Accessories

- 3 of 2/1GN gray rilsan grid with 2 runners PNC 881020


Optional Accessories

- 2 stainless steel runners for refrigerated cabinets - (Marine) PNC 880242
- Spacer for 670L and 1430L refrigerated cabinets PNC 880248
- Kit integrated HACCP for digital refrigerators (IR33) PNC 880252
- Pedal opening for cabinets PNC 880324
- Plastic container with false bottom, 1/1GN PNC 880705
- 4 swivelling wheels (2 with brake) for refrigerators, diam 125mm, NOT for glass door and remote models PNC 881002
- 2/1GN gray rilsan grid PNC 881004
- AISI 304 stainless steel grid, 2/1GN PNC 881016
- AISI 304 stainless steel grid with 2 runners, 2/1GN PNC 881018
- Meat rail for 670/1430L refrigerators with 4 hooks PNC 881019
- 2/1GN gray rilsan grid with 2 runners PNC 881020
- Set of 2 stainless steel runners for 670/1430L refrigerators and freezers PNC 881021
- 2/1GN perforated shelf PNC 881042
- 1/1GN rilsan steel wire basket h150mm PNC 881043

Front




Side



EI = Electrical inlet (power)

Top



Electric

Supply voltage:

727431 (RE472HR60) 220 V/1 ph/60 Hz

Electrical power max.:

0.23 kW

Key Information:

Gross capacity: 670 lt

Door hinges:

External dimensions, Width: 710 mm

External dimensions, Height: 2050 mm

External dimensions, Depth: 835 mm

External dimensions, Depth with Doors Open: 1480 mm

Number and type of doors: 2x1/2 Full

Number and type of grids (included): 3 - GN 2/1

Type of external material: Stainless Steel

Type of internal material: Stainless Steel

Internal panels material: Stainless Steel

Number of positions & pitch: 44; 30 mm

Refrigeration Data

Control type: Digital

Refrigerant type: R134a

Refrigeration power: 381 W

Refrigeration power at evaporation temperature: -10 °C

Operating temperature min.: 0 °C

Operating temperature max.: 6 °C

Operating mode: Ventilated