

## **CRIO Chill Blast Chiller-Freezer 2x20GN1/1 200/170 kg, Remote, Roll-in, disassembled**

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_



**729267 (ABFA221RDE)**

CRIO Chill blast chiller freezer 200/170kg, 2x20 GN 1/1 or 600x400mm with touch screen control and remote refrigerating unit - disassembled (R452a)

### Short Form Specification

#### Item No.

- Blast chiller freezer with high resolution full touch screen interface, multilanguage.
- For 2 x GN, 400x600 or Banqueting trolleys.
  - Load capacity: chilling 200 kg; freezing 170 kg.
  - AirFlow air distribution system to achieve maximum performance.
  - Chilling/Freezing modes: Automatic (10 food families with 100+ different pre-installed variants); Programs (a maximum 1000 programs can be stored and organized in 16 different categories); Manual (soft chilling, hard chilling, freezing, holding, turbo cooling and lite hot cycles); Special Cycles (Cruise chilling, fast thawing, Sushi&Sashimi, Sous-Vide chilling, ice-cream).
  - Special functions: MultiTimer chilling/freezing, Make-it-Mine to customize interface, Homepage to customize homepage, agenda Calendar.
  - Remaining time estimation for probe-driven cycles based on artificial intelligence techniques (ARTE 2.0).
  - Automatic and manual defrosting and drying.
  - USB port to download HACCP data, programs and settings. Connectivity ready.
  - 3-point multi sensor core temperature probe.
  - Stainless steel construction throughout.
  - Internal rounded corners.
  - Remote refrigeration unit (optional accessory).
  - R452a refrigerant gas.
  - Performance guaranteed at ambient temperatures of +43°C (Climatic class 5).
  - Delivered disassembled.
  - Compatible with Electrolux, Zanussi and Rational ovens.

### Main Features

- Holding at +3 °C for chilling or -22 °C for freezing, automatically activated at the end of each cycle, to save energy and maintain the target temperature (manual activation is also possible).
- Blast Chilling cycle: 200 kg from +90°C up to + 3°C.
- Freezing cycle: 170 kg from 90°C up to -41°C.
- X-Freeze cycle: ideal for blast freezing all kinds of food (raw, half or fully cooked).
- Lite-Hot cycle: ideal for soft heating preparations.
- Turbo cooling: chiller works continuously at the desired temperature; ideal for continuous production.
- Special Cycles:
  - Cruise Chilling automatically sets the parameters for the quickest and best chilling (it works by probe)
  - Fast Thawing
  - Sushi&Sashimi (anisakis-free food)
  - Sous-vide chilling
  - Ice Cream
- Automatic mode including 10 food families (meat, poultry, fish, sauces and soup, vegetables, pasta/rice, bread, savory and sweet bakery, dessert, beverage fast cooling) with 100+ different pre-installed variants. Through Automatic Sensing Phase the blast chiller optimizes the chilling process according to size, quantity and type of food loaded to achieve the selected result. Real time overview of the chilling parameters. Possibility to personalize and save up to 70 variants per family.
- Programs mode: a maximum of 1000 programs can be stored in the blast chiller's memory, to recreate the exact same high standard at any time. The programs can be grouped in 16 different categories to better organize the menu. 16-step chilling programs also available.
- AirFlow air distribution system to achieve maximum performance in chilling/heating evenness and temperature control thanks to a special design of the chamber combined with high precision variable speed fan.
- MultiTimer function to manage up to 20 different chilling cycles at the same time, improving flexibility and ensuring excellent results. Can be saved up to 200 MultiTimer programs.
- 3-point multi sensor core temperature probe for high precision and food safety.
- Tropicalized unit.
- Remaining time estimation for probe-driven cycles based on artificial intelligence techniques (ARTE 2.0 Patented US7971450B2 and related family) for an easier planning of the activities.
- Automatic and manual defrosting and drying.
- Performance guaranteed at ambient temperatures of +43°C (Climatic class 5).

### Construction

- Remote refrigeration unit (optional accessory).
- Solenoid valve to automatically manage the gas pressure in the thermodynamic circuit.
- Main components in 304 AISI stainless steel.
- Evaporator with antirust protection.
- Motors and fan waterproof protected IP23.
- Hygienic internal chamber with all rounded corners for easy cleaning.

APPROVAL: \_\_\_\_\_

- Removable magnetic gasket door with hygienic design.
- Ventilator swinging hinged panel for access to the evaporator for cleaning.
- Automatic heated door frame.

## User Interface & Data Management

- High resolution full touch screen interface (translated in more than 30 languages) - color-blind friendly panel.
- Pictures upload for full customization of cycles.
- Make-it-mine feature to allow full personalization or locking of the user interface.
- Homepage lets the user group the favorite functions in the homepage for immediate access.
- Calendar works as an agenda where the user can plan the daily work and receive personalized alerts for each task.
- USB port to download HACCP data, share chilling programs and configurations.
- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).
- Trainings and guidances supporting materials easily accessible by scanning QR-Code with any mobile device.
- Automatic consumption visualization at the end of the cycle.
- With Match function the Oven and the Blast Chiller are connected to each other and communicate in order to guide the user through the cook&chill process optimizing time and efficiency (requires optional accessory).


## Included Accessories

- 1 of 3-sensor probe for blast chiller freezer PNC 880582


## Optional Accessories

- Air remote refrigerating unit for 200/170kg, PNC 881225   
 20 GN 2/1 blast chiller freezer (> 10 m) and  
 200/170kg, 2x20GN 1/1 blast chiller freezer  
 (≤ 10 m) - R452A
- Connectivity router (WiFi and LAN) PNC 922435
- Trolley with tray rack, 16 GN 2/1, 84mm PNC 922686   
 pitch
- Trolley with tray rack 20 GN 2/1, 63mm PNC 922757   
 pitch
- Trolley with tray rack, 16 GN 2/1, 80mm PNC 922758   
 pitch
- Banquet trolley with rack holding 92 plates PNC 922760   
 for 20 GN 2/1 oven and blast chiller freezer,  
 85mm pitch
- Bakery/pastry trolley with rack holding PNC 922762   
 400x600mm grids for 20 GN 2/1 oven and  
 blast chiller freezer, 80mm pitch (16  
 runners)
- Banquet trolley with rack holding 116 plates PNC 922764   
 for 20 GN 2/1 oven and blast chiller freezer,  
 66mm pitch

### Front




### Side



- D** = Drain
- EI** = Electrical inlet (power)
- RO** = Refrigerant Outlet
- WIC** = Cooling water inlet

### Top



### Electric

Circuit breaker required

**Supply voltage:** 380-415 V/3N ph/50/60 Hz

**Electrical power, max:** 7.44 kW

**Heating power:** 7.4 kW

### Water:

**Drain line size:** 3/4"

### Installation:

**Clearance:** 5 cm on sides and back.

Please see and follow detailed installation instructions provided with the unit

### Capacity:

**Max load capacity:** 200 kg

**Number and type of grids:** 40 (GN 1/1; 600x400)

**Number and type of basins:** 30 (360x250x80h)

### Key Information:

**Door hinges:** Right Side

**External dimensions, Width:** 1800 mm

**External dimensions, Depth:** 1266 mm

**External dimensions, Height:** 2270 mm

**Net weight:** 220 kg

**Shipping weight:** 120 kg

**Shipping weight 2:** 220 kg

**Shipping volume:** 3.58 m<sup>3</sup>

### Refrigeration Data

Note: refrigeration power calculated at a distance of 20 linear mt.

**Suggested refrigeration power:** 12650 W

**Condition at evaporation temperature:** -20 °C

**Condition at condensation temperature:** 40 °C

**Condition at ambient temperature:** 30 °C

**Connection pipes (remote) - outlet:** 22 mm

**Connection pipes (remote) - inlet:** 12 mm

Remote refrigeration unit required. Working temperature in the cavity of the blast chiller is down to -41°C.

Note: refrigeration power calculated at a distance of 20 linear mt.

**\*Note:**

**Compatible refrigerant gas:** R404A; R452A