

D15-3 CLASSIC SINGLE 5-GALLON BUBBLER



General Features

D153SA

CRATHCO

D15-3 CLASSIC SINGLE 5-GALLON BUBBLER

D15-3 Pre-mix dispenser with stainless steel side panels. Large, 5 gallon (18.9 L) bowl with easy-to-read measuring marks. Dripless pouring valves are sanitary and easy to use and maintain. Better design and more stainless steel allow easier cleaning and less maintenance. Super-strong, virtually unbreakable polycarbonate bowls and covers for lasting durability. Certified NSF / ANSI 20- safe for milk. CRATHCO® Model D15-3 Unique evaporator and high-efficiency pump cools faster and more efficiently for quick start-up. Along with spray circulation, agitators are included with each unit for fresh juices, coffees or tea. Superior engineering allows full beverage cooling to the dispense point, and right down to the last drink. Cup height 8.25" (20.5 cm). Temperature range from 35 - 41°F (1.1 - 5° C). R134A Refrigerant

D15-3 CLASSIC SINGLE 5-GALLON BUBBLER

Specifications

- Certified NSF / ANSI 20- safe for milk.

Construction

- The unique evaporator and the high efficiency pump cool faster and more efficiently for a quick start-up
- Two-piece stainless steel dripless pouring valves are easy to use and clean
- Magnetic submerged impeller
- Refrigerant type: R134a.
- Temperature ranges from 35 - 41° F (1.7 -5° C)
- Pre-mix dispenser with one (1) 5 gallon/18.9 L bowl with 8.25" (20.5 cm) cup clearance
- Perfect to dispense refreshing cold brew coffee, teas, fresh juices and more
- Stainless steel side panels and drip tray

D15-3 CLASSIC SINGLE 5-GALLON BUBBLER

Electric

Supply voltage:	120 V / 1N ph / 60 Hz
Electrical power max.:	
Current consumption:	0 Amps
Plug type:	NEMA 5-15

Key Information:

Number of bowls:	1
Control board:	;Mechanical
Bowl's capacity:	4.8 gal
Dimensions, Width:	
Dimensions, Depth:	
Dimensions, Height:	
Net weight:	

Refrigeration Data

Refrigerant gas:

Certifications



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2025.04.29