E-29-4 CLASSIC MINI-TWIN BUBBLER, PLASTIC



RefCC0H6M (E2942S2A)

Classic Bubbler Mini-Twin E29-4 Base, Plastic Side Panels and Drip Tray, Bowl Assembly, 2 bowls, 8" cup clearance - Refrigerant R134A

General Features

E-29-4 Generous yet compact pre-mix dispenser with (2) 2.4 gallon (9 L) bowls. Plastic side panels, dripless dispense valves are sanitary and easy to use and maintain. Bowls have easy-to-read measuring marks made in super-strong polycarbonate for long lasting durability and a simple clean-up. Cup height up to 8" (20 cm). Unique evaporator and high efficiency pump cools faster and more efficiently for quick start-up. Along with spray circulation, agitators are included with each unit for fresh juices, coffees or tea. Superior engineering allows full beverage cooling to the dispense point, and right down to the last drink. Temperature range from 35 - 41°F (1.1 - 5° C). Large capacity drip pan. R134A Refrigerant

E-29-4 CLASSIC MINI-TWIN BUBBLER, PLASTIC

Specifications

- This equipment is perfect to refresh and dispense cold coffees, teas, fresh juices or cocktails
- Slushy machine with two (2) 3.2 gallon tanks, 6.4 gallon/24 L total capacity
- Plastic side panels and drip tray

Construction

- Refrigerant type: R134a.
- The unique evaporator and the high efficiency pump cool faster and more efficiently for a quick start-up
- Two-piece stainless steel dripless pouring valves are easy to use and clean
- Magnetic submerged impeller
- Pre-mix dispenser with plastic side panels and drip tray
- n. I-Tank insulated bowls containing (2) 1.3 gallon/5 L capacity, 2.6 gallon/10 L total capacity of finished product
- Pre-mix dispenser with two (2), 2.4 gallon/9 L bowls with a 9" (22.9 cm) cup clearance
- Temperature ranges from 35 41° F (1.7 5° C)
- Pre-mix dispenser with two (2) 2.4 gallon/9 L bowls with 8" (20 cm) cup clearance
- Perfect to dispense refreshing cold brew coffee, teas, fresh juices and more



E-29-4 CLASSIC MINI-TWIN BUBBLER, PLASTIC

Electric

Supply voltage: 120 V / 1N ph / 60 Hz

Electrical power max.: 0.4 kW
Current consumption: 0 Amps
Plug type: NEMA 5-15

Key Information:

Number of bowls:2Bowl's capacity:9 ltControl board:MechanicalDimensions, Width:290 mmDimensions, Depth:370 mmDimensions, Height:640 mmNet weight:24.7 kg

Refrigeration Data

Refrigerant gas: R134a

Certifications







The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2025.06.26

