



Hand held Mixers Motor Unit for Bermixer PRO Turbo 550 W

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____



602329 (DBMAU550)

Motor unit, variable speed
up to 10000 rpm - 550 W

Short Form Specification

Item No. _____

550W flat base motor unit for handheld mixer. Stainless steel tubes (various lengths) and whisk available upon request, to mix, liquidize, whip or emulsify. IP55 water protected control panel.

Main Features

- Flat base motor unit.
- Delivered with space saving storing wall support.
- Light weight, ergonomic grip and adjustable speeds make preparation tasks fast and easy.
- Overheating warning red indicator.
- Safety feature requires both hands to start the mixer (no volt release system).
- Designed to be used directly in stew pots up to 150 - 170 lt, depending on the tube size.
- Bayonet system makes fast and simple to exchange tools.
- Productivity suitable for 50 to 300 meals per service.

Construction

- Power: 550 watts.
- Maximum speed 10000 rpm.
- Motor has an air cooling system and is protected against overheating (in case of long intensive work).
- Smart speed control to ensure the right power according to the work load.
- Water protected motor unit (controls are IP55, IP34 throughout machine).

Optional Accessories

- | | |
|--|-------------------------------------|
| • REINFORCED WHISK FOR PORTABLE BERMIXER | PNC 650108 <input type="checkbox"/> |
| • S/S TUBE 353MM FOR PORT. MIXER BERMIXER | PNC 650132 <input type="checkbox"/> |
| • S/S TUBE 453MM FOR PORT. MIXER BERMIXER | PNC 650133 <input type="checkbox"/> |
| • S/S TUBE 553MM FOR PORT. MIXER BERMIXER | PNC 650134 <input type="checkbox"/> |
| • Adjustable rail for containers diam. 375 mm to 650 mm (to be used with 653294) | PNC 653292 <input type="checkbox"/> |
| • Holder to support portable mixer in containers (can be used only with tube attachment) | PNC 653294 <input type="checkbox"/> |

APPROVAL: _____



Hand held Mixers Motor Unit for Bermixer PRO Turbo 550 W

Front




Side



EI = Electrical inlet
(power)

Top



Electric

Supply voltage:	220-240 V/1 ph/50/60 Hz
Electrical power max.:	0.55 kW
Total Watts:	0.55 kW

Key Information:

External dimensions, Width:	138 mm
External dimensions, Depth:	120 mm
External dimensions, Height:	340 mm
Shipping weight:	3.57 kg



Hand held Mixers
Motor Unit for Bermixer PRO Turbo 550 W

The company reserves the right to make modifications to the products
without prior notice. All information correct at time of printing.

2025.04.20