

### Hand held Mixers Bermixer PRO 450 W with Stainless Steel Tube (453-553mm)

| ITEM #  |  |
|---------|--|
| MODEL # |  |
| NAME #  |  |
| SIS#    |  |
| AIA#    |  |



600321 (DBP4545)

Portable mixer, variable speed up to 9000 rpm, with stainless steel tube 453 mm, 450W

600329 (DBP4555)

Portable mixer, variable speed up to 9000 rpm, with stainless steel tube 553 mm, 450W

## **Short Form Specification**

Item No.

Handheld mixer with stainless steel tube and space saving storing wall support. To be used directly in stew pots, even during cooking. Bayonet system ensures easy removal of accessories. Parts in contact with food - tube, blade, shaft completely dismountable without tools for easy cleaning. Bell knife design ensures antisplash system and minimum handling during working operations. Flat motor base with ergonomic handle for a convenient grip. Electronic speed variator with speed regulation regardless of the load. Electronic speed adjustment by pulse on + and - buttons. Maximum speed: 9000 rpm. Safety feature requires both hands to start the machine. Design for heavy duty usage: double fan system to cool down the motor. Visible and water proof (IP55) control panel to control speed levels and overload warning light. Shaft locking device avoids release during operation. Whisk accessory available as an option.

### **Main Features**

- Parts in contact with food tube, blade, shaft - can be completely dismounted without tools for easy cleaning.
- Designed to be used directly in stew pots up to 100 lt with the 45 cm tube and 120 lt with the 55 cm tube.
- Delivered with:
- -flat base motor
- -stainless steel tube
- -space saving storing wall support
- Light weight, ergonomic grip and adjustable speeds make preparation tasks fast and easy.
- Anti-splash bell knife design.
- Bayonet system makes fast and simple to exchange tools.
- Overheating warning red indicator.
- Tube, knife and whisks are dishwasher safe.
- Safety feature requires both hands to start the mixer (no volt release system).
- Productivity suitable for 50 to 300 meals per service.

#### Construction

- Motor has an air cooling system and is protected against overheating (in case of long intensive work).
- Maximum speed 9000 rpm.
- Smart speed control to ensure the right power according to the work load.
- Power: 450 watts.
- Water protected motor unit (controls are IP55, IP34 throughout machine).

#### **Included Accessories**

- 1 of 453 mm stainless steel tube for portable mixer bermixer (only for 600321)
- 1 of 553 mm stainless steel tube for Bermixer (for 450W, 550W, 650W, 750W) (only for 600329)

### **Optional Accessories**

- Reinforced whisk for portable PNC 650108 
   Bermixer
- 353 mm stainless steel tube for PNC 650132 ☐ portable mixer bermixer (only for 600329)
- 453 mm stainless steel tube for portable mixer bermixer PNC 650133 □
- 553 mm stainless steel tube for PNC 650134 
  Bermixer (for 450W, 550W, 650W, 750W)

APPROVAL:





• Adjustable rail for containers diam. 375 mm to 650 mm (to be used with 653294)

 Holder to support portable mixer in containers (can be used only with tube attachment)


PNC 653292 📮

PNC 653294 🔲





# Hand held Mixers Bermixer PRO 450 W with Stainless Steel Tube (453-553mm)



| Electric                                                                                         |                                               |
|--------------------------------------------------------------------------------------------------|-----------------------------------------------|
| Supply voltage:<br>Electrical power, max:<br>Total Watts:                                        | 220-240 V/1 ph/50/60 Hz<br>0.45 kW<br>0.45 kW |
| Capacity:                                                                                        |                                               |
| Capacity (up to):<br>600321 (DBP4545)<br>600329 (DBP4555)                                        | 100 Litre<br>120 Litre                        |
| Key Information:                                                                                 |                                               |
| External dimensions,<br>Width:                                                                   | 138 mm                                        |
| External dimensions,<br>Depth:<br>External dimensions,<br>Height:                                | 120 mm                                        |
| 600321 (DBP4545)<br>600329 (DBP4555)<br>Shipping weight:<br>600321 (DBP4545)<br>600329 (DBP4555) | 765 mm<br>865 mm<br>5.64 kg<br>5.76 kg        |
|                                                                                                  |                                               |

