Motor Unit for Bermixer PRO Turbo 6

DITO SAMA

Hand held Mixers Motor Unit for Bermixer PRO Turbo 650 W

| ITEM # | | |
|--------|--|--|
| MODEL# | | |
| NAME# | | |
| SIS# | | |
| AIA# | | |
| | | |



600312 (DBPU650)

Motor unit, variable speed up to 10000 rpm - 650 W

Short Form Specification

Item No.

650W flat base motor unit for handheld mixer. Stainless steel tubes (various lengths) and whisk available upon request to mix, liquidize, whip or emulsify. IP55 water protected control panel.

Main Features

- Safety feature requires both hands to start the mixer (no volt release system).
- Flat base motor unit.
- Delivered with space saving storing wall support.
- Light weight, ergonomic grip adjustable speeds make preparation tasks fast and easy.
- Overheating warning red indicator.
- Designed to be used directly in stew pots up to 200 - 240 lt, depending on the tube
- Bayonet system makes fast and simple to exchange tools.
- Productivity suitable for 50 to 300 meals per service.

Construction

- Power: 650 watts.
- Maximum speed 10000 rpm.
- Motor has an air cooling system and is protected against overheating (in case of long intensive work).
- Smart speed control to ensure the right power according to the work load.
- Water protected motor unit (controls are IP55, IP34 throughout machine).


Optional Accessories

- Reinforced whisk for portable PNC 650108 Bermixer
- 353 mm stainless steel tube for PNC 650132 $\ \square$ portable mixer bermixer
- 453 mm stainless steel tube PNC 650133 📮 for portable mixer bermixer
- 553 mm stainless steel tube for PNC 650134 $\ \Box$ Bermixer (for 450W, 550W, 650W, 750W)
- 653 mm stainless steel tube for PNC 650135 Bermixer (for 650W, 750W)
- Adjustable rail for containers PNC 653292 □ diam. 375 mm to 650 mm (to be used with 653294)
- PNC 653294 🔲 Holder to support portable mixer in containers (can be used only with tube attachment)

APPROVAL:



Hand held Mixers Motor Unit for Bermixer PRO Turbo 650 W



Electric Supply voltage: 220-240 V/1 ph/50/60 Hz **Electrical power max:** 0.65 kW 0.65 kW **Total Watts:** Key Information: External dimensions, Width: 138 mm External dimensions, 120 mm Depth: External dimensions, 340 mm Height: **Shipping weight:** 3.7 kg







