

Planetary Mixers Planetary Mixer, 60 It

ITEM #	
MODEL#	
NAME #	
SIS#	
AIA#	
AIA II	



600177 (DBMX60B3)

60 It planetary mixer,bowl detection device and SOLID BPA free safety screen, with mechanical speed variator, timer and bowl lighting. Manual bowl movement. Equipped with stainless steel spiral hook, paddle and whisk

Short Form Specification

Item No.

Floor model, suitable for all kneading, blending and whipping operations. Body in non-corrosive material with 18/8 (AISI 302) 60 litre stainless steel bowl. Powerful asynchronous motor (1500 W) with two level mechanical speed variator, with speeds ranging from 1 to 10 (20 to 180 rpm). Plastic safety screen easily removable for cleaning. Control panel with timer and bowl lighting. Manual bowl lifting system. Removable/transparent solid safety screen - made of a bisphenol-A free (BPA) copolyester. Bowl detection device allows the mixer to switch on only when the bowl and the safety screen are properly installed and positioned together.

Supplied with 3 tools: stainless steel spiral kneading hook, cast aluminium paddle and stainless steel wire whisk.

Main Features

- Professional beater mixer for kneading, mixing and whisking all types of food products.
- Delivered with:
 - -Stainless steel spiral kneading hook, Cast aluminum paddle, 302 AISI stainless steel whisk and Mixing Bowl for 60 lt
- Two level mechanical speed variator.
- Maximum capacity (flour, with 60% of hydration) 20 kg, suitable for 400-800 meals per service.
- Waterproof control panel with timer setting knob, speed setting handle and speed display.
- Manual bowl lifting and lighting system.
- Safety device will automatically stop the machine if the screen is lifted.
- Solid BPA-free safety screen, covering the stainless steel wire one, limits the flour and unsafe dust particles when used in bakery and pastry preparation.
- Removable chute to add ingredients while working included as standard.
- Bowl detection device allows the mixer to switch on only when the bowl and the solid safety screen are properly installed and positioned together.

Construction

- Body in non-corrosive material.
- Sturdy construction with mechanically welded strong metal frame.
- 302 AISI Stainless steel bowl 60 lt. capacity.
- Asynchronous motor with high start-up torque.
- 10 speeds from 20 to 180 rpm (planetary movement), to be set while machine is working, according to the tool and the mixture hardness.
- Water protected planetary system (IP55 electrical controls, IP23 overall machine).
- Planetary movement based on self lubricating gears, eliminating any risk of leaks.
- Power: 1500 watts.
- Overload protected planetary system and motor.
- Adjustable feet for perfect stability.
- Plastic safety screen easily removable for cleaning.

Included Accessories

1 of Bowl 60 It mixer
1 of Paddle 60 It
1 of Stainless steel (AISI 303)
Spiral Hook for 60 It planetary mixers

• 1 of Whisk 60 lt PNC 653086

Optional Accessories

40 It reduction kit (bowl, spiral PNC 650127 Dhook, paddle, whisk) for 60 It and 80 It planetary mixers

APPROVAL:






•	Bowl 60 It mixer	PNC 650129	
•	Paddle 60 lt	PNC 653083	
•	Stainless steel (AISI 303) Spiral Hook for 60 It planetary mixers	PNC 653084	
•	Whisk 60 lt	PNC 653086	
•	Reinforced Whisk 60 lt (for heavy duty use)	PNC 653097	
•	Bowl scraper 60 lt	PNC 653442	
•	Bowl trolley for 40/60/80 lt planetary mixers	PNC 653585	





Planetary Mixers Planetary Mixer, 60 lt



Electric 220-240/380-415 V/3 ph/50 Supply voltage: Electrical power max: 1.54 kW **Total Watts:** 1.54 kW Capacity: ISO 9001; ISO 14001 kg/ Performance (up to): Cycle Capacity: 60 litres Key Information: External dimensions, 685 mm Width: External dimensions, Depth: 1087 mm External dimensions, Height: 1445 mm

330 kg

ISO 9001; ISO 14001 kg with Spiral hook

100 with Whisk

Shipping weight:

Cold water paste:

Egg whites: