

## **Peelers** Vegetable Peeler, 25 kg -**Abrasive Plate**

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



603649 (DT25EF350)

25 kg vegetable peeler. Stainless steel body with abrasive plate and abrasive cylinder. Suitable for 100 to 500 meals

603650 (DT25EF150)

25 kg vegetable peeler. Stainless steel body with abrasive plate and abrasive cylinder. Suitable for 100 to 500 meals

# **Short Form Specification**

### Item No.

Constructed in stainless steel. The removable rotating plate and the cylinder are covered with a removable rotating plate covered in very resistant abrasive material (silicon carbide). Fully opening polycarbonate lid. An interlocking safety magnetic device will stop the machine when the unloading door is opened. Flat and waterproof touch button control panel with timer. The electronic controls and motor have IP55 protection.

Supplied with abrasive plate and abrasive cylinder for hard vegetables

### **Main Features**

- Suitable for 100-500 meals per service.
- Removable rotating plate covered in very resistant abrasive material (silicon carbide).
- Peels are reduced to small pieces to facilitate drainage process.
- Supplied with:
  - -abrasive plate and abrasive cylinder as standard
- Timer with countdown display.
- Pulse function to control the unloading operation.
- Safety device stops the machine from operating with unloading door open.

### Construction

- Complete stainless steel construction.
- IP55 waterproof touch button control panel.
- Transparent BPA free cover.

### **Included Accessories**

 1 of Abrasive plate for 25 kg PNC 653506 vegetable peeler

# **Optional Accessories**


- Mobile trolley with filter tray for 25 PNC 653302 □ kg peeler
- Abrasive plate for 25 kg vegetable PNC 653506 🖵 peeler
- PNC 653509 🖵 Waste dilution unit for 25 kg vegetable peeler

APPROVAL:



# Peelers Vegetable Peeler, 25 kg -Abrasive Plate


# Front 1212 mm



**CWI1** = Cold Water inlet 1 (cleaning)

**D** = Drain

**EI** = Electrical inlet (power)



### **Electric**

Supply voltage: 603649 (DT25EF350)

220-240/380-415 V/3 ph/50 Hz

**603650 (DT25EF150)** 220-240 V/1N ph/50 Hz

Electrical power max.:

**603649 (DT25EF350)** 0.9 kW **603650 (DT25EF150)** 1.1 kW

**Total Watts:** 

**603649 (DT25EF350)** 0.9 kW **603650 (DT25EF150)** 1.1 kW

**Capacity:** 

**Performance (up to):** 400 - kg/hour

Capacity: 25 kg

**Key Information:** 

External dimensions, Width: 585 mm
External dimensions, Depth: 785 mm
External dimensions, Height: 1215 mm

Shipping weight:

**603649 (DT25EF350)** 90 kg **603650 (DT25EF150)** 103 kg

