



Modular Cooking Range Line 700XP Half Module Electric Fry Top, Chromium Steel



371193 (E7FTEDCS10)

Half module electric fry top
with smooth chrome plate,
thermostatic control

Short Form Specification

Item No.

To be installed on open base installations or bridging supports. Smooth cooking surface in chromium-plated mild steel. Temperature range from 110°C to 280°C. Removable drawer below the cooking surface for the collection of grease and fat. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

ITEM # _____
MODEL # _____
NAME # _____
SIS # _____
AIA # _____

Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- Large drain hole on cooking surface permits the draining of fat into large 1 liter collector placed under the cooking surface.
- Large grease collection container available as optional accessory to be installed under top units over open base cupboard.
- Safety thermostat and thermostatic control.
- Stainless steel high splash guard on the rear and sides of cooking surface. Splash guard can be easily removed for cleaning.
- IPX4 water protection.
- Frontal simmering zone.
- Temperature range from 120° up to 280°C.
- Polished chromium surface avoids the mixing of flavors when passing from one type of food to another.
- Cooking surface 12mm thick polished chrome for optimum grilling results and ease of use.
- Infrared heating elements mounted below the cooking surface.
- Suitable for countertop installation.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- Cooking surface completely smooth.

Included Accessories

- 1 of Scraper for smooth plate fry tops PNC 164255

Optional Accessories

• Scraper for smooth plate fry tops	PNC 164255 <input type="checkbox"/>
• Junction sealing kit	PNC 206086 <input type="checkbox"/>
• Support for bridge type installation, 800mm	PNC 206137 <input type="checkbox"/>
• Support for bridge type installation, 1000mm	PNC 206138 <input type="checkbox"/>
• Support for bridge type installation, 1200mm	PNC 206139 <input type="checkbox"/>
• Support for bridge type installation, 1400mm	PNC 206140 <input type="checkbox"/>
• Support for bridge type installation, 1600mm	PNC 206141 <input type="checkbox"/>

APPROVAL: _____






Experience the Excellence
www.electroluxprofessional.com
ELUX_EMAIL

- Support for bridge type installation, 400mm
PNC 206154
- Kit 4 feet for concrete installation (not for 900 line free standing grill)
PNC 206210
- Chimney upstand, 400mm
PNC 206303
- Right and left side handrails
PNC 206307
- Back handrail 800mm, Marine
PNC 206308
- Grease/oil kit container for 700 line frytops (half and module) and 900 line frytops (module)
PNC 206346
- Chimney grid net, 400mm (700XP/900)
PNC 206400
- - NOT TRANSLATED -
PNC 206455
- Frontal handrail, 400mm
PNC 216046
- Frontal handrail, 800mm
PNC 216047
- Frontal handrail, 1200mm
PNC 216049
- Frontal handrail, 1600mm
PNC 216050
- Large handrail - portioning shelf, 400mm
PNC 216185
- Large handrail - portioning shelf, 800mm
PNC 216186
- 2 side covering panels for top appliances
PNC 216277

ACC_CHEM

- *NOT TRANSLATED*
PNC 0S2292


Front

Side
EI = Electrical inlet (power)
EQ = Equipotential screw

Top

Electric
Supply voltage: 400 V/3 ph/50-60 Hz
Electrical power max.: 4.2 kW
Total Watts: 4.2 kW

Key Information:

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Working Temperature MIN: 120 °C
Working Temperature MAX: 280 °C
External dimensions, Width: 400 mm
External dimensions, Depth: 730 mm
External dimensions, Height: 250 mm
Net weight: 40 kg
Shipping weight: 41 kg
Shipping height: 530 mm
Shipping width: 460 mm
Shipping depth: 820 mm
Shipping volume: 0.2 m³
[NOT TRANSLATED] EFT71
Cooking surface width: 330 mm
Cooking surface depth: 540 mm