

## Modular Cooking Range Line 700XP Freestanding Electric Pasta Cooker, 2 Wells 24.5 litres

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



## **Short Form Specification**

#### Item No.

Infrared heating system positioned below the well. Constant starch removal during the cooking process. Pressed tank in 316-L AISI stainless steel to protect against corrosion. Manual water tap. Height adjustable feet in stainless steel. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

cooker with 2 wells

#### **Main Features**

- In addition to cooking pasta, the appliance can be used for noodles of every kind, rice, dumplings and vegetables.
- Unit to have infrared heating system positioned beneath the base of the wells.
- Water basins are seamlessly welded into the top of the appliance.
- Provided with integrated drip zone on which baskets can be placed for draining purposes.
- 24.5 liters water basins.
- Unit to feature skimming zone for starch removal: improved water quality over time.
- Easy-to-use control panel.
- Safety thermostat to avoid operation without water.
- Continuous water filling regulated through a manual water tap.
- Large drain with manual ball-valve for fast emptying of well.
- Automatic lifting system (optional accessory): 200mm wide unit with two stainless steel basket supports, holding one GN 1/2 basket each, to be placed on either or both sides of machine to provide automatic lifting for four small portion baskets (to be ordered separately). Possibility to memorize nine cooking times through digital control.
- All major compartments located in front of unit for ease of maintenance.
- Unit delivered with four 50 mm legs in stainless steel as standard (all round Stainless steel kick plates as option).

### Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- IPX4 water resistance certification.
- Water basin in 316-L Stainless steel.

#### Sustainability



• ESD available as accessory (installed separately): energy saving device uses heat produced by water drained through the overflow to pre-heat tap-in water up to 60°C, for constant water boiling.



# Modular Cooking Range Line 700XP Freestanding Electric Pasta Cooker, 2 Wells 24.5 litres

			• 2 baskets 170x220 for pasta cookers	PNC 921610
<ul><li>Included Accessories</li><li>2 of Door for open base cupboard</li></ul>	PNC 206350		• Full size basket for 24,5lt pasta cookers	PNC 921611 PNC 921619
	1110 200000		<ul> <li>2 half size baskets 105x350 for pasta cookers for 24,5lt pasta cookers</li> </ul>	PINC 921019
Optional Accessories	DNIC 20/00/		•	
Junction sealing kit	PNC 206086			
• Kit 4 wheels - 2 swivelling with brake	PNC 206135			
Flanged feet kit	PNC 206136			
<ul> <li>Frontal kicking strip for concrete installation, 800mm</li> </ul>	PNC 206148			
<ul> <li>Frontal kicking strip for concrete installation, 1000mm</li> </ul>	PNC 206150			
<ul> <li>Frontal kicking strip for concrete installation, 1200mm</li> </ul>	PNC 206151			
<ul> <li>Frontal kicking strip for concrete installation, 1600mm</li> </ul>	PNC 206152			
<ul> <li>Frontal kicking strip, 800mm (not for refr-freezer base)</li> </ul>	PNC 206176			
<ul> <li>Frontal kicking strip, 1000mm (not for refr-freezer base)</li> </ul>	PNC 206177			
<ul> <li>Frontal kicking strip, 1200mm (not for refr-freezer base)</li> </ul>	PNC 206178			
<ul> <li>Frontal kicking strip, 1600mm (not for refr-freezer base)</li> </ul>	PNC 206179			
<ul> <li>Kit 4 feet for concrete installation (not for 900 line free standing grill)</li> </ul>	PNC 206210			
Pair of side kicking strips	PNC 206249			
Pair of side kicking strips for concrete installation	PNC 206265			
Chimney upstand, 800mm	PNC 206304			
Right and left side handrails	PNC 206307			
Back handrail 800mm, Marine	PNC 206308	_		
<ul> <li>Energy saving device for pasta cookers</li> </ul>				
<ul> <li>Door for open base cupboard</li> </ul>	PNC 206350			
<ul> <li>Automatic programmable basket lifting</li> </ul>	PNC 206352			
<ul> <li>system for 24,51t pasta cookers, 2 lifters</li> <li>Base support for feet or wheels -</li> </ul>	PNC 206367			
800mm (700/900)  • Base support for feet or wheels -	PNC 206368			
1200mm (700/900)				
Base support for feet or wheels - 1600mm (700/900)	PNC 206369			
Base support for feet or wheels - 2000mm (700/900)	PNC 206370			
• Rear paneling - 800mm (700/900)	PNC 206374			
<ul> <li>Rear paneling - 1000mm (700/900)</li> </ul>	PNC 206375			
<ul> <li>Rear paneling - 1200mm (700/900)</li> </ul>	PNC 206376			
<ul> <li>Support frame for 2 pasta cooker basket (700XP)</li> </ul>	PNC 206396			
<ul> <li>Chimney grid net, 400mm (700XP/900)</li> </ul>	PNC 206400			
<ul> <li>2 side covering panels for free standing appliances</li> </ul>	PNC 216000			
• Frontal handrail, 800mm	PNC 216047			
• Frontal handrail, 1200mm	PNC 216049			
• Frontal handrail, 1600mm	PNC 216050			
<ul> <li>Large handrail - portioning shelf, 800mm</li> </ul>	PNC 216186			
<ul> <li>2 baskets, left and right (105x160) for pasta cookers - 700XP and EMPower</li> </ul>	PNC 921020			
<ul> <li>2 baskets, left and right (105x105) for pasta cookers - 700XP and EMPower</li> </ul>	PNC 921021			
<ul> <li>Support for pasta cooker baskets</li> </ul>	PNC 921022			
Lid for pasta cookers	PNC 921607			













# Modular Cooking Range Line 700XP Freestanding Electric Pasta Cooker, 2 Wells 24.5 litres






Drain

Electrical inlet (power)

EQ Equipotential screw

Water inlet



#### **Electric**

Supply voltage:

380-400 V/3N ph/50/60 Hz

371099 (E7PCEH2KF0)

Electrical power max.: 12 kW **Total Watts:** 12 kW

Water:

Drain "D":

Incoming Cold/hot Water

1/2" line size: Total hardness: 5-50 ppm

Electrolux Professional recommends the use of treated water, based on testing of specific water conditions. Please refer to user manual for detailed water quality information.

#### **Key Information:**

Usable well dimensions (width): 250 mm

Usable well dimensions (height):

300 mm Usable well dimensions

(depth):

Side

Top

400 mm Well Capacity (MAX): 24.5 It MAX

Net weight: 65 kg 77 kg Shipping weight: 1130 mm Shipping height: Shipping width: 820 mm 860 mm Shipping depth: Shipping volume: 0.8 m<sup>3</sup>

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

[NOT TRANSLATED] EPC72S







