Electrolux PROFESSIONAL

Modular Cooking Range Line 900XP 2-Hot Plates Electric Boiling Top



391039 (E9ECED2Q00)

2-hot square plates (4 kW each) electric boiling top

391165 (E9ECED2Q0N)

2-hot plate (4 kW each) electric boiling top

Short Form Specification

Item No.

To be installed on open base installations, bridging supports or cantilever systems. Two 4 kW square cast-iron hot plates hermetically sealed to the one-piece top. Exterior panels of unit in stainless steel with Scotch Brite finish. Extra strength work top in heavy duty 2 mm stainless steel. Rightangled side edges to allow flush-fitting junction between units.

Main Features Unit to be mounted on open base cupboards, bridging supports or cantilever systems.

- The two 4kW cast-iron plates are hermtically sealed to the one-piece top. Hot plates with a power of 4kW for each plate.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.
- Top configuration allows installation on ambient base only (not possible to install on refrigerated nor freezer base).
- Suitable for countertop installation.

Construction

- Unit is 930 mm deep to give a larger working surface area.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Optional Accessories

- Pair of cast iron plate bars for PNC 206056 electric cooking top
- Junction sealing kit
 Support for bridge type
 PNC 206086 □
 PNC 206137 □
- installation, 800mm
- Support for bridge type PNC 206138 up installation, 1000mm
- Support for bridge type PNC 206139 D installation, 1200mm
- Support for bridge type PNC 206140 □ installation, 1400mm
- Support for bridge type PNC 206141
- Support for bridge type PNC 206154 🗆 installation, 400mm
- Water column with swivel arm PNC 206289
 (water column extension not included)
- Water column extension for PNC 206290 900 line
- Chimney upstand, 400mm PNC 206303 🗅
- Back handrail 800mm, Marine PNC 206308 🗅
- - NOT TRANSLATED PNC 206309 □
- Chimney grid net, 400mm PNC 206400 □ (700XP/900)
- Side handrail-right/left hand PNC 216044 🗆 (900XP)
- Frontal handrail, 400mm PNC 216046 🗆

APPROVAL:



ITEM # MODEL # NAME # SIS # AIA #



• Frontal handrail, 800mm	PNC 216047	
 Frontal handrail, 1200mm 	PNC 216049	
 Frontal handrail, 1600mm 	PNC 216050	
 Large handrail - portioning shelf, 400mm 	PNC 216185	
 Large handrail - portioning shelf, 800mm 	PNC 216186	
 2 side covering panels for top appliances 	PNC 216278	
 1x1/1GN basket for 40lt pasta cookers (only for 391039) 	PNC 927216	
Upper support frame to hold 6	PNC 960644	

 Upper support frame to hold 6 round baskets for 40lt pasta cookers (alternative to 927219 for 6 round baskets) (only for 391165)



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Electrolux PROFESSIONAL

Modular Cooking Range Line 900XP 2-Hot Plates Electric Boiling Top



3 15/16 100 mm

CE IEC TECEE

Electric

Supply voltage:		
391039 (E9ECED2Q00)	380-400 V/3N ph/50-60 Hz	
391165 (E9ECED2Q0N)	230 V/3 ph/50/60 Hz	
Total Watts:	8 kW	
Key Information:		
Net weight:	35 kg	
Shipping weight:	43 kg	
Shipping height:		
391039 (E9ECED2Q00)	520 mm	
391165 (E9ECED2Q0N)	540 mm	
Shipping width:	460 mm	
Shipping depth:	1020 mm	
Shipping volume:		
391039 (E9ECED2Q00)	0.24 m³	
391165 (E9ECED2Q0N)	0.25 m³	
[NOT TRANSLATED]		
391039 (E9ECED2Q00)	EH927	
391165 (E9ECED2Q0N)	N9CE1	
Front Plates Power:	4 - 0 kW	
Back Plates Power:	4 - kW	
Front Plates dimensions:	300x300	
Back Plates dimensions:	300x300	
If appliance is set up or next to or against temperature		

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Modular Cooking Range Line 900XP 2-Hot Plates Electric Boiling Top

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.