

Modular Cooking Range Line 900XP 4-Burner Gas Range 10 kW on Gas Oven

TEM #	
MODEL #	
NAME #	
SIS #	
AIA#	



391006 (E9GCGH4CGM)

4-burner (10 kW each) gas range on gas oven (8,5 kW)

Short Form Specification

Item No.

To be installed on stainless steel feet with height adjustment up to 50 mm. High efficiency flower flame burners with continuous power regulation and optimized combustion. Flame failure device as standard on burners to protect against accidental extinguishing. Oven chamber with 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans). Ribbed, cast-iron oven base plate. Exterior panels of unit in stainless steel with Scotch Brite finish. Pan supports in heavy duty cast iron. Extra strength work top in heavy duty 2 mm stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on stainless steel feet with height adjustment up to 50 mm. Unit can be easily mounted on cantilever systems.
- Four 10 kW high efficiency burners are equipped with continuous power regulation from 2.2 kW to 10 kW.
- Gas appliance supplied for use with natural or LPG gas, conversion jets supplied as standard.
- Large sized pan support in cast iron (stainless steel as option) with long center fins to allow the use of the largest down to the smallest pans.
- Burners with optimized combustion.
- Flame failure device on each burner protects against gas leakage when accidental extinguishing of the flame occurs.
- Protected pilot light.
- Base compartment consists of a gas heated standard oven with stainless steel burners and self stabilizing flame positioned beneath the base plate. Oven chamber to have 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans) and ribbed cast iron base plate.
- 40 mm thick oven door for heat insulation.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.
- Control knobs provide smooth, continuous rotation from min to max power level.

Construction

- Unit is 930 mm deep to give a larger working surface area.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Sustainability

• [NOTTRANSLATED]



Included Accessories

 1 of GN2/1 chrome grid for PNC 164250 static oven

Optional Accessories

• GN2/1 chrome grid for static PNC 164250 ☐ oven

Junction sealing kit
 Draught diverter, 150 mm diameter
 PNC 206086 □
 PNC 206132 □

APPROVAL:






Modular Cooking Range Line 900XP 4-Burner Gas Range 10 kW on Gas Oven


•	Matching ring for flue condenser, 150 mm diameter	PNC 206133	Rear paneling - 1000mm (700/900)Rear paneling - 1200mm (700/900)	PNC 206375 PNC 206376	
•	Kit 4 wheels - 2 swivelling with brake	PNC 206135	- NOTTRANSLATED -Chimney grid net, 400mm	PNC 206385 PNC 206400	
•	Flanged feet kit	PNC 206136	(700XP/900)		
	Frontal kicking strip for concrete	PNC 206148	• - NOTTRANSLATED -	PNC 206458	
•	installation, 800mm • Frontal kicking strip for concrete installation, 1000mm	PNC 206150	Side handrail-right/left hand (900XP) Second learn death 200 area.	PNC 216044	
•	Frontal kicking strip for concrete installation, 1200mm	PNC 206151	Frontal handrail, 800mmFrontal handrail, 1200mm	PNC 216047 PNC 216049	
•	Frontal kicking strip for concrete installation, 1600mm	PNC 206152	Frontal handrail, 1600mm2 side covering panels for free	PNC 216050 PNC 216134	
•	2 SIDE KICKING STRIPS- CONCRETE INST-900	PNC 206157	standing appliancesLarge handrail - portioning shelf, 400mm	PNC 216185	
•	Single burner smooth plate for direct cooking - fits frontal burners only	PNC 206171	Large handrail - portioning shelf, 800mm	PNC 216186	
•	 Single burner ribbed plate for direct cooking - fits frontal burners only 	PNC 206172	2 half size baskets for 18/23 lt fryersPressure regulator for gas units	PNC 927223 PNC 927225	
•	• Frontal kicking strip, 800mm (not for refr-freezer base)	PNC 206176			
•	Frontal kicking strip, 1000mm (not for refr-freezer base)	PNC 206177			
•	Frontal kicking strip, 1200mm (not for refr-freezer base)	PNC 206178			
•	Frontal kicking strip, 1600mm (not for refr-freezer base)	PNC 206179			
	 Pair of side kicking strips (not for refr-freezer base) 	PNC 206180			
	2 panels for service duct for single installation	PNC 206181			
	2 panels for service duct for back to back installation				
	Kit 4 feet for concrete installation (not for 900 line free standing grill)	PNC 206210			
	Flue condenser for 1 module, 150 mm diameter	PNC 206246			
•	 Water column with swivel arm (water column extension not included) 	PNC 206289			
•	Water column extension for 900 line	PNC 206290			
•	Stainless steel double grid for 2 burners	PNC 206298			
•	Chimney upstand, 800mm	PNC 206304			
	Back handrail 800mm, Marine	PNC 206308			
	- NOTTRANSLATED -	PNC 206309			
	Wok pan support for open burners	PNC 206363			
•	(700/900) • Base support for feet or wheels - 800mm (700/900)	PNC 206367			
•	• Base support for feet or wheels - 1200mm (700/900)	PNC 206368			
•	Base support for feet or wheels - 1600mm (700/900)	PNC 206369			
•	Base support for feet or wheels - 2000mm (700/900)	PNC 206370			
•	Rear paneling - 800mm (700/900)	PNC 206374			






Modular Cooking Range Line 900XP 4-Burner Gas Range 10 kW on Gas Oven





Gas connection



Gas

Natural gas - Pressure:

7" w.c. (17.4 mbar)

Gas Power:

Natural Gas G20 (20mbar)

Gas Type Option:

Key Information:

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Oven working Temperature: 120 °C MIN; 270 °C MAX

Oven Cavity Dimensions

(width): 575 mm

Oven Cavity Dimensions (height):

300 mm

Oven Cavity Dimensions 700 mm (depth): Net weight: 155 kg Shipping weight: 137 kg

Shipping height: 1080 mm Shipping width: 1020 mm Shipping depth: 860 mm Shipping volume: 0.95 m³ Front Burners Power: 10 - 10 kW **Back Burners Power:** 10 - 10 kW

[NOT TRANSLATED] **Back Burners Dimension -**

Front Burners Dimension -

[NOT TRANSLATED]

Ø 100 Ø 100 EcoFlame model available

N9CG

Ø 100 Ø 100

to save up to 20% on gas

391006 (E9GCGH4CGM)

48.5 kW

Standard gas delivery:

LPG;Natural Gas

Gas Inlet: 1/2"

Modular Cooking Range Line 900XP 4-Burner Gas Range 10 kW on Gas Oven