# FROFESSIONAL

# SkyLine PremiumS Electric Combi Oven 6GN1/1

ITEM #
MODEL #
NAME #
<u>SIS</u> #
AIA #



boiler oven with touch screen control, 6x1/1GN, electric, 3 cooking modes (automatic, recipe program, manual), automatic cleaning

## **Short Form Specification**

### Item No.

Combi oven with high resolution full touch screen interface, multilanguage - Built-in steam generator with real humidity control based upon Lambda Sensor - OptiFlow air distribution system to achieve maximum performance with 7 fan speed levels

- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinseonly) and green functions to save energy, water, detergent and rinse aid

Cooking modes: Automatic (9 food families with 100+ different pre-installed variants);
 Programs (a maximum of 1000 recipes can be stored and organized in 16 different categories);
 Manual (steam, combi and convection cycles);
 Specialistic Cycles (regeneration, Low Temperature Cooking, proving, EcoDelta, Sous-Vide, Static-Combi, Pasteurization of pasta, dehydration, Food Safe Control and Advanced Food Safe Control)

 Special functions: MultiTimer cooking, Plan-n-Save to cut running costs, Make-it-Mine to customize interface, SkyHub to customize homepage, agenda MyPlanner, SkyDuo connection to SkyLine ChillerS, automatic backup mode to avoid downtime

- USB port to download HACCP data, programs and settings. Connectivity ready
   6-point multi sensor core temperature probe
- Double glass door with LED lights
- Stainless steel construction throughout
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

## **Main Features**

- Built-in steam generator for highly precise humidity and temperature control according to the chosen settings.
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- Dry, hot convection cycle (25 °C 300 °C): ideal for low humidity cooking.
- Combination cycle (25 °C 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- Low temperature Steam cycle (25 °C 99 °C): ideal for sous-vide, re-thermalization and delicate cooking. Steam cycle (100 °C): seafood and vegetables. High temperature steam (25 °C - 130 ° C).
- Automatic mode including 9 food families (meat, poultry, fish, vegetables, pasta/rice, eggs, savory and sweet bakery, bread, dessert) with 100+ different pre-installed variants. Through Automatic Sensing Phase the oven optimizes the cooking process according to size, quantity and type of food loaded to achieve the selected cooking result. Real time overview of the cooking parameters. Possibility to personalize and save up to 70 variants per family.
- Cycles+: Regeneration (ideal for banqueting on plate or rethermalizing on tray), - Low Temperature Cooking (to minimize weight loss and maximize food quality) Patented US7750272B2 and related family, - Proving cycle, - EcoDelta cooking, cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber, - Sous-vide cooking, - Static Combi (to reproduce traditional cooking from static oven), - Pasteurization of pasta, - Dehydration cycles (ideal for drying fruits, vegetables, meats, seafood), - Food Safe Control (to automatically monitor safety of cooking process in compliance with HACCP hygienic standards) Patented US6818865B2 and related family, - Advanced Food Safe Control (to drive the cooking with pasteurization factor).
- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be group in 16 different categories to better organize the menu. 16-step cooking programs also available.
- MultiTimer function to manage up to 20 different cooking cycles at the same time, improving flexibility and ensuring excellent cooking results. Can be saved up to 200 MultiTimer programs.
- Fan with 7 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- 6-point multi sensor core temperature probe for maximum precision and food safety.
- Automatic fast cool down and pre-heat function.
- Different chemical options available: solid (phosphate-free), liquid (requires optional accessory).
- GreaseOut: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).

### APPROVAL:





- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- Capacity: 6 GN 1/1 trays.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber.

## Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Seamless hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- Integrated spray gun with automatic retracting system for fast rinsing.
- IPX 5 spray water protection certification for easy cleaning.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

## User Interface & Data Management

- High resolution full touch screen interface (translated in more than 30 languages) color-blind friendly panel.
- Pictures upload for full customization of cooking cycles.
- Make-it-mine feature to allow full personalization or locking of the user interface.
- SkyHub lets the user group the favorite functions in the homepage for immediate access.
- MyPlanner works as an agenda where the user can plan the daily work and receive personalized alerts for each task.
- With SkyDuo the Oven and the Blast Chiller are connected to each other and communicate in order to guide the user through the cook&chill process optimizing time and efficiency (requires optional accessory).
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plugin sous-vide probe (optional accessory).
- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).
- Trainings and guidances supporting materials easily accessible by scanning QR-Code with any mobile device.
- Automatic consumption visualization at the end of the cycle.

## **Sustainability**

- Human centered design with 4-star certification for ergonomics and usability.
- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler (Registered Design at EPO).
- Reduced powerfunction for customized slow cooking cycles.
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only) and green functions to save energy, water, detergent and rinse aid. Also programmable with delayed start.
- Plan-n-Save function organizes the cooking sequence of the chosen cycles optimizing the work in the kitchen from a time and energy efficiency point of view.
- Zero Waste provides chefs with useful tips for minimizing food waste.
  - Zero Waste is a library of Automatic recipes that aims to: give a second life to raw food close to expiration date (e. g.: from milk to yogurt)

obtain genuine and tasty dishes from overripe fruit/



vegetables (usually considered not appropriate for sale) promote the use of typically discarded food items (e.g.: carrot peels).

• Energy Star 2.0 certified product.

C	Optional Accessories		
•	External reverse osmosis filter for single tank Dishwashers with atmosphere boiler and Ovens	PNC 864388	
•	- NOTTRANSLATED -	PNC 920004	
•	Wheel kit for 6 & 10 GN 1/1 and 2/1 GN oven base (not for the disassembled one)	PNC 922003	
•	Pair of AISI 304 stainless steel grids, GN 1/1	PNC 922017	
•	Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1	PNC 922036	
٠	AISI 304 stainless steel grid, GN 1/1	PNC 922062	
	Grid for whole chicken (4 per grid - 1,2kg each), GN 1/2	PNC 922086	
•	External side spray unit (needs to be mounted outside and includes support to be mounted on the oven)	PNC 922171	
•	Baking tray for 5 baguettes in perforated aluminum with silicon coating, 400x600x38mm	PNC 922189	
•	Baking tray with 4 edges in perforated aluminum, 400x600x20mm	PNC 922190	
•	Baking tray with 4 edges in aluminum, 400x600x20mm	PNC 922191	
٠	Pair of frying baskets	PNC 922239	
	AISI 304 stainless steel bakery/pastry grid 400x600mm	PNC 922264	
	Double-step door opening kit	PNC 922265	
	Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1	PNC 922266	
	USB probe for sous-vide cooking	PNC 922281	
	Grease collection tray, GN 1/1, H=100 mm	PNC 922321	
	Kit universal skewer rack and 4 long skewers for Lenghtwise ovens	PNC 922324	
	Universal skewer rack	PNC 922326 PNC 922327	
	4 long skewers Smoker for lengthwise and crosswise	PNC 922327 PNC 922338	
•	oven (4 kinds of smoker wood chips are available on request)	FIGC 722000	
	Multipurpose hook	PNC 922348	
	4 flanged feet for 6 & 10 GN , 2", 100-130mm	PNC 922351	
	Grid for whole duck (8 per grid - 1,8kg each), GN 1/1	PNC 922362	
	Tray support for 6 & 10 GN 1/1 disassembled open base	PNC 922382	
	Wall mounted detergent tank holder	PNC 922386	
	- NOTTRANSLATED	PNC 922390	
	- NOT TRANSLATED - - NOT TRANSLATED -	PNC 922421 PNC 922435	
	- NOT TRANSLATED -	PNC 922435 PNC 922438	
	- NOT TRANSLATED -	PNC 922430	
	Tray rack with wheels, 6 GN 1/1, 65mm	PNC 922600	
	pitch (included)		

#### SkyLine PremiumS Electric Combi Oven 6GN1/1

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

# Electrolux PROFESSIONAL

# SkyLine PremiumS Electric Combi Oven 6GN1/1

<ul> <li>Tray rack with wheels 5 GN 1/1, 80mm pitch</li> </ul>	PNC 922606	• 4
<ul> <li>Bakery/pastry tray rack with wheels holding 400x600mm grids for 6 GN 1/1 oven and blast chiller freezer, 80mm</li> </ul>	PNC 922607	• [ • [ (
pitch (5 runners) • Slide-in rack with handle for 6 & 10 GN	PNC 922610	• \ •
<ul> <li>1/1 oven</li> <li>Open base with tray support for 6 &amp; 10 GN 1/1 oven</li> </ul>	PNC 922612	• [ • (
<ul> <li>Cupboard base with tray support for 6 &amp; 10 GN 1/1 oven</li> </ul>	PNC 922614	1 • (
<ul> <li>Hot cupboard base with tray support for 6 &amp; 10 GN 1/1 oven holding GN 1/1 or400x600mm</li> </ul>	PNC 922615	( • ( (
<ul> <li>External connection kit for detergent and rinse aid</li> </ul>	PNC 922618	• ( 5
<ul> <li>Grease collection kit for GN 1/1-2/1 cupboard base (trolley with 2 tanks, open/close device and drain)</li> </ul>	PNC 922619	( • [ (
• Stacking kit for electric 6+6 GN 1/1 ovens or electric 6+10 GN 1/1 GN ovens	PNC 922620	• [
• Trolley for slide-in rack for 6 & 10 GN 1/1 oven and blast chiller freezer	PNC 922626	• [
<ul> <li>Trolley for mobile rack for 2 stacked 6 GN 1/1 ovens on riser</li> </ul>	PNC 922628	• t
<ul> <li>Trolley for mobile rack for 6 GN 1/1 on 6 or 10 GN 1/1 ovens</li> </ul>	PNC 922630	•   • 4
<ul> <li>Riser on feet for 2 6 GN 1/1 ovens or a 6 GN 1/1 oven on base</li> </ul>	PNC 922632	• 1
<ul> <li>Riser on wheels for stacked 2x6 GN 1/1 ovens, height 250mm</li> </ul>	PNC 922635	ا ] •
<ul> <li>Stainless steel drain kit for 6 &amp; 10 GN oven, dia=50mm</li> </ul>	PNC 922636	• -
<ul> <li>Plastic drain kit for 6 &amp;10 GN oven, dia=50mm</li> </ul>	PNC 922637	• -
<ul> <li>Trolley with 2 tanks for grease collection</li> </ul>	PNC 922638	• - •
<ul> <li>Grease collection kit for open base (2 tanks, open/close device and drain)</li> </ul>	PNC 922639	   •
<ul> <li>Wall support for 6 GN 1/1 oven</li> </ul>	PNC 922643	ŀ
<ul> <li>Dehydration tray, GN 1/1, H=20mm</li> </ul>	PNC 922651	• 1
<ul> <li>Flat dehydration tray, GN 1/1</li> </ul>	PNC 922652	ŀ
• Open base for 6 & 10 GN 1/1 oven, disassembled	PNC 922653	• [
<ul> <li>Bakery/pastry rack kit for 6 GN 1/1 oven with 5 racks 400x600mm and 80mm pitch</li> </ul>	PNC 922655	• • • F ł
<ul> <li>Stacking kit for gas 6 GN 1/1 oven placed on 7kg and 15kg crosswise blast chiller freezer</li> </ul>	PNC 922657	• [ • [
Heat shield for stacked ovens 6 GN 1/1 on 6 GN 1/1	PNC 922660	•
Heat shield for stacked ovens 6 GN 1/1 on 10 GN 1/1	PNC 922661	   •
Heat shield for 6 GN 1/1 oven	PNC 922662	ł
<ul> <li>Compatibility kit for installation of 6 GN 1/1 electric oven on previous 6 GN 1/1 electric oven</li> </ul>	PNC 922679	1 •   
<ul> <li>Fixed tray rack for 6 GN 1/1 and 400x600mm grids</li> </ul>	PNC 922684	ہ ک
5	DNC 000407	A
Kit to fix oven to the wall	PNC 922687	• *
<ul> <li>Tray support for 6 &amp; 10 GN 1/1 open base</li> </ul>	PNC 922690	• *

1	• 4 adjustable feet with black cover for 6 & 10 GN ovens, 100-115mm	PNC 922693	
	Detergent tank holder for open base	PNC 922699	
]	Bakery/pastry runners 400x600mm for	PNC 922702	
	6 & 10 GN 1/1 oven base	1110 /22/02	-
	Wheels for stacked ovens	PNC 922704	
1	Mesh grilling grid	PNC 922713	
	<ul> <li>Probe holder for liquids</li> </ul>	PNC 922714	
)	Odourless hood with fan for 6 & 10 GN	PNC 922718	Ē
	1/1 electric ovens	1110 722/10	
]	Odourless hood with fan for 6+6 or 6+10 GN 1/1 electric ovens	PNC 922722	
נ	Condensation hood with fan for 6 & 10 GN 1/1 electric oven	PNC 922723	
	Condensation hood with fan for	PNC 922727	
]	stacking 6+6 or 6+10 GN 1/1 electric ovens		-
1		PNC 922728	
	ovens	1100 /22/20	-
	• Exhaust hood with fan for stacking 6+6	PNC 922732	
)	or 6+10 GN 1/1 ovens		
)	<ul> <li>Exhaust hood without fan for 6&amp;10 1/1GN ovens</li> </ul>	PNC 922733	
נ	• Exhaust hood without fan for stacking 6+6 or 6+10 GN 1/1 ovens	PNC 922737	
	• Fixed tray rack, 5 GN 1/1, 85mm pitch	PNC 922740	
ן	• 4 high adjustable feet for 6 & 10 GN	PNC 922745	
1	ovens, 230-290mm		
	<ul> <li>Tray for traditional static cooking,</li> </ul>	PNC 922746	
1	H=100mm		
	Double-face griddle, one side ribbed	PNC 922747	
1	and one side smooth, 400x600mm		
	- NOTTRANSLATED -	PNC 922752	
)	- NOTTRANSLATED -	PNC 922773	
	<ul> <li>- NOTTRANSLATED -</li> </ul>	PNC 922774	
)	<ul> <li>- NOTTRANSLATED -</li> </ul>	PNC 922776	
נ	<ul> <li>Non-stick universal pan, GN 1/1, H=20mm</li> </ul>	PNC 925000	
1	<ul> <li>Non-stick universal pan, GN 1/ 1, H=40mm</li> </ul>	PNC 925001	
1	<ul> <li>Non-stick universal pan, GN 1/1,</li> </ul>	PNC 925002	
1	H=60mm		
נ	• Double-face griddle, one side ribbed and one side smooth, GN 1/1	PNC 925003	
1	<ul> <li>Aluminum grill, GN 1/1</li> </ul>	PNC 925004	
	<ul> <li>Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1</li> </ul>	PNC 925005	
1	<ul> <li>Flat baking tray with 2 edges, GN 1/1</li> </ul>	PNC 925006	
	<ul> <li>Baking tray for 4 baguettes, GN 1/1</li> </ul>	PNC 925007	
	<ul> <li>Potato baker for 28 potatoes, GN 1/1</li> </ul>	PNC 925008	
1	-		_
	<ul> <li>Non-stick universal pan, GN 1/2, H=20mm</li> </ul>	PNC 925009	
נ	<ul> <li>Non-stick universal pan, GN 1/2,</li> </ul>	PNC 925010	
נ	H=40mm		-
3	<ul> <li>Non-stick universal pan, GN 1/2, H=60mm</li> </ul>	PNC 925011	
נ	<ul> <li>Compatibility kit for installation on previous base GN 1/1</li> </ul>	PNC 930217	
-	ACC_CHEM		
)	<ul> <li>*NOT TRANSLATED*</li> </ul>	PNC 0S2394	
]	*NOT TRANSLATED*	PNC 0S2395	
		1110 002070	-




#### SkyLine PremiumS Electric Combi Oven 6GN1/1

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

# **Electrolux**

# SkyLine PremiumS Electric Combi Oven 6GN1/1



15/16 "

50 mm

(1)

1 15/16

50 mm ЯF

2 9/16 "

3

#### Electric Circuit breaker required Supply voltage: 217720 (ECOE61T2A0) 380-415 V/3N ph/50-60 Hz 217710 (ECOE61T2C0) 220-240 V/3 ph/50-60 Hz Electrical power max.: 11.8 kW 11.1 kW Electrical power, default: Water: Max inlet water supply 30 °C temperature: 3/4" Water inlet "FCW" connection: 1-6 bar Pressure, bar min/max: Chlorides: <45 ppm Conductivity: 217720 (ECOE61T2A0) 0 µS/cm 217710 (ECOE61T2C0) >50 µS/cm Drain "D": 50mm Electrolux Professional recommends the use of treated water, based on testing of specific water conditions. Please refer to user manual for detailed water quality information. Installation: Clearance: 5 cm rear and Clearance: right hand sides. Suggested clearance for service access: 50 cm left hand side. Capacity: GN: 6 (GN 1/1)

### Shipping weight: Shipping height: Shipping width:

**ISO Certificates** 

**ISO Standards:** 

04

30 kg

**Right Side** 

867 mm 775 mm

808 mm 117 kg

117 kg

134 kg

1030 mm

930 mm

930 mm 0.89 m<sup>3</sup>

# SkyLine PremiumS Electric Combi Oven 6GN1/1

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.