

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	



217782 (ECOG101T2G0)

SkyLine PremiumS combi boiler oven with touch screen control, 10x1/1GN, gas, 3 cooking modes (automatic, recipe program, manual), automatic cleaning

225762 (ECOG101T2G6)

\* NOT TRANSLATED \*

# **Short Form Specification**

#### Item No.

Combi oven with high resolution full touch screen interface, multilanguage

- Built-in steam generator with real humidity control based upon Lambda Sensor
- OptiFlow air distribution system to achieve maximum performance with 7 fan speed levels
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinseonly) and green functions to save energy, water, detergent and rinse aid
- Cooking modes: Automatic (9 food families with 100+ different pre-installed variants); Programs (a maximum of 1000 recipes can be stored and organized in 16 different categories); Manual (steam, combi and convection cycles); Specialistic Cycles (regeneration, Low Temperature Cooking, proving, EcoDelta, Sous-Vide, Static-Combi, Pasteurization of pasta, dehydration, Food Safe Control and Advanced Food Safe Control)
- Special functions: MultiTimer cooking, Plan-n-Save to cut running costs, Make-it-Mine to customize interface, SkyHub to customize homepage, agenda MyPlanner, SkyDuo connection to SkyLine ChillerS, automatic backup mode to avoid downtime
- USB port to download HACCP data, programs and settings. Connectivity ready
- 6-point multi sensor core temperature probe
- Double glass door with LED lights
- Stainless steel construction throughout
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

#### **Main Features**

- Built-in steam generator for highly precise humidity and temperature control according to the chosen settings.
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- Dry, hot convection cycle (25 °C 300 °C): ideal for low humidity cooking.
- Combination cycle (25 °C 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- Low temperature Steam cycle (25 °C 99 °C): ideal for sous-vide, re-thermalization and delicate cooking. Steam cycle (100 °C): seafood and vegetables. High temperature steam (25 °C - 130 °C).
- Automatic mode including 9 food families (meat, poultry, fish, vegetables, pasta/rice, eggs, savory and sweet bakery, bread, dessert) with 100+ different pre-installed variants. Through Automatic Sensing Phase the oven optimizes the cooking process according to size, quantity and type of food loaded to achieve the selected cooking result. Real time overview of the cooking parameters. Possibility to personalize and save up to 70 variants per family.
- Cycles\*: Regeneration (ideal for banqueting on plate or rethermalizing on tray), Low Temperature Cooking (to minimize weight loss and maximize food quality) Patented US7750272B2 and related family, Proving cycle, EcoDelta cooking, cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber, Sous-vide cooking, Static Combi (to reproduce traditional cooking from static oven), Pasteurization of pasta, Dehydration cycles (ideal for drying fruits, vegetables, meats, seafood), Food Safe Control (to automatically monitor safety of cooking process in compliance with HACCP hygienic standards) Patented US6818865B2 and related family, Advanced Food Safe Control (to drive the cooking with pasteurization factor).
- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be group in 16 different categories to better organize the menu. 16-step cooking programs also available.
- MultiTimer function to manage up to 20 different cooking cycles at the same time, improving flexibility and ensuring excellent cooking results. Can be saved up to 200 MultiTimer programs.
- Fan with 7 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- 6-point multi sensor core temperature probe for maximum precision and food safety.
- Pictures upload for full customization of cooking cycles.
- Automatic fast cool down and pre-heat function.
- Different chemical options available: solid (phosphate-free), liquid (requires optional accessory).

#### APPROVAL:





- GreaseOut: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- Capacity: 10 GN 1/1 trays.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber.

#### Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Seamless hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- Integrated spray gun with automatic retracting system for fast rinsing.
- IPX 5 spray water protection certification for easy cleaning.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

### User Interface & Data Management

- High resolution full touch screen interface (translated in more than 30 languages) - color-blind friendly panel.
- Make-it-mine feature to allow full personalization or locking of the user interface.
- SkyHub lets the user group the favorite functions in the homepage for immediate access.
- MyPlanner works as an agenda where the user can plan the daily work and receive personalized alerts for each task.
- With SkyDuo the Oven and the Blast Chiller are connected to each other and communicate in order to guide the user through the cook&chill process optimizing time and efficiency (requires optional accessory).
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plugin sous-vide probe (optional accessory).
- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).
- Trainings and guidances supporting materials easily accessible by scanning QR-Code with any mobile device.
- Automatic consumption visualization at the end of the cycle.

#### Sustainability



- Human centered design with 4-star certification for ergonomics and usability.
- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler (Registered Design at EPO).
- Reduced powerfunction for customized slow cooking cycles.
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only) and green functions to save energy, water, detergent and rinse aid. Also programmable with delayed start.
- Plan-n-Save function organizes the cooking sequence of the chosen cycles optimizing the work in the kitchen from a time and energy efficiency point of view.
- Zero Waste provides chefs with useful tips for minimizing food waste
  - Zero Waste is a library of Automatic recipes that aims to: give a second life to raw food close to expiration date (e.

- g.: from milk to yogurt)
- obtain genuine and tasty dishes from overripe fruit/vegetables (usually considered not appropriate for sale) promote the use of typically discarded food items (e.g.: carrot peels).
- Energy Star 2.0 certified product.

#### **Optional Accessories**

Optional Accessories		
<ul> <li>External reverse osmosis filter for single tank Dishwashers with atmosphere boiler and Ovens</li> </ul>	PNC 864388	
• - NOTTRANSLATED -	PNC 920004	
Wheel kit for 6 & 10 GN 1/1 and 2/1 GN oven base (not for the disassembled one)	PNC 922003	
<ul> <li>Pair of AISI 304 stainless steel grids, GN 1/1</li> </ul>	PNC 922017	
<ul> <li>Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1</li> </ul>	PNC 922036	
• AISI 304 stainless steel grid, GN 1/1	PNC 922062	
<ul> <li>Grid for whole chicken (4 per grid - 1,2kg each), GN 1/2</li> </ul>	PNC 922086	
<ul> <li>External side spray unit (needs to be mounted outside and includes support to be mounted on the oven)</li> </ul>	PNC 922171	
<ul> <li>Baking tray for 5 baguettes in perforated aluminum with silicon coating, 400x600x38mm</li> </ul>	PNC 922189	
Baking tray with 4 edges in perforated aluminum, 400x600x20mm	PNC 922190	
• Baking tray with 4 edges in aluminum, 400x600x20mm	PNC 922191	
<ul> <li>Pair of frying baskets</li> </ul>	PNC 922239	
<ul> <li>AISI 304 stainless steel bakery/pastry grid 400x600mm</li> </ul>	PNC 922264	
<ul> <li>Double-step door opening kit</li> </ul>	PNC 922265	
<ul> <li>Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1</li> </ul>	PNC 922266	
<ul> <li>USB probe for sous-vide cooking</li> </ul>	PNC 922281	
<ul> <li>Grease collection tray, GN 1/1, H=100 mm</li> </ul>	PNC 922321	
<ul> <li>Kit universal skewer rack and 4 long skewers for Lenghtwise ovens</li> </ul>	PNC 922324	
<ul> <li>Universal skewer rack</li> </ul>	PNC 922326	
<ul> <li>4 long skewers</li> </ul>	PNC 922327	
<ul> <li>Multipurpose hook</li> </ul>	PNC 922348	
<ul> <li>4 flanged feet for 6 &amp; 10 GN , 2", 100-130mm</li> </ul>	PNC 922351	
<ul> <li>Grid for whole duck (8 per grid - 1,8kg each), GN 1/1</li> </ul>	PNC 922362	
<ul> <li>Thermal cover for 10 GN 1/1 oven and blast chiller freezer</li> </ul>	PNC 922364	
<ul> <li>Tray support for 6 &amp; 10 GN 1/1 disassembled open base</li> </ul>	PNC 922382	
<ul> <li>Wall mounted detergent tank holder</li> </ul>	PNC 922386	
• - NOTTRANSLATED -	PNC 922390	
• - NOTTRANSLATED - (only for 217782)	PNC 922421	
• - NOTTRANSLATED -	PNC 922435	
• - NOTTRANSLATED -	PNC 922438	
• - NOTTRANSLATED -	PNC 922439	
• Tray rack with wheels, 10 GN 1/1, 65mm	PNC 922601	

SkyLine PremiumS Natural Gas Combi Oven 10GN1/1















pitch (included)



•	Tray rack with wheels 8 GN 1/1, 80mm pitch	PNC 922602		<ul> <li>Bakery/pastry runners 400x600mm for PNC 922702 6 &amp; 10 GN 1/1 oven base</li> </ul>	
	Bakery/pastry tray rack with wheels	PNC 922608		<ul> <li>Wheels for stacked ovens</li> <li>PNC 922704</li> </ul>	
•	400x600mm for 10 GN 1/1 oven and blast chiller freezer, 80mm pitch (8	111C 722000	_	• Spit for lamb or suckling pig (up to PNC 922709 12kg) for GN 1/1 ovens	
	runners)			Mesh grilling grid     PNC 922713	
•	Slide-in rack with handle for 6 & 10 GN	PNC 922610		• Probe holder for liquids PNC 922714	
	1/1 oven		_	·	
•	Open base with tray support for 6 & 10 GN 1/1 oven	PNC 922612		<ul> <li>Exhaust hood with fan for 6 &amp; 10 GN 1/1 PNC 922728 ovens</li> </ul>	
•	Cupboard base with tray support for 6 & 10 GN 1/1 oven	PNC 922614		Exhaust hood with fan for stacking 6+6 PNC 922732 or 6+10 GN 1/1 ovens  The stacking 6+6 PNC 922732 or 6+10 GN 1/1 ovens  The stacking 6+6 PNC 922732 or 6+10 GN 1/1 ovens	
•	Hot cupboard base with tray support for 6 & 10 GN 1/1 oven holding GN 1/1	PNC 922615		• Exhaust hood without fan for 6&10 PNC 922733 1/1GN ovens	
_	or400x600mm External connection kit for detergent	PNC 922618		<ul> <li>Exhaust hood without fan for stacking 6+6 or 6+10 GN 1/1 ovens</li> </ul>	
•	and rinse aid	1110 722010	_	• Fixed tray rack, 8 GN 1/1, 85mm pitch PNC 922741	
	Grease collection kit for GN 1/1-2/1	PNC 922619		• Fixed tray rack, 8 GN 2/1, 85mm pitch PNC 922742	
•	cupboard base (trolley with 2 tanks, open/close device and drain)	FINC 922019	_	<ul> <li>4 high adjustable feet for 6 &amp; 10 GN PNC 922745 ovens, 230-290mm</li> </ul>	
	Stacking kit for gas 6 GN 1/1 oven	PNC 922623		<ul> <li>Tray for traditional static cooking,</li> <li>PNC 922746</li> </ul>	
٠	placed on gas 10 GN 1/1 oven	FINC 722023	_	H=100mm	
•	Trolley for slide-in rack for 6 & 10 GN 1/1 oven and blast chiller freezer	PNC 922626		Double-face griddle, one side ribbed and one side smooth, 400x600mm  PNC 922747	
_	Trolley for mobile rack for 6 GN 1/1 on 6	DNIC 022630		• - NOTTRANSLATED - PNC 922752	
٠	or 10 GN 1/1 ovens	FINC 722030	_	• - NOTTRANSLATED - PNC 922773	
_	Stainless steel drain kit for 6 & 10 GN	PNC 922636		• - NOTTRANSLATED - PNC 922776	
•	oven, dia=50mm	PNC 922030			
•	Plastic drain kit for 6 &10 GN oven, dia=50mm	PNC 922637		• Non-stick universal pan, GN 1/1, PNC 925000 H=20mm	
•	Grease collection kit for open base (2	PNC 922639		<ul> <li>Non-stick universal pan, GN 1/ 1, H=40mm</li> </ul> PNC 925001	
	tanks, open/close device and drain)		_	<ul> <li>Non-stick universal pan, GN 1/1, PNC 925002</li> </ul>	
	Wall support for 10 GN 1/1 oven	PNC 922645		H=60mm	
•	Banquet rack with wheels holding 30 plates for 10 GN 1/1 oven and blast	PNC 922648		<ul> <li>Double-face griddle, one side ribbed PNC 925003 and one side smooth, GN 1/1</li> </ul>	
	chiller freezer, 65mm pitch		_	<ul> <li>Aluminum grill, GN 1/1</li> <li>PNC 925004</li> </ul>	
•	Banquet rack with wheels holding 23 plates for 10 GN 1/1 oven and blast chiller freezer, 85mm pitch	PNC 922649		• Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1	
	Dehydration tray, GN 1/1, H=20mm	PNC 922651		• Flat baking tray with 2 edges, GN 1/1 PNC 925006	
				<ul> <li>Baking tray for 4 baguettes, GN 1/1</li> <li>PNC 925007</li> </ul>	
	Flat dehydration tray, GN 1/1	PNC 922652		<ul> <li>Potato baker for 28 potatoes, GN 1/1</li> <li>PNC 925008</li> </ul>	
	Open base for 6 & 10 GN 1/1 oven, disassembled	PNC 922653	_	Non-stick universal pan, GN 1/2, PNC 925009     H=20mm	
•	Bakery/pastry rack kit for 10 GN 1/1 oven with 8 racks 400x600mm and 80mm pitch	PNC 922656		Non-stick universal pan, GN 1/2, PNC 925010 H=40mm	
•	Heat shield for stacked ovens 6 GN 1/1 on 10 GN 1/1	PNC 922661		Non-stick universal pan, GN 1/2, PNC 925011 H=60mm	
•	Heat shield for 10 GN 1/1 oven	PNC 922663		Compatibility kit for installation on PNC 930217     Provious base GN 1/1	
•	Kit to convert from natural gas to LPG	PNC 922670		previous base GN 1/1	
	Kit to convert from LPG to natural gas	PNC 922671		ACC CHEM	
	_			• *NOTTRANSLATED* PNC 0S2394	
	Flue condenser for gas oven	PNC 922678			
	Fixed tray rack for 10 GN 1/1 and 400x600mm grids	PNC 922685		• *NOTTRANSLATED* PNC 0S2395	
•	Kit to fix oven to the wall	PNC 922687			
•	Tray support for 6 & 10 GN 1/1 open base	PNC 922690			
	4 adjustable feet with black cover for 6 & 10 GN ovens, 100-115mm				
•	Reinforced tray rack with wheels, lowest support dedicated to a grease collection tray for 10 GN 1/1 oven, 64mm pitch				
•	Detergent tank holder for open base	PNC 922699			























CWII Cold Water inlet 1 CWI2 Cold Water Inlet 2 D

Gas connection Drain

DO Overflow drain pipe

> Top 20 15/16 <sup>s</sup> 532 mm 4 15/16 " D CWI1 **₹**000 CWI2 ΕI 1 15/16 " 50 mm 1 15/16 65 mm Ġ

#### **Electric**

Circuit breaker required

Supply voltage:

217782 (ECOG101T2G0) 220-240 V/1 ph/50 Hz 225762 (ECOG101T2G6) 220-230 V/1 ph/60 Hz

Electrical power max.: 1.1 kW 1.1 kW Electrical power, default:

Total thermal load: 105679 BTU (31 kW)

Gas Power: 31 kW

Standard gas delivery: Natural Gas G20

ISO 7/1 gas connection

diameter: 1/2" MNPT

#### Water:

Max inlet water supply

30 °C temperature: Water inlet "FCW" connection: 3/4" Pressure, bar min/max: 1-6 bar Chlorides: <17 ppm Conductivity: >50 µS/cm Drain "D": 50mm

Electrolux Professional recommends the use of treated water,

based on testing of specific water conditions.

Please refer to user manual for detailed water quality

information.

#### Installation:

Clearance: 5 cm rear and Clearance:

right hand sides.

Suggested clearance for service access: 50 cm left hand side.

Capacity:

10 (GN 1/1) Max load capacity: 50 kg

## **Key Information:**

Door hinges: Right Side External dimensions, Width: 867 mm 775 mm External dimensions, Depth: External dimensions, Height: 1058 mm Weight: 159 kg Net weight: 159 kg Shipping weight: 177 kg Shipping volume:

217782 (ECOG101T2G0) 1.11 m<sup>3</sup> 225762 (ECOG101T2G6) 1.04 m<sup>3</sup>

#### **ISO Certificates**

ISO Standards: 04















