

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	



217680 (ECOG61K2G0)

SkyLine ProS combi boilerless oven with touch screen control, 6x1/1GN, gas, 2 cooking modes (recipe program, manual), automatic cleaning

225660 (ECOG61K2G6)

* NOT TRANSLATED *

Short Form Specification

Item No.

Combi oven with high resolution full touch screen interface, multilanguage.

- Boilerless steaming function to add and retain moisture.
- OptiFlow air distribution system to achieve maximum performance with 7 fan speed levels.
- SkyClean: Automatic and built-in self cleaning system. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only) and green functions to save energy, water, detergent and rinse aid.
- Cooking modes: Programs (a maximum of 1000 recipes can be stored and organized in 16 different categories); Manual; EcoDelta cooking cycle.
- Special functions: MultiTimer cooking, Plan-n-Save to cut running costs, Make-it-Mine to customize interface, SkyHub to customize homepage, agenda MyPlanner, automatic backup mode to avoid downtime.
- USB port to download HACCP data, programs and settings. Connectivity readv.
- Single sensor core temperature probe.
- Double-glass door with LED lights.
- Stainless steel construction throughout.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

Main Features

- Boilerless steaming function to add and retain moisture for high quality, consistent cooking results.
- Dry hot convection cycle (max 300 °C) ideal for low humidity cooking. Automatic moistener (11 settings) for boiler-less steam generation:-0 = no additional moisture (browning, au gratin, baking, pre-cooked food)-1-2 = low moisture (small portions of meat and fish)-3-4 = medium low moisture (large pieces of meat, reheating, roasted chicken and proving)-5-6 = medium moisture (roasted vegetable and first step of roasted meat & fish)-7-8 = medium-high moisture (stewed vegetables)-9-10 = high moisture (poached meat and jacket potatoes)
- EcoDelta cooking: cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber.
- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be group in 16 different categories to better organize the menu. 16-step cooking programs also available.
- MultiTimer function to manage up to 20 different cooking cycles at the same time, improving flexibility and ensuring excellent cooking results. Can be saved up to 200 MultiTimer programs.
- Fan with 7 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Single sensor core temperature probe included.
- Pictures upload for full customization of cooking cycles.
- Automatic fast cool down and pre-heat function.
- Different chemical options available: solid (phosphate-free), liquid (requires optional accessory).
- GreaseOut: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plug-in sous-vide probe (optional accessory).
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- [NOTTRANSLATED]
- [NOTTRANSLATED]

Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Seamless hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- IPX 5 spray water protection certification for easy cleaning.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

User Interface & Data Management







PNC 922321

PNC 922324

PNC 922326

PNC 922327

PNC 922338

PNC 922348

PNC 922351

PNC 922362

PNC 922382

PNC 922386

PNC 922390

PNC 922600

PNC 922606

PNC 922607

PNC 922610

PNC 922612

PNC 922614

 \Box

 \Box

Grease collection tray, GN 1/1, H=100

• Kit universal skewer rack and 4 long

• Smoker for lengthwise and crosswise

oven (4 kinds of smoker wood chips are

Grid for whole duck (8 per grid - 1,8kg

Wall mounted detergent tank holder

• Tray rack with wheels, 6 GN 1/1, 65mm

Tray rack with wheels 5 GN 1/1, 80mm

 Bakery/pastry tray rack with wheels holding 400x600mm grids for 6 GN 1/1

oven and blast chiller freezer, 80mm

• Slide-in rack with handle for 6 & 10 GN

Open base with tray support for 6 & 10

Cupboard base with tray support for 6

skewers for Lenghtwise ovens

4 flanged feet for 6 & 10 GN , 2",

Tray support for 6 & 10 GN 1/1

disassembled open base

• - NOTTRANSLATED -

pitch (included)

pitch (5 runners)

pitch

1/1 oven

GN 1/1 oven

& 10 GN 1/1 oven

• Universal skewer rack

available on request)

Multipurpose hook

100-130mm

each), GN 1/1

• 4 long skewers

- High resolution full touch screen interface (translated in more than 30 languages) - color-blind friendly panel.
- Make-it-mine feature to allow full personalization or locking of the user interface.
- SkyHub lets the user group the favorite functions in the homepage for immediate access.
- MyPlanner works as an agenda where the user can plan the daily work and receive personalized alerts for each task.
- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).
- Trainings and guidances supporting materials easily accessible by scanning QR-Code with any mobile device.
- Automatic consumption visualization at the end of the cycle.
- [NOT TRANSLATED]

Sustainability



- Human centered design with 4-star certification for ergonomics and usability.
- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler (Registered Design at EPO).
- Reduced powerfunction for customized slow cooking cycles.
- SkyClean: Automatic and built-in self cleaning system. 5 automatic cycles (soft, medium, strong, extra strong, rinseonly) and green functions to save energy, water, detergent and rinse aid. Also programmable with delayed start.
- Plan-n-Save function organizes the cooking sequence of the chosen cycles optimizing the work in the kitchen from a time and energy efficiency point of view.

Optional Accessories

Optional Accessories			DV10 000/15	
 Water softener with cartridge and flow meter (high steam usage) 	PNC 920003	 Hot cupboard base with tray support for 6 & 10 GN 1/1 oven holding GN 1/1 or400x600mm 	PNC 922615	
 Water softener with salt for ovens with automatic regeneration of resin 	PNC 921305	External connection kit for detergent and rinse gid	PNC 922618	
 Wheel kit for 6 & 10 GN 1/1 and 2/1 GN oven base (not for the disassembled one) 	PNC 922003	 Grease collection kit for GN 1/1-2/1 cupboard base (trolley with 2 tanks, open/close device and drain) 	PNC 922619	
 Pair of AISI 304 stainless steel grids, GN 1/1 	PNC 922017	Stacking kit for gas 6 GN 1/1 oven placed on gas 6 GN 1/1 oven	PNC 922622	
 Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1 	PNC 922036	Stacking kit for gas 6 GN 1/1 oven placed on gas 10 GN 1/1 oven	PNC 922623	
 AISI 304 stainless steel grid, GN 1/1 	PNC 922062	• Trolley for slide-in rack for 6 & 10 GN 1/1	PNC 922626	
 Grid for whole chicken (4 per grid - 	PNC 922086	oven and blast chiller freezer		
1,2kg each), GN 1/2	5,10,000171	 Trolley for mobile rack for 2 stacked 6 	PNC 922628	
 External side spray unit (needs to be mounted outside and includes support 	PNC 922171	GN 1/1 ovens on riser		_
to be mounted on the oven)		 Trolley for mobile rack for 6 GN 1/1 on 6 or 10 GN 1/1 ovens 	PNC 922630	
 Baking tray for 5 baguettes in perforated aluminum with silicon coating, 400x600x38mm 	PNC 922189	• Riser on feet for 2 6 GN 1/1 ovens or a 6 GN 1/1 oven on base		
 Baking tray with 4 edges in perforated 	PNC 922190	Riser on wheels for stacked 2x6 GN 1/1 Avens height 250mm	PNC 922635	
aluminum, 400x600x20mm		ovens, height 250mm	DNC 022474	
Baking tray with 4 edges in aluminum, 400x600x20mm	PNC 922191	Stainless steel drain kit for 6 & 10 GN oven, dia=50mm	PNC 922636	
 Pair of frying baskets 	PNC 922239	 Plastic drain kit for 6 &10 GN oven, dia=50mm 	PNC 922637	
 AISI 304 stainless steel bakery/pastry grid 400x600mm 	PNC 922264	Grease collection kit for open base (2 tanks, open/close device and drain)	PNC 922639	
 Double-step door opening kit 	PNC 922265	Wall support for 6 GN 1/1 oven	PNC 922643	
Grid for whole chicken (8 per grid -	PNC 922266	Dehydration tray, GN 1/1, H=20mm	PNC 922651	_
1,2kg each), GN 1/1		Flat dehydration tray, GN 1/1	PNC 922652	
 USB probe for sous-vide cooking 	PNC 922281	- Hat achyaladon day, Oly 1/1	1110 /22002	_







• USB probe for sous-vide cooking







PNC 922281





•	Open base for 6 & 10 GN 1/1 oven, disassembled	PNC 922653		 Non-stick universal pan, GN 1/2, H=20mm 	PNC 925009
•	Bakery/pastry rack kit for 6 GN 1/1 oven with 5 racks 400x600mm and 80mm	PNC 922655		 Non-stick universal pan, GN 1/2, H=40mm 	PNC 925010
	pitch		_	Non-stick universal pan, GN 1/2, H-40mm	PNC 925011
•	Stacking kit for gas 6 GN 1/1 oven placed on 7kg and 15kg crosswise blast chiller freezer	PNC 922657		 H=60mm Compatibility kit for installation on previous base GN 1/1 	PNC 930217
•	Heat shield for stacked ovens 6 GN 1/1 on 6 GN 1/1	PNC 922660			
•	Heat shield for stacked ovens 6 GN 1/1 on 10 GN 1/1	PNC 922661			
•	Heat shield for 6 GN 1/1 oven	PNC 922662			
•	Kit to convert from natural gas to LPG	PNC 922670			
•	Kit to convert from LPG to natural gas	PNC 922671			
•	Flue condenser for gas oven	PNC 922678			
•	Fixed tray rack for 6 GN 1/1 and 400x600mm grids	PNC 922684			
•	Kit to fix oven to the wall	PNC 922687			
•	Tray support for 6 & 10 GN 1/1 open base	PNC 922690			
•	4 adjustable feet with black cover for 6 & 10 GN ovens, 100-115mm				
	Detergent tank holder for open base	PNC 922699			
	Bakery/pastry runners 400x600mm for 6 & 10 GN 1/1 oven base	PNC 922702			
	Wheels for stacked ovens	PNC 922704			
	- NOTTRANSLATED -	PNC 922706			
	Mesh grilling grid	PNC 922713			
	Probe holder for liquids	PNC 922714			
	Exhaust hood with fan for 6 & 10 GN 1/1 ovens	PNC 922728	_		
	Exhaust hood with fan for stacking 6+6 or 6+10 GN 1/1 ovens	PNC 922732			
	Exhaust hood without fan for 6&10 1/1GN ovens	PNC 922733			
	Exhaust hood without fan for stacking 6+6 or 6+10 GN 1/1 ovens	PNC 922737			
	Fixed tray rack, 5 GN 1/1, 85mm pitch	PNC 922740			
	4 high adjustable feet for 6 & 10 GN ovens, 230-290mm	PNC 922745			
	Tray for traditional static cooking, H=100mm	PNC 922746			
	Double-face griddle, one side ribbed and one side smooth, 400x600mm	PNC 922747			
	- NOTTRANSLATED -	PNC 922752			
	- NOTTRANSLATED -	PNC 922773			
	- NOTTRANSLATED -	PNC 922776			
	Non-stick universal pan, GN 1/1, H=20mm	PNC 925000			
	Non-stick universal pan, GN 1/1, H=40mm	PNC 925001			
	Non-stick universal pan, GN 1/1, H=60mm	PNC 925002			
	Double-face griddle, one side ribbed and one side smooth, GN 1/1	PNC 925003			
	Aluminum grill, GN 1/1	PNC 925004			
	Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1	PNC 925005			
	Flat baking tray with 2 edges, GN 1/1	PNC 925006			
	Baking tray for 4 baguettes, GN 1/1 Potato baker for 28 potatoes, GN 1/1	PNC 925007 PNC 925008			




















33 1/2 " 850 mm 2 " 50 mm 3 " 75 mm 8 CWI1 CWI2 EI 53 13/16 3 15/16 " 100 mm 935 36 2 5/16 58 mm 23 1/4 " 4 15/16 "

ΕI

Electrical inlet (power)

Gas connection

CWII Cold Water inlet 1 CWI2

Cold Water Inlet 2

Drain

DO Overflow drain pipe

> Top 20 15/16 " 4 15/16 " 125 mm 7 3/8 " 188 mm 8 7/16 " 214 mm 18 3/4 " 477 mm D CWI1 CWI2 ♠ EI 1 15/16 " 1 15/16 G



Front

Side

Supply voltage:

217680 (ECOG61K2G0) 220-240 V/1 ph/50 Hz 225660 (ECOG61K2G6) 220-230 V/1 ph/60 Hz

Electrical power, default: 1.1 kW Electrical power max.: 1.1 kW

Circuit breaker required

12 kW Gas Power:

Standard gas delivery: Natural Gas G20

ISO 7/1 gas connection

diameter: 1/2" MNPT

Total thermal load: 40908 BTU (12 kW)

Water:

Water inlet "FCW" connection: 3/4" Pressure, bar min/max: 1-6 bar Drain "D": 50mm

Max inlet water supply

30 °C temperature:

Hardness: 5 °fH / 2.8 °dH Chlorides: <10 ppm Conductivity: >50 µS/cm

Electrolux Professional recommends the use of treated water, based on testing of specific water conditions.

Please refer to user manual for detailed water quality

information.

Installation:

Clearance: 5 cm rear and Clearance:

right hand sides.

Suggested clearance for

service access: 50 cm left hand side.

Capacity:

6 - 1/1 Gastronorm

Max load capacity: 30 kg

Key Information:

Door hinges:

External dimensions, Width: 867 mm External dimensions, Depth: 775 mm 808 mm External dimensions, Height:

Net weight:

217680 (ECOG61K2G0) 115 kg 225660 (ECOG61K2G6) 118 kg

Shipping weight:

217680 (ECOG61K2G0) 132 kg 225660 (ECOG61K2G6) 135 kg

Shipping volume:

217680 (ECOG61K2G0) 0.89 m³ 225660 (ECOG61K2G6) 0.85 m³

ISO Certificates

ISO Standards:













