

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



217791 (ECOG62T2G1)

SkyLine PremiumS combi boiler oven with touch screen control, 6x2/IGN, gas, 3 cooking modes (automatic, recipe program, manual), automatic cleaning, boiler in AISI 316

## **Short Form Specification**

#### Item No.

Combi oven with high resolution full touch screen interface, multilanguage

- Built-in steam generator (in s/s 316L) with real humidity control based upon Lambda Sensor
- OptiFlow air distribution system to achieve maximum performance with 7 fan speed levels
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinseonly) and green functions to save energy, water, detergent and rinse aid
- Cooking modes: Automatic (9 food families with 100+ different pre-installed variants); Programs (a maximum of 1000 recipes can be stored and organized in 16 different categories); Manual (steam, combi and convection cycles); Specialistic Cycles (regeneration, Low Temperature Cooking, proving, EcoDelta, Sous-Vide, Static-Combi, Pasteurization of pasta, dehydration, Food Safe Control and Advanced Food Safe Control)
- Special functions: MultiTimer cooking, Plan-n-Save to cut running costs, Make-it-Mine to customize interface, SkyHub to customize homepage, agenda MyPlanner, SkyDuo connection to SkyLine ChillerS, automatic backup mode to avoid downtime
- USB port to download HACCP data, programs and settings. Connectivity ready
- 6-point multi sensor core temperature probe
- Double glass door with LED lights
- Stainless steel construction throughout
- Supplied with n.1 tray rack 2/1 GN, 67 mm pitch.

#### **Main Features**

- Built-in steam generator for highly precise humidity and temperature control according to the chosen settings.
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- Dry, hot convection cycle (25 °C 300 °C): ideal for low humidity cooking.
- Combination cycle (25 °C 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- Low temperature Steam cycle (25 °C 99 °C): ideal for sous-vide, re-thermalization and delicate cooking. Steam cycle (100 °C): seafood and vegetables. High temperature steam (25 °C - 130 °C).
- Automatic mode including 9 food families (meat, poultry, fish, vegetables, pasta/rice, eggs, savory and sweet bakery, bread, dessert) with 100+ different pre-installed variants. Through Automatic Sensing Phase the oven optimizes the cooking process according to size, quantity and type of food loaded to achieve the selected cooking result. Real time overview of the cooking parameters. Possibility to personalize and save up to 70 variants per family.
- Cycles\*: Regeneration (ideal for banqueting on plate or rethermalizing on tray), Low Temperature Cooking (to minimize weight loss and maximize food quality) Patented US7750272B2 and related family, Proving cycle, EcoDelta cooking, cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber, Sous-vide cooking, Static Combi (to reproduce traditional cooking from static oven), Pasteurization of pasta, Dehydration cycles (ideal for drying fruits, vegetables, meats, seafood), Food Safe Control (to automatically monitor safety of cooking process in compliance with HACCP hygienic standards) Patented US6818865B2 and related family, Advanced Food Safe Control (to drive the cooking with pasteurization factor).
- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be group in 16 different categories to better organize the menu. 16-step cooking programs also available.
- MultiTimer function to manage up to 20 different cooking cycles at the same time, improving flexibility and ensuring excellent cooking results. Can be saved up to 200 MultiTimer programs.
- Fan with 7 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- 6-point multi sensor core temperature probe for maximum precision and food safety.
- Pictures upload for full customization of cooking cycles.
- Automatic fast cool down and pre-heat function.
- Different chemical options available: solid (phosphate-free), liquid (requires optional accessory).

#### APPROVAL:





- GreaseOut: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- Capacity: 6 GN 2/1 or 12 GN 1/1 trays.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber.

#### Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Seamless hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- Integrated spray gun with automatic retracting system for fast rinsing.
- IPX 5 spray water protection certification for easy cleaning.
- Supplied with n.1 tray rack 2/1 GN, 67 mm pitch.

#### User Interface & Data Management

- High resolution full touch screen interface (translated in more than 30 languages) - color-blind friendly panel.
- Make-it-mine feature to allow full personalization or locking of the user interface.
- SkyHub lets the user group the favorite functions in the homepage for immediate access.
- MyPlanner works as an agenda where the user can plan the daily work and receive personalized alerts for each task.
- With SkyDuo the Oven and the Blast Chiller are connected to each other and communicate in order to guide the user through the cook&chill process optimizing time and efficiency (requires optional accessory).
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plugin sous-vide probe (optional accessory).
- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).
- Trainings and guidances supporting materials easily accessible by scanning QR-Code with any mobile device.
- Automatic consumption visualization at the end of the cycle.

#### Sustainability



- Human centered design with 4-star certification for ergonomics and usability.
- Wing-shaped handle with ergonomic design and hands-free opening with the elbow, making managing trays simpler (Registered Design at EPO).
- Reduced powerfunction for customized slow cooking cycles.
- SkyClean: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only) and green functions to save energy, water, detergent and rinse aid. Also programmable with delayed start.
- Plan-n-Save function organizes the cooking sequence of the chosen cycles optimizing the work in the kitchen from a time and energy efficiency point of view.
- Zero Waste provides chefs with useful tips for minimizing food waste
  - Zero Waste is a library of Automatic recipes that aims to: give a second life to raw food close to expiration date (e.

- g.: from milk to yogurt)
- obtain genuine and tasty dishes from overripe fruit/vegetables (usually considered not appropriate for sale) promote the use of typically discarded food items (e.g.: carrot peels).
- Energy Star 2.0 certified product.

#### **Optional Accessories**

Optional Accessories		
External reverse osmosis filter for single tank Dishwashers with atmosphere boiler and Ovens	PNC 864388	
• - NOTTRANSLATED -	PNC 920004	
Wheel kit for 6 & 10 GN 1/1 and 2/1 GN oven base (not for the disassembled one)	PNC 922003	
<ul> <li>Pair of AISI 304 stainless steel grids, GN 1/1</li> </ul>	PNC 922017	
<ul> <li>Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1</li> </ul>	PNC 922036	
<ul> <li>AISI 304 stainless steel grid, GN 1/1</li> </ul>	PNC 922062	
<ul> <li>AISI 304 stainless steel grid, GN 2/1</li> </ul>	PNC 922076	
<ul> <li>External side spray unit (needs to be mounted outside and includes support to be mounted on the oven)</li> </ul>	PNC 922171	
<ul> <li>Pair of AISI 304 stainless steel grids, GN 2/1</li> </ul>	PNC 922175	
<ul> <li>Baking tray for 5 baguettes in perforated aluminum with silicon coating, 400x600x38mm</li> </ul>	PNC 922189	
<ul> <li>Baking tray with 4 edges in perforated aluminum, 400x600x20mm</li> </ul>	PNC 922190	
<ul> <li>Baking tray with 4 edges in aluminum, 400x600x20mm</li> </ul>	PNC 922191	
<ul> <li>Pair of frying baskets</li> </ul>	PNC 922239	
<ul> <li>AISI 304 stainless steel bakery/pastry grid 400x600mm</li> </ul>	PNC 922264	
<ul> <li>Double-step door opening kit</li> </ul>	PNC 922265	
<ul> <li>Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1</li> </ul>	PNC 922266	
<ul> <li>USB probe for sous-vide cooking</li> </ul>	PNC 922281	
<ul> <li>Kit universal skewer rack and 6 short skewers for Lengthwise and Crosswise ovens</li> </ul>	PNC 922325	
Universal skewer rack	PNC 922326	
6 short skewers	PNC 922328	
<ul> <li>Smoker for lengthwise and crosswise oven (4 kinds of smoker wood chips are available on request)</li> </ul>	PNC 922338	
Multipurpose hook	PNC 922348	
<ul> <li>4 flanged feet for 6 &amp; 10 GN, 2", 100-130mm</li> </ul>	PNC 922351	
<ul> <li>Grease collection tray, GN 2/1, H=60 mm</li> </ul>	PNC 922357	
<ul> <li>Grid for whole duck (8 per grid - 1,8kg each), GN 1/1</li> </ul>	PNC 922362	
<ul> <li>Tray support for 6 &amp; 10 GN 2/1 disassembled open base</li> </ul>	PNC 922384	
<ul> <li>Wall mounted detergent tank holder</li> </ul>	PNC 922386	
• - NOTTRANSLATED -	PNC 922390	
• - NOTTRANSLATED -	PNC 922421	
• - NOTTRANSLATED -	PNC 922435	
• - NOTTRANSLATED -	PNC 922438	
- NOTTDANGLATED	DNIC 0227.70	

SkyLine PremiumS Natural Gas Combi Oven 6GN2/1













- NOTTRANSLATED -

PNC 922439



•	Slide-in rack with handle for 6 & 10 GN 2/1 oven	PNC 922605		<ul> <li>Exhaust hood with fan for stacking 6+6 PNC 922731 or 6+10 GN 2/1 ovens</li> </ul>	
•	Tray rack with wheels, 5 GN 2/1, 80mm pitch	PNC 922611		<ul> <li>Exhaust hood without fan for 6&amp;10x2/1 PNC 922734 GN oven</li> </ul>	
•	•	PNC 922613		• Exhaust hood without fan for stacking PNC 922736 6+6 or 6+10 GN 2/1 ovens	
•	Cupboard base with tray support for 6 & 10 GN 2/1 oven	PNC 922616		<ul> <li>4 high adjustable feet for 6 &amp; 10 GN PNC 922745 ovens, 230-290mm</li> </ul>	
•	Hot cupboard base with tray support for 6 & 10 GN 2/1 oven holding 5xGN 2/1 trays	PNC 922617		<ul> <li>Tray for traditional static cooking, H=100mm</li> <li>Double-face griddle, one side ribbed</li> <li>PNC 922747</li> </ul>	
•	External connection kit for detergent and rinse aid	PNC 922618		and one side smooth, 400x600mm  • - NOTTRANSLATED - PNC 922752	
•	Stacking kit for gas 6X2/1 GN oven on gas 6&10X2/1 GN oven	PNC 922624		• - NOTTRANSLATED - PNC 922773 • - NOTTRANSLATED - PNC 922776	
•	Stacking kit for gas 6 GN 2/1 oven placed on gas 10 GN 2/1 oven	PNC 922625		Non-stick universal pan, GN 1/1, PNC 925000 H=20mm	
•	Trolley for slide-in rack for 6 & 10 GN 2/1 oven and blast chiller freezer	PNC 922627		Non-stick universal pan, GN 1/1, PNC 925001 H=40mm	
•	Trolley for mobile rack for 2 stacked 6 GN 2/1 ovens on riser	PNC 922629		Non-stick universal pan, GN 1/1, PNC 925002 H=60mm	
•	Trolley for mobile rack for 6 GN 2/1 on 6 or 10 GN 2/1 ovens	PNC 922631		<ul> <li>Double-face griddle, one side ribbed and one side smooth, GN 1/1</li> </ul>	
•	Riser on feet for stacked 2x6 GN 2/1 ovens	PNC 922633		<ul> <li>Aluminum grill, GN 1/1 PNC 925004</li> <li>Frying pan for 8 eggs, pancakes, PNC 925005</li> </ul>	
•	Riser on wheels for stacked 2x6 GN 2/1 ovens, height 250mm	PNC 922634		hamburgers, GN 1/1  • Flat baking tray with 2 edges, GN 1/1  PNC 925006	
•	Stainless steel drain kit for 6 & 10 GN oven, dia=50mm	PNC 922636		• Potato baker for 28 potatoes, GN 1/1 PNC 925008	
•	Plastic drain kit for 6 &10 GN oven, dia=50mm	PNC 922637		<ul> <li>Compatibility kit for installation on previous base GN 2/1</li> </ul>	
	Trolley with 2 tanks for grease collection	PNC 922638		• *NOT TRANSLATED* PNC 0S2394	
	Grease collection kit for open base (2 tanks, open/close device and drain)	PNC 922639		• *NOTTRANSLATED* PNC 0S2395	
•	Wall support for 6 GN 2/1 oven	PNC 922644			
•	Dehydration tray, GN 1/1, H=20mm	PNC 922651			
	Flat dehydration tray, GN 1/1	PNC 922652			
	Open base for 6 & 10 GN 2/1 oven, disassembled	PNC 922654	ā		
•	Heat shield for 6 GN 2/1 oven	PNC 922665			
•	Heat shield-stacked for ovens 6 GN 2/1 on 6 GN 2/1	PNC 922666			
	Heat shield-stacked for ovens 6 GN 2/1 on 10 GN 2/1	PNC 922667			
•	Kit to convert from natural gas to LPG	PNC 922670			
•	Kit to convert from LPG to natural gas	PNC 922671			
•	Flue condenser for gas oven	PNC 922678			
•	Fixed tray rack, 5 GN 2/1, 85mm pitch	PNC 922681			
	Kit to fix oven to the wall	PNC 922687			
	Tray support for 6 & 10 GN 2/1 open base	PNC 922692	ū		
•	4 adjustable feet with black cover for 6 & 10 GN ovens, 100-115mm	PNC 922693			
•	Detergent tank holder for open base	PNC 922699			
	Tray rack with wheels, 6 GN 2/1, 65mm pitch (included)	PNC 922700			
•	- NOTTRANSLATED -	PNC 922706			
•	Mesh grilling grid	PNC 922713			
	Probe holder for liquids	PNC 922714			
	Exhaust hood with fan for 6 & 10 GN 2/1		_		
	GN ovens		_		
























CWII Cold Water inlet 1 CWI2 Cold Water Inlet 2 ΕI Electrical inlet (power)

Gas connection

Drain

DO Overflow drain pipe



#### **Electric**

Circuit breaker required

Supply voltage: 220-240 V/1 ph/50 Hz

Electrical power max.: 1.5 kW Electrical power, default: 1.5 kW

Gas

Total thermal load: 109088 BTU (32 kW)

Gas Power: 32 kW

Standard gas delivery: Natural Gas G20

ISO 7/1 gas connection diameter:

1/2" MNPT

#### Water:

Max inlet water supply

30 °C temperature: 3/4" Water inlet "FCW" connection: Pressure, bar min/max: 1-6 bar Chlorides: <20 ppm Conductivity:  $>50 \mu S/cm$ Drain "D": 50mm

Electrolux Professional recommends the use of treated water,

based on testing of specific water conditions.

Please refer to user manual for detailed water quality information

#### Installation:

Clearance: 5 cm rear and Clearance:

right hand sides.

Suggested clearance for 50 cm left hand side. service access:

#### Capacity:

GN: 6 (GN 2/1) Max load capacity: 60 kg

#### **Key Information:**

Door hinges: Right Side External dimensions, Width: 1090 mm External dimensions, Depth: 971 mm External dimensions, Height: 808 mm Weight: 176 kg 176 kg Net weight: Shipping weight: 199 kg 1.28 m<sup>3</sup> Shipping volume:

#### **ISO Certificates**

ISO Standards: 04















