



Electrolux
PROFESSIONAL

High Productivity Cooking Promix Electric Boiling Pan with Stirrer 200lt, 600mm tilting height

ITEM #

MODEL #

NAME #

SIS #

AIA #



232230 (SM6P200)

* NOT TRANSLATED *

Main Features

- High thermal input and fast heat up.
- Curved pan base guarantees that the appliance is also suitable to prepare small quantities of food.
- Safety valve avoids overpressure of the steam in the jacket.
- Safety thermostat protects against low water level.
- Compliant to CE requirements for safety.
- Constructed to meet the highest hygiene standards.
- Fast working thanks to the high efficient heating technology and well insulation that keeps the heat inside the well.
- Isolated upper well rim avoids risk of harm for the user.
- Electronic control with possibility to store up to 50 programs, large display for easy use and a complete control over the following functions: start, cooking time, temperature, water filling and mixing speed.
- Food is uniformly heated through the base and side walls of the pan by an indirect heating system which uses integrally generated saturated steam at a temperature of 120°C in a jacket with an automatic deaeration system.
- OPTIONS (to be ordered with the machine and must be installed in the factory):
 - Automatic water filling - makes it possible to preset the desired quantity of water
 - Automatic cooling - allows cooling down of the food
- 600 mm tilting height minimum.
- Safe thanks to the higher water protection IPX5 and the lower temperature outside the panels.

Construction

- Vessel can be tilted beyond 90° to completely empty the food.
- Motorised tilting.
- Ergonomic and user friendly thanks to the high tilting position and the pouring lip design which allow to easily fill containers.
- Variable speed agitator moves at up to 170 rpm (for 100 to 150 liters) and up to 140 rpm (for 200 to 300 liters) and is strong and fast enough to mix even compact food, such as mashed potatoes.
- Max pressure 1,5 bar.
- Heavy duty, balanced stainless steel lid with sliding plastic cover to insert ingredients. Easy to remove and turn to facilitate cleaning.
- Tilting axis located at the front and upper position of the pan to keep the pouring path short when filling different types of vessels.
- AISI 304 stainless steel construction with AISI 316 stainless steel deep drawn pan with rounded edges.

Sustainability

- High-quality thermal insulation of the pan saves energy and keeps operating ambient temperature low.



APPROVAL: _____




Experience the Excellence
www.electroluxprofessional.com
ELUX_EMAIL

Optional Accessories


- | | | |
|--|------------|--------------------------|
| • Strainer 200lt | PNC 928027 | ☐ |
| • Kit for a correct and easy positioning and installation of 150-300 lt pan (for a correct installation you need 2 for each pan) | PNC 928030 | ☐ |
| • Floor fastening kit for left leg/column (fastening is integrated in the floor) | PNC 928031 | ☐ |
| • Floor fastening kit for 150-300 lt right leg/column (fastening is integrated in the floor) | PNC 928033 | ☐ |
| • Floor fastening kit for left leg/column (fastening on the floor surface) | PNC 928034 | ☐ |
| • Floor fastening kit for 150-300 lt right leg/column (fastening on the floor surface) | PNC 928036 | ☐ |
| • Trolley to store tools for 5 boiling pans | PNC 928043 | ☐ |
| • Trolley to store tools for 2 boiling pans | PNC 928044 | ☐ |
| • Distance ring for connection (to previous version of pan) | PNC 928049 | ☐ |
| • Short brush for connection to boiling pan spray unit | PNC 928082 | ☐ |
| • Long brush for connection to boiling pan spray unit | PNC 928083 | ☐ |
| • Cleaning tool for Promix boiling pans, 150lt | PNC 928126 | ☐ |
| • - NOT TRANSLATED - | PNC 928150 | ☐ |
| • - NOT TRANSLATED - | PNC 928152 | ☐ |
| • - NOT TRANSLATED - | PNC 928160 | ☐ |

High Productivity Cooking Promix Electric Boiling Pan with Stirrer 200lt, 600mm tilting height

Front




Side



CWI = Cold Water inlet 1
 EI = Electrical inlet (power)
 HWI = Hot water inlet

Top



Electric

Supply voltage: 400 V/3N ph/50-60 Hz
 Electrical power max.: 40.5 kW

Installation:

Distance back floor tilted: 620 mm

Key Information:

Working Temperature MIN: 30 °C
 Working Temperature MAX: 121 °C
 Vessel (round) diameter: 742 mm
 Vessel (round) depth: 555 mm
 External dimensions, Width: 1345 mm
 External dimensions, Depth: 1070 mm
 External dimensions, Height: 1050 mm
 Net vessel useful capacity: 200 lt
 Tilting mechanism: Automatic
 Bearing: Front