

Turbo Liquidisers Turbo Liquidiser for Soups - 2 Speed with micro liquidiser

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



602067 (TBM150001)

Stainless steel turbo liquidiser 2 speeds (for soup) with micro liquidiser

Short Form Specification

Item No.

For mixing, liquidising, reducing and emulsifying. Constructed entirely in 18/8 stainless steel. Mounted on a mobile stainless steel trolley. Can be adapted to all recipient shapes: cylindrical, rectangular, etc. The mixer tube is easily removable without tools and can be dismantled in separate parts: tube, shaft, bearing, and rotor. No volt release system. Safety device in non-working position and protective ring for the grinding head. 2 speeds motor: 830 and 1660 rpm. Stainless steel micro liquidiser for fish soup available as an option. Supplied with stainless steel micro liquidiser for kitchen use.

Main Features

- Turbo liquidizer is used to mix, liquidize, reduce and CHAR(10) emulsify vegetable and fish soups, fruit and vegetable purées, liquid pastries and sauces, etc. directly in cooking containers.
- Liquidiser is mounted on a mobile stainless steel trolley and is height adjustable on installation.
- Turbine accelerates the flow of the liquid over the impeller providing a greater throughput and finer grinding.
- Safety device allows the machine to start only when it is in a working position.
- Equipped with protective ring to cover grinding head.
- Suggested for deep and low pans containing between 500 and 1000 liter of liquid.
- Microliquidizer head easily removable and dishwasher safe.
- Remove the micro liquidisers and clean them separately under running water or in a dishwasher.

Construction

- Constructed entirely in stainless steel to offer maximum durability.
- 2 speeds: 830 and 1660 rpm.
- Power: 4500 W.
- IP55 electrical controls and IP34 overall machine.

Included Accessories

• 1 of Stainless steel micro PNC 653243 liquidiser for TBM150 (kitchen)

Optional Accessories

- Stainless steel micro liquidiser PNC 650043 ☐ for TBM150 (fish soup)
- Stainless steel micro liquidiser PNC 653243 ☐ for TBM150 (kitchen)

APPROVAL:





Turbo Liquidisers Turbo Liquidiser for Soups - 2 Speed with micro liquidiser

Front Side EI = Electrical inlet (power) Top

CE comus intertek Intertek

Electric

Supply voltage:

602067 (TBM150001) 380-415 V/3 ph/50 Hz

Electrical power max.: 4.5 kW
Total Watts: 4.5 kW

Key Information:

External dimensions, Width: 663 mm
External dimensions, Depth: 1852 mm
External dimensions, Height: 1475 mm
Shipping weight: 220 kg