

Spin Dryers Vegetable Washer & Spin Dryer, 2/6kg - Programmable

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		

vegetables). Washing speed: 60 rpm - Spin drying speed: 270



660071 (LVA100D)

Food washer and dryer, programmable - load 2/6 kg - washing phase 60 rpm, drying phase 270 rpm

Short Form Specification

Item No.

Combi machine to wash and dry in a unique compact footprint. Constructed in 304 AISI stainless steel, it can operate in automatic or manual mode. Automatic mode: 3 automatic washing cycles, with or without sanitation, pump speed personalization and spin exclusion. Manual mode: cycle time, including continuous mode, and pump speed set by the operator. The washing effect is obtained by combining basket rotation and water turbulence generated by a two speeds pump. Equipped with a $500\,\mathrm{ml}$ frontal tank, to be filled with the sanitising product, automatically introduced via peristaltic pump during the washing. Flat and waterproof (IPX5) touch button control panel. Lid safety micro switch prevents operation when the lid is open during use. Self braking motor is stopping the basket rotation immediately. Very efficient and easy to clean filter system. Self-cleaning cycle and rounded corners of the well facilitate cleaning operations

Supplied with 304 AISI stainless steel basket with small squared holes (5x5 mm).

Load per cycle: 2-3 kg (light vegetables); 6 kg (heavy

APPROVAL:



Experience the Excellence www.electroluxprofessional.com ELUX_EMAIL





Main Features

- Lid microswitch prevents the appliance from operating with the lid open.
- Electromagnetic device stops the machine in 2 seconds if lid is lifted during operation.
- Easy to clean, efficient filter system.
- Automatic operating mode:
 - -3 washing cycles with or without automatic sanitizing function (with the possibility to set pump speed and to exclude the spinning in case of heavy vegetables).
 - -well self-cleaning cycle.
- Self cleaning cycle of the well.
- Load per cycle: 3 kg (light vegetables); 15 kg (heavy vegetables).
- Two turbulence levels (soft for light vegetables, and strong for heavy vegetables).
- Immersion wash or spray wash (tub filled at low level).
- Drain through solenoid valve.
- Peristaltic dispenser to add sanitizing during immersion wash.
- Supplied with:

 AISI 304 stainless steel basket with small square roundish holes (5x5 mm).
- Manual operating mode: CHAR(10)operator can set the time for each step and the pump speed. Continuous cycle is also possible, selecting "cont" mode
- 500 ml tank placed in front of the machine to be filled with the sanitizing product.

Construction

- Bearing frame, external panelling, lid and extractable basket in 304 AISI stainless steel.
- Basket support in corrosion resistant aluminum.
- Spin rotation speed of 270 rpm.
- Two speeds pump for immersion wash and spray wash.





Spin Dryers Vegetable Washer & Spin Dryer, 2/6kg - Programmable



Supply voltage: 230 V/1N ph/50 Hz

Key Information:


External dimensions, Width: 700 mm 700 mm External dimensions, Depth: 1000 mm External dimensions, Height: Shipping weight: 116 kg Well Capacity: 30 It Usable well capacity: 30 It


Load per cycle - light

vegelables: 2-3 kg

Load per cycle - heavy

vegetables: 6 kg 300 RPM **Rotation Speed:**





CWI1 = Cold Water inlet 1

Electrical inlet (power)

