Electrolux PROFESSIONAL

Modular Cooking Range Line 900XP One Well Gas Fryer 23 liter



ITEM #

SIS #

<u>MODEL #</u> NAME #

APPROVAL:





Included Accessories

Included Accessories		
 1 of Door for open base cupboard 1 of 2 half size baskets for 18/23lt well fryers 	PNC 206350 PNC 927223	
Optional Accessories		
 NOT TRANSLATED - 	PNC 200086	
 Junction sealing kit 	PNC 206086	
 Draught diverter 	PNC 206126	
 Matching ring for flue condenser 	PNC 206127	
• 4 wheels, 2 swivelling with brake (700/900XP). It is mandatory to install with base supports for feet/wheels.	PNC 206135	
Flanged feet kit	PNC 206136	
 Pair of side kicking strips (not for refr- freezer base) 	PNC 206180	
 Hygienic lid for 23lt fryers 	PNC 206201	
 Frontal kicking strip for 23lt fryers in two parts 	PNC 206203	
• Extension pipe for oil drainage for 15lt, 18lt, 23lt fryers	PNC 206209	
 Chimney upstand, 400mm 	PNC 206303	
• Flue condenser for 1/2 module, 120 mm diameter	PNC 206310	
 Door for open base cupboard 	PNC 206350	
 Base support for wheels (lateral) for 23lt fryers and pastacookers (900) 		
 Chimney grid net, 400mm 	PNC 206400	
- NOTTRANSLATED -	PNC 206467	
• 2 side covering panels for free standing appliances	PNC 216134	
- NOT TRANSLATED -	PNC 921023	
 Water additive against corrosion for indirect boiling pans 	PNC 927222	
• 2 half size baskets for 18/23lt well fryers	PNC 927223	
Pressure regulator for gas units	PNC 927225	
• 1 full size basket for 18/23lt well fryers	PNC 927226	
Unclogging rod for HD fryers drainage pipe	PNC 927227	
 Oil life saver for 23lt fryers 	PNC 960645	


Electrolux PROFESSIONAL

Modular Cooking Range Line 900XP One Well Gas Fryer 23 liter





EQ = Equipotential screw G = Gas connection



Gas

Тор

21 kW
Natural Gas G20 (20mbar)
LPG;Natural Gas
1/2"

Key Information:

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Usable well dimensions (width): Usable well dimensions (height): Usable well dimensions (depth): Well capacity: Performance*: Thermostat Range: Net weight: Shipping weight: Shipping height: Shipping width: Shipping depth: Shipping volume: *Based on: Certification group:

340 mm 575 mm 400 mm 21 It MIN; 23 It MAX 28.4 kg\hr 120 °C MIN; 190 °C MAX 57 kg 75 kg 1080 mm 480 mm 1020 mm 0.53 m³ ASTM F1361-Deep fat fryers GF91M23

Modular Cooking Range Line 900XP One Well Gas Fryer 23 liter

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.