



Electrolux
PROFESSIONAL

Vegetable Slicer
**TrinityPro Combined Vegetable Slicer/
Cutter Mixer 3,6 Lt - Single Speed - UK
plug**

ITEM #

MODEL #

NAME #

SIS #

AIA #



602162 (COM36G)

* NOT TRANSLATED *

Main Features

- Combined appliance with two functions: vegetable slicer and cutter mixer.
- Equipped with vegetable slicer attachment for slicing, grating, shredding (julienne) as well as dicing and French fries cutting.
- Cutter mixer and emulsifier function included, for fast chopping, mixing, mincing, griding, liquidizing and kneading.
- Equipped with half moon hopper (1,25lt capacity) and 2 small round feed chutes: Ø 25mm and Ø 55mm, for precise slicing of long shaped vegetables.
- Uniform cuts and maximised load capacity, thanks to the design patented lever-pusher.
- Large output chute for efficient ejection. Fits up to 200mm high standard kitchen containers (like GN) under the output chute.
- Continuous feed model.
- Pulse function for quick and precise slicing and grating.
- Ergonomical frontal lever, suitable for left handed and right handed operators.
- Vegetable slicer blade stops when lever pusher is lifted for operator safety.
- Optional discs and grids available of various sizes for slicing, dicing, grating and shredding (diam. 175mm).
- Includes 3,6 liter stainless steel bowl with micro-toothed blades rotor.
- Bowl/lid scraper included for uniform smooth results (emulsifying) and continuous working.
- Transparent lid, with funnel shaped hole, to add ingredients during use.
- All ingredients are processed evenly and quickly thanks to a special movement generated inside the bowl.
- Pulse function to coarse chopping.
- Flat and waterproof control panel with on/off button and pulse function.
- All parts in contact with food are removable without the use of tools, completely dismountable and dishwasher safe.
- Productivity: up to 100 settings per service for vegetable slicer, up to 50 settings per service for cutter mixer function.
- ErgoCert 4-star certification for ergonomic design and ease of use.

APPROVAL:



Experience the Excellence
www.electroluxprofessional.com

Construction

- Food safety assured in accordance to European directives and UK legislation. In addition, materials in contact with food, are BPA-free.
- Product safety conform to European directives, UK legislation and international health and safety standards.
- 1 speed: 1.500 rpm.
- Power: 500 watts.
- Bowl in AISI 304 stainless steel.
- Microtoothed blades in 420 AISI stainless steel and ergonomic scraper in high resistant composite material to ensure consistent mixing.
- IPX5 (IP55) flat panel touch-control, waterproof panel.
- Main switch ON/OFF on the back of the appliance.
- Asynchronous industrial motor with no brushes for high reliability and quiet functioning, stainless steel motor shaft.

• - NOT TRANSLATED -	PNC 650226	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650227	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650228	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650229	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650230	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650231	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650232	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650233	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650234	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650235	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650236	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650237	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650245	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 653632	<input type="checkbox"/>



Included Accessories

• 1 of - NOT TRANSLATED -	PNC 650118
• 1 of - NOT TRANSLATED -	PNC 650232
• 1 of - NOT TRANSLATED -	PNC 650233
• 1 of - NOT TRANSLATED -	PNC 650235
• 1 of - NOT TRANSLATED -	PNC 650236



Optional Accessories

• - NOT TRANSLATED -	PNC 650110	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650117	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650118	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650196	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650197	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650198	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650199	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650205	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650207	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650208	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650209	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650210	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650211	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650213	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650214	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650215	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650216	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650217	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650218	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650219	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650220	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650221	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650222	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650223	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650224	<input type="checkbox"/>
• - NOT TRANSLATED -	PNC 650225	<input type="checkbox"/>

Front





Side



EI = Electrical inlet (power)

Top



Electric

Supply voltage:	220-240 V/1N ph/50 Hz
Electrical power max.:	0.5 kW
Total Watts:	0.5 kW

Capacity:

Performance (up to):	150 kg\hour
Capacity:	3.6 litres

Key Information:

External dimensions, Width:	348 mm
External dimensions, Depth:	334 mm
External dimensions, Height:	527 mm
Shipping weight:	19 kg