



## High Speed Equipment GourmeXpress High Speed Oven, black 380-415V/3N/50Hz

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_



603952  
(EPRPROBTD)

\* NOT TRANSLATED \*

### Main Features

- Ventless equipment, can be installed without extraction hood. Perfect for front house cooking (see handbook for more details).
- Adjustable temperature control from 30°C to 280°C.
- Adjustable impingement speed from 10% to 100% with 10% increment.
- Adjustable microwave power from 0% to 100% with 10% increment. With 0% microwave it can be used as a convection oven.
- Easy to use 5" capacitive touchscreen user interface where up to 1024 recipes can be stored.
- It is possible to create multiphase recipes with different combinations of temperature, microwave and impingement for each phase.
- For easier recipe management each recipe can be linked to:
  - a dedicated session (i.e. breakfast, lunch, dinner, etc.)
  - a customized image
  - a bar code, to be retrieved with a bar code scanner (available as an optional accessory PNC 653820)
- Countdown display and buzzer with adjustable volume at the end of the cycle (or phase in case of multiphase recipes).
- Prearranged for USB memory stick data transfer.
- [NOT TRANSLATED]
- [NOT TRANSLATED]

### Construction

- AISI 304 stainless steel cooking chamber with all rounded corners for easy cleaning.
- Compact footprint with a wide 17-liter cooking chamber.
- Removable easy to clean top and bottom hot air jet plates.
- Catalytic filters, removable and replaceable.
- Easy to access air filter.
- Ergonomic door handle.
- 2" adjustable feet.
- IPX3 protected.
- Shovel shelf rack on top of the oven.

### Included Accessories

- 1 of Non-stick Teflon sample basket for GourmeXpress High Speed Oven PNC 653816
- 1 of Non-stick Teflon sample mesh basket for GourmeXpress High Speed Oven PNC 653817
- 1 of Aluminium shovel for GourmeXpress High Speed Oven PNC 653819

### Optional Accessories

- LABEL PRINTER, BLUETOOTH (FOR 50X60 MM LABELS), DISPLAY ENG/ITA (MANAGED VIA DEDICATED APP) PNC 650243

APPROVAL: \_\_\_\_\_



Experience the Excellence  
[www.electroluxprofessional.com](http://www.electroluxprofessional.com)

- - NOT TRANSLATED -


PNC 653820

### Recommended Detergents

- S02 DEGREASER 6pzx750ml -  
ADR&IMDG Limited Quantity


PNC 0S2882

Front



Front


Side



Side


EI = Electrical inlet (power)  
 EO = Electrical Outlet

Top



Side (door open)

Distances



### Electric

Supply voltage:	380-415 V/3N ph/50 Hz
Rated amps:	14.5 A
Total Watts:	5.8 kW
Plug type:	Cable without plug

### Installation:

Clearance: 60 mm from side, 140 mm from top

### Key Information:

Net Volume:	17 lt
Total Power:	5.8 kW
Power of Microwave:	2.2kW
- 2 magnetron	
Power of Convection:	5.5 kW
Power details:	
Oven working Temperature:	30 °C MIN; 280 °C MAX
Oven Cavity Dimensions (width):	317 mm
Oven Cavity Dimensions (height):	193 mm
Oven Cavity Dimensions (depth):	294 mm
External dimensions, Width:	460 mm
External dimensions, Depth:	710 mm
External dimensions, Height:	660 mm
Net weight:	81 kg
Shipping weight:	107 kg
Shipping height:	740 mm
Shipping width:	560 mm
Shipping depth:	760 mm
Shipping volume:	0.31 m <sup>3</sup>
Controls:	5" Capacitive Touchscreen Display 1024 Cooking Programs