

Modular Cooking Range Line 700XP 2-Hot Plates Electric Boiling Top Range

ITEM # _____
 MODEL # _____
 NAME # _____
 SIS # _____
 AIA # _____



371014 (E7ECED2R00) 2-hot plate (2,6 kW each)
electric boiling top

371126 (E7ECED2R0N) 2-hot plate (2,6 kW each)
electric boiling top

Short Form Specification

Item No. _____

To be installed on open base installations, bridging supports or cantilever systems. Two 2.6 kW cast-iron hot plates hermetically sealed to the one-piece top. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 m

Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- The two 2.6kW cast-iron plates are hermetically sealed to the one-piece top.
- The special design of the control knob system guarantees against water infiltration.
- IPx4 water protection.
- Suitable for countertop installation.

Construction


- External panel in Stainless Steel with Scotch Brite finish.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Optional Accessories


- Junction sealing kit PNC 206086 ☐
- Support for bridge type system, 800mm PNC 206137 ☐
- Support for bridge type system, 1000mm PNC 206138 ☐
- Support for bridge type system, 1200mm PNC 206139 ☐
- Support for bridge type system, 1400mm PNC 206140 ☐
- Support for bridge type system, 1600mm PNC 206141 ☐
- Support for bridge type system, 400mm PNC 206154 ☐
- Water coulmun with swivel arm (water column extension not included) PNC 206289 ☐
- Water column extension for 700 line PNC 206291 ☐
- Chimney upstand, 400mm PNC 206303 ☐
- Right and left side handrails PNC 206307 ☐
- BACK HANDRAIL 800 MM - MARINE PNC 206308 ☐
- Chimney grid net, 400mm PNC 206400 ☐
- Frontal handrail 400mm PNC 216046 ☐
- Frontal handrail 800mm PNC 216047 ☐
- Frontal handrail 1200mm PNC 216049 ☐
- Frontal handrail 1600mm PNC 216050 ☐
- Large handrail - portioning shelf, 400mm PNC 216185 ☐
- Large handrail - portioning shelf, 800mm (only for 371126) PNC 216186 ☐
- 2 side covering panels for top appliances PNC 216277 ☐
- 1 full size basket for 14/15lt fryers (only for 371126) PNC 921691 ☐

APPROVAL: _____

Front




Side



EI = Electrical inlet (power)
 EQ = Equipotential screw

Top



Electric

Supply voltage:

371014 (E7ECED2R00)

380-400 V/3 ph/50-60 Hz

371126 (E7ECED2R0N)

230 V/3 ph/50/60 Hz

Predisposed for:

Total Watts:

5.2 kW

Key Information:

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

External dimensions, Width: 400 mm

External dimensions, Depth: 730 mm

External dimensions, Height: 250 mm

Net weight: 20 kg

Shipping weight:

371014 (E7ECED2R00)

23.75 kg

371126 (E7ECED2R0N)

24 kg

Shipping height:

371014 (E7ECED2R00)

520 mm

371126 (E7ECED2R0N)

540 mm

Shipping width:

460 mm

Shipping depth:

371014 (E7ECED2R00)

800 mm

371126 (E7ECED2R0N)

820 mm

Shipping volume:

371014 (E7ECED2R00)

0.19 m³

371126 (E7ECED2R0N)

0.2 m³

Certification group:

371014 (E7ECED2R00)

EH72T

371126 (E7ECED2R0N)

N7CE1

Front Plates Power:

2.6 - 0 kW

Back Plates Power:

2.6 - kW

Front Plates dimensions:

Ø 230

Back Plates dimensions:

Ø 230