

Modular Cooking Range Line 700XP 4 Hot Plate Electric Induction Cooking Top Range

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	



371021 (E7INEH4000)

4-zone (3,5 kW each) electric induction cooking

top

371132 (E7INEH400N)

4-zone (3,5 kW each) electric induction cooking top

Short Form Specification

Item No.

6 mm thick glass ceramic cooking surface with 4 independently controlled 3.5 kW induction zones. Induction top surface with seamless transition between individual heating zones. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- 6mm glass ceramic cooking surface with 4 independently controlled induction zones with a power of 3.5 kW per zone.
- Almost the entire surface of the ceramic plate can be used without "dead" spots.
- Indicating lamp for each zone located on control console.
- Induction plates endowed with overheating safety device.
- Power to the individual zones can be set with progressive output i.e. fine regulation at the lower and larger progress at the upper levels.
- Low heat dissipation to the kitchen.
- The smooth, glass ceramic plate is not directly heated, so there is no burning on cooking surface.
- IPx4 water protection.
- Pots diameter to be used: min 12cm, max 28 cm in order to obtain maximum heating efficiency.
- Suitable for countertop installation.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

Sustainability



• This model is compliant with Swiss Energy Efficiency Ordinance (730.02).

Optional Accessories

• GN2/1 chrome grid for static oven (only for 371021)	PNC 164250 □
 Scraper for smooth plate fry tops (only for 371132) 	PNC 164255 🗅
 Support for bridge type system, 800mm 	PNC 206137 🗖
 Support for bridge type system, 1000mm 	PNC 206138 🗖
 Support for bridge type system, 1200mm 	PNC 206139 🗖
 Support for bridge type system, 1400mm 	PNC 206140 🗖
 Support for bridge type system, 1600mm 	PNC 206141 🗖
• Water column extension for 700 line	PNC 206291 🗖
• Chimney upstand, 800mm	PNC 206304 🗖

APPROVAL:





Modular Cooking Range Line 700XP 4 Hot Plate Electric Induction Cooking Top Range

 Chimney grid net, 400mm 	ı P	NC :	206400	
• 2 side covering panels fo appliances	rtop P	NC :	216277	
 Stainless steel universal fr with stainless steel handle 200mm) suitable for inductal all other heating sources 	e (diam.	NC	653596	
 Universal frying pan with steel handle (diam. 240m for induction and all othe sources 	m) suitable	NC	653597	
 Universal frying pan with steel handle (diam. 280m for induction and all othe sources 	m) suitable	NC	653598	





Modular Cooking Range Line 700XP 4 Hot Plate Electric Induction Cooking Top Range

Front Α0 :@ 30 5/8 " 778 mm 0 7/16 " 0 7/16 11 mm 11 mm Side Α0 15/16 E 1/16 74 332 251 3 7/16 **EQ** 15/16 37 ΕI 24 4 1/16 " 103 mm 17 11/16 " 149 mm 450 mm Electrical inlet (power) **Equipotential screw** Top Α0 730 8 31 1/2 ' 800 mm

Electric

Supply voltage:

371021 (E7INEH4000) 380-415 V/3 ph/50/60 Hz **371132 (E7INEH400N)** 230 V/3 ph/50/60 Hz

Predisposed for:

380-415V 3~ 50/60Hz

371021 (E7INEH4000) 14kW **Total Watts:** 14 kW

Key Information:

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Induction compatible pots & pans must be used.

External dimensions, Width: 800 mm
External dimensions, Depth: 730 mm
External dimensions, Height: 250 mm
Net weight: 57 kg

Shipping weight:

371021 (E7INEH4000) 65 kg **371132 (E7INEH400N)** 67 kg

Shipping height:

 371021 (E7INEH4000)
 530 mm

 371132 (E7INEH400N)
 520 mm

 Shipping width:
 820 mm

 Shipping depth:
 860 mm

 Shipping volume:
 0.37 m³

Certification group:

371021 (E7INEH4000) IH740 **371132 (E7INEH400N)** NIN87F

Induction Top Dimensions

(width): 800 mm

Induction Top Dimensions

(depth): 730 mm

